

## Article

# Adaptive Dual-Anchor Fusion Framework for Robust SOC Estimation and SOH Soft-Sensing of Retired Batteries with Heterogeneous Aging

Hai Wang <sup>1</sup>, Rui Liu <sup>1,2</sup>, Yupeng Guo <sup>1,2</sup>, Yijun Liu <sup>1</sup>, Jiawei Chen <sup>1,2</sup>, Yan Jiang <sup>1,\*</sup> and Jianying Li <sup>1</sup>

<sup>1</sup> School of Mechanical and Automotive Engineering, Zhaoqing University, Zhaoqing 526000, China; wanghai\_sky@126.com (H.W.); lruiooo2022@163.com (R.L.); guoyupengwork@163.com (Y.G.); 19339141044@163.com (Y.L.); chenjw0203@163.com (J.C.); lijianying@zqu.edu.cn (J.L.)

<sup>2</sup> School of Electronic and Electrical Engineering, Zhaoqing University, Zhaoqing 526000, China

\* Correspondence: jiangyan128@zqu.edu.cn

## Abstract

Reliable state estimation is critical for the safe operation of second-life battery systems but is severely hindered by significant parameter heterogeneity arising from diverse historical aging conditions. Traditional static models struggle to adapt to such variability, while online identification methods are prone to divergence under dynamic loads. To overcome these challenges, this paper proposes a Dual-Anchor Adaptive Fusion Framework for robust State of Charge (SOC) estimation and State of Health (SOH) soft-sensing. Specifically, to establish a reliable physical baseline, an automated Dynamic Relaxation Interval Selection (DRIS) strategy is introduced. By minimizing the fitting Root Mean Square Error (RMSE), DRIS systematically extracts high-fidelity parameters to construct two “anchor models” that rigorously define the boundaries of the aging space. Subsequently, a residual-driven Bayesian fusion mechanism is developed to seamlessly interpolate between these anchors based on real-time voltage feedback, enabling the model to adapt to uncalibrated target batteries. Concurrently, a novel “SOH Soft-Sensing” capability is unlocked by interpreting the adaptive fusion weights as real-time health indicators. Experimental results demonstrate that the proposed framework achieves robust SOC estimation with an RMSE of 0.42%, significantly outperforming the standard Adaptive Extended Kalman Filter (A-EKF, RMSE 1.53%), which exhibits parameter drift under dynamic loading. Moreover, the a posteriori voltage tracking residual is compressed to ~0.085 mV, effectively approaching the hardware’s ADC quantization limit. Furthermore, SOH is inferred with a relative error of 0.84% without additional capacity tests. This work establishes a robust methodological foundation for calibration-free state estimation in heterogeneous retired battery packs.

Academic Editor: Stefan Adams

Received: 28 December 2025

Revised: 28 January 2026

Accepted: 30 January 2026

Published: 1 February 2026

**Keywords:** retired lithium-ion battery; state of charge (SOC) estimation; SOH Soft-sensing; dual-anchor adaptive fusion; dynamic relaxation interval selection (DRIS); parameter identification

**Copyright:** © 2026 by the authors.

Licensee MDPI, Basel, Switzerland.

This article is an open access article distributed under the terms and conditions of the [Creative Commons Attribution \(CC BY\) license](https://creativecommons.org/licenses/by/4.0/).

## 1. Introduction

With the rapid expansion of the electric vehicle (EV) market, the sustainable management of retired lithium-ion batteries—often referred to as “second-life” batteries—has

emerged as an important economic and environmental topic in battery management [1–5]. Globally, and particularly in dominant markets like China, the industry is entering a critical stage of large-scale battery retirement. Driven by government regulations and traceability-oriented management, “echelon utilization” has been actively promoted for stationary storage and backup-power applications, aiming to improve resource efficiency [6]. However, unlike fresh battery packs with uniform properties, retired modules exhibit significant cell-to-cell heterogeneity in their State of Health (SOH) and impedance characteristics, stemming from diverse historical operating conditions and thermal gradients [7–12]. This inconsistency poses a fundamental dilemma: retired modules often exhibit incomplete usage history and highly dispersed degradation states, making fast screening and safe operation considerably difficult [13].

Accurate state estimation is a prerequisite for managing such heterogeneity in embedded Battery Management Systems (BMS). In China, growing attention has been devoted to these challenges, reflected in a stable increase in related patent applications [14]. In practice, research and industrial efforts in China broadly follow two complementary streams—material recycling and echelon utilization—aiming at element recovery and residual-value maximization, respectively. While material recycling technologies (e.g., hydrometallurgy) focus on element recovery [15], echelon utilization aims to maximize the remaining value of the battery. For the latter, rapid sorting methods based on feature-based sorting and clustering methods have been investigated to classify retired cells with similar static characteristics [16]. Simultaneously, for online applications, model-based state estimation has been recognized as a key enabling technique for echelon-utilization BMS, with increasing emphasis on robust SOC/SOH estimation and engineering-oriented BMS management under parameter dispersion [17]. Despite these advances, a clear gap remains between academic methods and engineering needs: many existing approaches for second-life scenarios still rely on intensive calibration—such as periodic full-capacity tests, full OCV curve characterization, or long rest periods—or are validated under relatively controlled conditions. Consequently, embedded, calibration-light, and robustness-oriented state estimation for heterogeneous retired cells under dynamic loads is still limited.

From a methodological perspective, two major technical routes are commonly adopted to address these issues: (i) continuously tracking battery dynamics via online parameter identification, such as Recursive Least Squares (RLS) and Adaptive Extended Kalman Filters (A-EKFs) [18–26]; and (ii) utilizing data-driven models, such as Support Vector Regression (SVR) or neural networks [27,28]. While online identification theoretically reduces modeling mismatch, it suffers from high computational burdens and divergence risks under weak excitation, and is particularly sensitive to aging-induced parameter drift in retired cells. Similarly, although data-driven approaches deliver high accuracy on specific datasets, they often function as “black boxes” with poor interpretability and require massive labeled training data, which is unavailable for retired batteries with unknown histories.

To enhance robustness without the drawbacks of the above methods, multi-model fusion strategies, such as the Interacting Multiple Model (IMM) algorithm [29,30], offer a promising pathway by interpolating between pre-defined models. However, traditional IMM approaches often require a large bank of pre-calibrated models and complex transition probability matrices, leading to high computational costs. More critically, the efficacy of any fusion strategy relies entirely on the fidelity of its base models (anchors). In offline identification using standard Hybrid Pulse Power Characterization (HPPC) tests, researchers face a critical, yet often overlooked, challenge which we term the “E-point selection dilemma”. Arbitrary truncation of the relaxation curve leads to a fundamental

trade-off: short intervals cause underfitting of slow polarization dynamics, while excessively long intervals induce overfitting of measurement noise. This dilemma compromises the physical fidelity of Equivalent Circuit Models (ECMs), rendering them unreliable as baselines for fusion algorithms.

To systematically resolve these interconnected challenges, this paper proposes a comprehensive Adaptive Dual-Anchor Fusion Framework. First, we introduce an automated Dynamic Relaxation Interval Selection (DRIS) strategy. By minimizing the fitting Root Mean Square Error (RMSE) over a dynamic window, DRIS rigorously extracts high-fidelity parameters to construct robust “anchor models” representing the boundaries of the aging space (e.g., an aged anchor and a healthy anchor). Building on these solid foundations, a residual-driven Bayesian fusion mechanism is developed to dynamically interpolate between anchors, enabling the BMS to adapt to uncalibrated target batteries.

The main contributions of this work are three-fold:

1. Resolution of the “E-point Selection Dilemma”: An innovative automated DRIS strategy is proposed to replace empirical data truncation. It ensures the construction of physically meaningful anchor models that accurately capture electrochemical dynamics without noise corruption.
2. Cost-Effective Solution for Heterogeneity: A “Modeling by Boundary” concept is introduced. The observability and stability of the proposed dual-anchor framework are rigorously verified mathematically, ensuring its feasibility for control systems. We demonstrate at the cell level that robust state estimation can be achieved using only two extreme anchor models, offering a scalable pathway to reduce calibration effort compared to building a massive model library.
3. Physics-Informed SOH Soft-Sensing: A novel soft-sensing capability is discovered and validated. The adaptive fusion weights are shown to inherently reflect the battery’s health status, allowing for real-time SOH inference under dynamic loads without requiring full calibration cycles or offline capacity tests during operation.


## 2. High-Fidelity Anchor Model Construction via DRIS

### 2.1. Second-Order RC Equivalent

To accurately capture the dynamic electrochemical characteristics of retired lithium-ion batteries, the second-order RC Equivalent Circuit Model (ECM) is employed. As a trade-off between computational complexity and physical fidelity, this model structure is widely adopted in BMS applications [31,32]. As shown in Figure 1, the electrical behavior is governed by Kirchhoff’s laws.

To ensure consistency with the convention used by the experimental testing equipment, the sign convention for current is defined globally throughout this paper: current is considered positive for charging and negative for discharging. All subsequent equations and analyses adhere to this convention.

Based on Kirchhoff’s Voltage Law (KVL) and Current Law (KCL), the electrical behavior of this model is described by Equations (1) and (2):



**Figure 1.** Schematic of the second-order RC equivalent circuit model.

$$\begin{cases} \dot{U}_1 = -\frac{1}{R_1 C_1} U_1 + \frac{1}{C_1} I(t) \\ \dot{U}_2 = -\frac{1}{R_2 C_2} U_2 + \frac{1}{C_2} I(t) \end{cases} \quad (1)$$

$$U_t(t) = U_{OCV}(z) + U_1(t) + U_2(t) + I(t)R_0 \quad (2)$$


where  $U_t$  denotes the terminal voltage, and  $I$  (labeled as  $I_t$  in Figure 1, with the arrow indicating the positive charging direction) is the load current.  $U_{OCV}(z)$  represents the open-circuit voltage as a function of  $SOC(z)$ .  $R_0$  is the ohmic resistance, while  $(R_1, C_1)$  and  $(R_2, C_2)$  characterize the lumped polarization dynamics with different time constants. Since these parameters can vary significantly with the battery's aging state and operating conditions, a robust identification strategy is essential.

It is worth noting that while the adopted circuit topology follows the standard second-order RC structure widely utilized in BMS applications, the “High-Fidelity” designation in this framework pertains specifically to the parameterization methodology rather than a new circuit topology. Conventional identification approaches often rely on empirical, fixed relaxation windows, which may make the identified parameters sensitive to noise and truncation-induced under-/overfitting. In contrast, the anchor models in this work are constructed using parameter sets rigorously extracted via the automated DRIS strategy (detailed in Section 2.3), where an optimal truncation point  $E^*$  is selected by validation error minimization. Therefore, compared with a traditional single second-order ECM identified with a fixed window, our anchor models share the same structure but provide more stable and physically consistent parameter sets that serve as boundary anchors for subsequent fusion.

## 2.2. The “E-point Selection Dilemma” in Parameter Identification

Parameter identification is essentially an inverse problem that extracts physical parameters from voltage relaxation curves. In a standard Hybrid Pulse Power Characterization (HPPC) test [33,34], the relaxation phase spans from the moment the current is cut off (Point D) to a stable equilibrium state (Point E).

However, defining the optimal cutoff time for Point E is a critical, yet often overlooked, challenge, which we term the “E-point selection dilemma”. The choice of the data window length involves a fundamental trade-off between signal integrity and noise corruption. As illustrated in Figure 2, this dilemma manifests in two distinct failure modes:




**Figure 2.** Magnified View of a Single Cycle from the HPPC Test Profile.

1. Underfitting (Short Interval): If the selected interval (D–E) is too short, the data fails to capture the slow polarization dynamics governed by the large time constant  $\tau_2$  (concentration polarization). The identification algorithm consequently “forces” a fit to the incomplete transient, resulting in significant estimation errors for  $R_2$  and  $C_2$ .
2. Overfitting (Long Interval): Conversely, if the interval is extended too long into the equilibrium tail where the voltage change is minimal, the signal-to-noise ratio (SNR) degrades [35,36]. The algorithm begins to fit the random measurement noise rather than the underlying system dynamics, leading to unstable parameter solutions with high variance.

Therefore, finding the mathematically optimal “E-point” is not trivial but is a prerequisite for obtaining high-fidelity anchor models for the subsequent fusion framework.

### 2.3. Dynamic Relaxation Interval Selection (DRIS) Strategy

To systematically resolve the aforementioned dilemma and extract pure electrochemical parameters, this study employs the Dynamic Relaxation Interval Selection (DRIS) strategy. The core principle of DRIS is to transform the subjective choice of the data cutoff point into an automated optimization problem based on the goodness-of-fit. The complete workflow is depicted in Figure 3.



**Figure 3.** Flowchart of the DRIS Strategy.

The strategy operates by iteratively traversing a set of candidate endpoints,  $\varepsilon = \{E_1, E_2, \dots, E_N\}$ , within the relaxation phase. For each candidate endpoint, a subset of voltage relaxation data  $\Omega(E_i) = \{(t_k, V_k) | t_k \leq E_i\}$  is constructed. Parameter identification is then performed on this subset using a nonlinear least-squares algorithm [37]. To quantitatively evaluate the quality of the identified parameters for each candidate interval, the Root Mean Square Error (RMSE) is calculated as Equation (3):


$$\text{RMSE}(E_i) = \sqrt{\frac{1}{N_{E_i}} \sum_{k \in \Omega(E_i)} [V_k - \hat{V}(t_k; P^*(E_i))]^2} \quad (3)$$

where  $N_{E_i}$  is the number of data points in the subset  $\Omega(E_i)$ , and  $V_k$  is the measured voltage at time step  $k$ . The term  $\hat{V}(t_k; P^*(E_i))$  denotes the model-predicted voltage, calculated using the optimal parameter set  $P^*(E_i)$  identified for the specific cutoff point  $E_i$ . Based on this metric, the optimal E-point,  $E^*$ , is defined as the time point that yields the global minimum of the RMSE curve, as defined in Equation (4):

$$E^* = \arg \min_{E_i \in \varepsilon} \text{RMSE}(E_i) \quad (4)$$

In the implementation, the search space for candidate E-points  $\varepsilon$  covers the entire relaxation period, with a search step interval of 1 s to guarantee high resolution. The efficacy of this strategy is visually analyzed in Figure 4. The top-left subplot validates the 'E-point selection dilemma' via the 'U-shaped' RMSE curve, identifying the optimal window that balances underfitting and noise. At this optimal point, the top-right subplot demonstrates high fitting accuracy—comparing the actual voltage (blue solid line) with the model-fitted voltage (red dashed line)—while the bottom-left subplot confirms minimal residuals. Crucially, the bottom-right subplot (labeled 'Time Constant Trend') demonstrates the evolution of the time constants, denoted as  $\tau_1'$  ( $\tau_1$ ) and  $\tau_2'$  ( $\tau_2$ ), where the

blue and orange lines correspond to  $\tau_1$  and  $\tau_2$ , respectively. Both parameters rapidly converge to stable values near the optimal E-point, verifying the extraction of true electrochemical dynamics.




**Figure 4.** Analysis of the DRIS Strategy for Parameter Identification at a Typical SOC Interval.

#### 2.4. Identification Results for Anchor Boundaries


By applying the DRIS strategy, we successfully constructed two representative anchor models: Anchor A (Aged, SOH  $\approx 0.61$ ) and Anchor B (Healthy, SOH  $\approx 0.80$ ). To verify their fidelity, a rigorous back-testing validation was conducted under the HPPC profile.

First, the performance of the traditional method (using a fixed 2-h relaxation window) is evaluated. As shown in Figure 5, where the red dashed line represents the model simulation and the blue solid line denotes the actual measured voltage, the model exhibits significant voltage prediction deviations. The error subplot reveals large spikes reaching up to 100 mV, confirming that arbitrarily extending the data window introduces excessive measurement noise into the fitting process, thereby degrading parameter accuracy.




**Figure 5.** Verification Results for the Model with Parameters Identified by the Traditional Method.

In contrast, the verification results for the model identified via the proposed DRIS strategy are presented in Figure 6. Consistent with the benchmark comparison, the red simulation curve tracks the blue measured curve closely. By automatically truncating the data at the optimal  $E^*$ , the model achieves a significantly tighter fit. The peak voltage error is suppressed to below 50 mV, and the overall RMSE is reduced from 6.22 mV (Traditional) to 3.39 mV (DRIS). This 45.5% quantitative improvement demonstrates that the DRIS-based anchors provide a much higher fidelity representation of the battery dynamics.



**Figure 6.** Verification Results for the Model with Parameters Identified by the DRIS Strategy.

Finally, the physical consistency of the identified anchors is visually verified in Figure 7.



**Figure 7.** Comparison of identified model parameters ( $R_0$ ,  $R_1$ ,  $R_2$ ,  $\tau_1$ ) for the two anchor boundaries (SOH 0.61 vs. SOH 0.80) across the operating SOC range.

Figure 7 provides a comprehensive comparison of the identified parameters. The results exhibit strong physical consistency and provide a clear envelope for the subsequent fusion:

First, a distinct impedance separation is observed across the entire operating range (20–100% SOC). The aged anchor (Anchor A, red line) consistently exhibits higher ohmic ( $R_0$ ) and polarization resistances ( $R_1$ ,  $R_2$ ) compared to the healthy anchor (Anchor B, blue line). For instance, the  $R_0$  of Anchor A is approximately 25–30% higher, effectively capturing the degradation-induced impedance rise.

Second, despite the magnitude differences, the parameter trajectories of both anchors follow consistent dynamic trends with respect to SOC (e.g., the characteristic peaks in  $R_1$  and  $R_2$  around 40% and 80% SOC). This indicates that the DRIS strategy successfully filters out measurement noise and captures the underlying electrochemical properties of the NCM chemistry.

Third, the time constants ( $\tau$ ) demonstrate excellent stability, avoiding the erratic fluctuations often seen in traditional identification methods. These distinct and stable parameter sets confirm that Anchor A and Anchor B form a reliable boundary space, which is a prerequisite for the proposed adaptive fusion framework.

### 3. Adaptive Dual-Anchor Fusion Framework

#### 3.1. Structure of the Dual-Anchor Observer

Based on the high-fidelity parameters identified via the DRIS strategy in Section 2, we establish two distinct observer models, defined as the “Anchor Models”. Let model  $M_A$  represent the battery state at a lower health condition (e.g., SOH = 0.61) and  $M_B$  represent the state at a higher health condition (e.g., SOH = 0.80).

These two models run in parallel to form a state-estimation envelope. Following the standard discrete-time state-space realization of the second-order (two-RC) Thevenin ECM widely used in model-based battery estimation, we define the state vector as  $x_k = [z_k, U_{1,k}, U_{2,k}]^T$  and update SOC via Coulomb counting. By applying zero-order-hold (ZOH) discretization to the continuous-time polarization dynamics over each sampling interval  $\Delta t$ , the discrete-time state-space equations for the  $i$ -th anchor model ( $i \in \{A, B\}$ ) are formulated as follows. The exponential terms in Equations (7) and (8) arise from the analytical ZOH discretization of the first-order RC polarization dynamics, determined by  $\exp(-\Delta t/\tau)$  with time constants  $\tau_1 = R_1 C_1$  and  $\tau_2 = R_2 C_2$  [38,39].

For the  $i$ -th anchor model  $i \in \{A, B\}$  the discrete state-space equations are formulated as Equations (5) and (6), with the system matrices explicitly defined in Equations (7) and (8):

$$x_{k+1}^{(i)} = A_k^{(i)} x_k^{(i)} + B_k^{(i)} I_k + w_k \quad (5)$$

$$U_{\text{est},k}^{(i)} = U_{\text{OCV}}(z_k^{(i)}) + U_{1,k}^{(i)} + U_{2,k}^{(i)} + I_k R_0^{(i)} \quad (6)$$

$$A_k^{(i)} = \begin{bmatrix} 1 & 0 & 0 \\ 0 & \exp\left(-\frac{\Delta t}{\tau_1^{(i)}}\right) & 0 \\ 0 & 0 & \exp\left(-\frac{\Delta t}{\tau_2^{(i)}}\right) \end{bmatrix} \quad (7)$$

$$B_k^{(i)} = \left[ \frac{\eta \Delta t}{C_n^{(i)}}, R_1^{(i)} \left(1 - e^{-\frac{\Delta t}{\tau_1^{(i)}}}\right), R_2^{(i)} \left(1 - e^{-\frac{\Delta t}{\tau_2^{(i)}}}\right) \right]^T \quad (8)$$

Here,  $C_n^{(i)}$  is the calibrated capacity of the  $i$ -th anchor model.  $\eta$  represents the Coulombic efficiency. Since the focus of this study is on the fusion algorithm and the battery operates within a normal temperature range,  $\eta$  is assumed to be unity, as the validation is performed under controlled laboratory conditions with negligible side reactions. The system matrices  $A^{(i)}$  and  $B^{(i)}$  are populated using the high-fidelity physical parameters  $(\tau_1^{(i)}, \tau_2^{(i)}, R_1^{(i)}, R_2^{(i)}, R_0^{(i)}, C_n^{(i)})$  rigorously extracted via the DRIS strategy in Section 2.

Critically, unlike traditional adaptive filters that tune parameters online (which risks divergence), the parameters in our anchor models are fixed. The adaptation is achieved solely through the dynamic weighting mechanism described below.

### 3.2. Observability and Stability Analysis of the Anchor Models

Before implementing the fusion estimation, it is essential to verify the observability and stability of the discrete-time state-space models constructed in Section 3.1. These properties determine whether the internal states (SOC and polarization voltages) can be accurately reconstructed from the terminal voltage measurements and whether the estimation error remains bounded.

The system described by Equations (5) and (6) is locally linearized at each time step  $k$ . The Jacobian matrix of the measurement equation  $C_k$  with respect to the state vector  $x_k = [z_k, U_{1,k}, U_{2,k}]^T$  is defined as:

$$C_k = \left[ \left. \frac{\partial U_{OCV}}{\partial z} \right|_{z=z_k}, 1, 1 \right] \quad (9)$$

Let  $A_k$  be the state transition matrix defined in Equation (7). Substituting the diagonal matrix  $A_k = \text{diag}(1, e^{-\Delta t/\tau_1}, e^{-\Delta t/\tau_2})$ , the observability matrix  $O_k$  expands to:

$$O_k = \begin{bmatrix} \frac{dOCV}{dz} & 1 & 1 \\ \frac{dOCV}{dz} & e^{-\frac{\Delta t}{\tau_1}} & e^{-\frac{\Delta t}{\tau_2}} \\ \frac{dOCV}{dz} & e^{-\frac{2\Delta t}{\tau_1}} & e^{-\frac{2\Delta t}{\tau_2}} \end{bmatrix} \quad (10)$$

For the system to be observable, the observability matrix must be full rank, i.e.,  $\text{rank}(O_k) = 3$ . By performing Gaussian elimination, it can be proven that the rank condition is satisfied if and only if the slope of the OCV curve  $\frac{dOCV}{dz} \neq 0$  and the time constants are distinct, i.e.,  $\tau_1 \neq \tau_2$ . For the NCM battery used in this study, the OCV curve is strictly monotonic ( $\frac{dOCV}{dz} > 0$ ) across the operating range, and the identified time constants naturally differ by an order of magnitude. Therefore, the proposed dual-anchor models are locally observable, ensuring the feasibility of the EKF algorithm.

Furthermore, the stability of the discrete-time system is determined by the eigenvalues of the state transition matrix  $A_k$ . As shown in Equation (7),  $A_k$  is a diagonal matrix, so its eigenvalues are its diagonal elements:

$$\lambda_1 = 1, \quad \lambda_2 = e^{-\frac{\Delta t}{\tau_1}}, \quad \lambda_3 = e^{-\frac{\Delta t}{\tau_2}} \quad (11)$$

Since time constants  $\tau_1, \tau_2 > 0$  and sampling interval  $\Delta t > 0$ , the eigenvalues for the polarization states satisfy  $0 < \lambda_{2,3} < 1$ , indicating that the polarization dynamics are asymptotically stable. Although the eigenvalue  $\lambda_1 = 1$  corresponds to the SOC integration process representing a marginally stable system, the stability of the estimation error dynamics in the closed-loop EKF observer is guaranteed by the Kalman gain  $K_k$ , provided that the system is observable and the noise covariance matrices  $Q$  and  $R$  are positive definite. Consequently, the proposed framework satisfies the stability requirements for real-time control systems.

### 3.3. Residual-Driven Likelihood Assessment

To evaluate the fitness of each anchor model for the current target battery, the algorithm calculates the instantaneous output residual,  $e_k^{(i)}$ , defined as the difference between the measured terminal voltage  $U_{\text{meas},k}$  and the model-predicted voltage  $U_{\text{est},k}^{(i)}$ , as shown in Equation (12):

$$e_k^{(i)} = U_{\text{meas},k} - U_{\text{est},k}^{(i)} \quad (12)$$

Assuming the measurement noise follows a Gaussian distribution, the likelihood of the  $i$ -th model matching the true battery state at time step  $k$  can be quantified using a Gaussian probability density function, given by Equation (13):

$$\Lambda_k^{(i)} \propto \exp\left(-\frac{(e_k^{(i)})^2}{2\sigma^2}\right) \quad (13)$$

Here,  $\sigma$  is a tuning parameter representing the tolerance for voltage mismatch. Since the weights are normalized in the subsequent step (Equation (15)), the constant coefficient of the probability density function is omitted; the likelihood  $\Lambda_k^{(i)}$  is thus expressed as proportional to the exponential term. In this study, the tuning parameter  $\sigma$  is set to 0.015 V. Although the data acquisition system possesses a high resolution, a conservative tolerance (larger than the physical noise floor) was selected. This robustness-oriented tuning effectively desensitizes the weighting mechanism to transient outliers and high-frequency measurement noise, ensuring that the weight adaptation is driven solely by significant impedance mismatches. A higher likelihood  $\Lambda_k^{(i)}$  indicates that the impedance characteristics of the target battery at the current moment are closer to those of anchor model  $i$ .

### 3.4. Recursive Weight Update with Fading Memory

Directly using the instantaneous likelihood for fusion may lead to jitter due to sensor noise. Conversely, a simple cumulative average limits the system's ability to track time-varying behaviors (e.g., dynamic impedance changes under load). To balance stability and responsiveness, we introduce a recursive Bayesian update law with a fading memory factor  $\alpha$  (Equation (14)), followed by the normalization step in Equation (15):

$$w_k^{(i)*} = \Lambda_k^{(i)} \cdot (w_{k-1}^{(i)})^\alpha \quad (14)$$

$$w_k^{(i)} = \frac{w_k^{(i)*}}{\sum_{j \in \{A,B\}} w_k^{(j)*}} \quad (15)$$

where  $w_k^{(i)}$  is the normalized weight of model  $i$ . The factor  $\alpha \in (0,1]$  (set to 0.99 in this study) serves as a “forgetting” mechanism. It prevents the weights from locking onto a single model history, ensuring the algorithm remains sensitive to instantaneous nonlinear polarization responses, as visualized later in the experimental results.

From a theoretical perspective, the essence of this recursive weight update mechanism is a Maximum Likelihood Estimation (MLE) process constrained by the physical boundaries of the anchor models. Unlike neural networks that minimize a global loss function via backpropagation, our framework performs instantaneous impedance matching. The adaptive weight  $w_k$  serves as a dynamic “slider,” automatically positioning the target battery within the convex parameter set defined by the aged and healthy anchors. This ensures that the estimation is not only numerically optimized but also electrochemically plausible, as it physically maps the target's degradation state onto the trajectory established by the high-fidelity DRIS anchors.

The recursive process is initialized with equal weights, i.e.,  $w_0^{(A)} = w_0^{(B)} = 0.5$ , reflecting an unbiased initial estimation of the battery's SOH.

### 3.5. Fusion Estimation and SOH Soft-Sensing

Based on the recursive weight update mechanism derived above, the complete workflow of the proposed framework is summarized in Algorithm 1. This algorithm integrates the dual-model EKF prediction (Time Update) with the Bayesian weight correction (Measurement Update) into a unified real-time loop. Crucially, in Step 2.3, the fused SOC is computed as the weighted sum of the states from both anchors, while the SOH is simultaneously inferred (‘soft-sensed’) by mapping the adaptive weights onto the known aging boundaries (SOH A and SOH B).

The final estimated SOC is derived from the weighted sum of the states from both independent EKFs, as expressed in Equation (16):

$$\widehat{\text{SOC}}_{\text{fusion},k} = w_k^{(A)} \cdot \hat{z}_k^{(A)} + w_k^{(B)} \cdot \hat{z}_k^{(B)} \quad (16)$$

Furthermore, a novel capability of this framework is the ‘Soft-Sensing’ of the battery’s health state. Since the anchor models  $M_A$  and  $M_B$  correspond to known, fixed SOH values ( $\text{SOH}_A$  and  $\text{SOH}_B$ ), the fusion weights inherently reflect the relative position of the target battery within this aging parameter space. The estimated SOH can thus be inferred using Equation (17):

$$\widehat{\text{SOH}}_{\text{est},k} \approx w_k^{(A)} \cdot \text{SOH}_A + w_k^{(B)} \cdot \text{SOH}_B \quad (17)$$

The validity of this linear interpolation relies on the concept of local linearity. While the degradation trajectory of lithium-ion batteries is globally nonlinear over their full lifecycle, the parameter evolution within the bounded interval defined by the two anchors (e.g., SOH range of 0.61–0.80) can be effectively approximated as linear. Since the fusion weights  $w_k^{(i)}$  are dynamically calculated based on the instantaneous impedance match between the target battery and the anchor models, they serve as a reliable metric for determining the target’s relative position within this ‘‘piecewise linear’’ aging envelope. However, it implies that if the SOH interval between anchors is excessively large (e.g., spanning regions with distinct degradation mechanisms), the non-linearity error would increase. In such scenarios, the proposed framework allows for scalability: additional intermediate anchors can be inserted to maintain the validity of the local linearity assumption.

This mechanism enables real-time monitoring of the degradation level without requiring additional capacity test cycles, providing a cost-effective solution for second-life battery management.

---

#### Algorithm 1. Dual-Anchor Adaptive Fusion and SOH Soft-Sensing

---

Inputs: Current  $I_k$ , Voltage  $U_k$  (at time step  $k$ ), Anchor Models  $M_A$ ,  $M_B$  (Parameters from DRIS strategy)

Outputs: Fused SOC  $\widehat{\text{SOC}}_{\text{fusion},k}$ , Estimated SOH  $\widehat{\text{SOH}}_{\text{est},k}$

1. Initialization: Initialize state vectors  $\hat{x}_0^{(A)}$ ,  $\hat{x}_0^{(B)}$  and covariance matrices  $P_0^{(A)}$ ,  $P_0^{(B)}$ .

Set initial fusion weights:  $w_0^{(A)} = w_0^{(B)} = 0.5$ .

2. Recursive Loop (for each time step  $k = 1, 2, \dots$ ):

Step 2.1: Dual-Model Prediction (Time Update)

for  $i \in \{A, B\}$  do

State prediction:  $\hat{x}_{k|k-1}^{(i)} = A_k^{(i)} \hat{x}_{k-1}^{(i)} + B_k^{(i)} I_k$

Voltage prediction:  $\hat{U}_{\text{est},k}^{(i)} = U_{\text{OCV}}(\hat{z}_{k|k-1}^{(i)}) + \hat{U}_{1,k}^{(i)} + \hat{U}_{2,k}^{(i)} + I_k R_0^{(i)}$

end for

Step 2.2: Adaptive Weight Update (Measurement Update)

Calculate voltage residuals:  $e_k^{(i)} = U_k - \hat{U}_{\text{est},k}^{(i)}$

---

---


$$\text{Compute likelihood: } \Lambda_k^{(i)} = \exp\left(-\frac{(e_k^{(i)})^2}{2\sigma^2}\right)$$

$$\text{Recursive update (with fading factor } \alpha): w_k^{(i)*} = \Lambda_k^{(i)} \cdot (w_{k-1}^{(i)})^\alpha$$

$$\text{Normalization: } w_k^{(i)} = w_k^{(i)*} / \sum_{j \in \{A, B\}} w_k^{(j)*}$$

Step 2.3: State Fusion & SOH Soft-Sensing

$$\widehat{\text{SOC}}_{\text{fusion},k} = w_k^{(A)} \cdot \hat{z}_k^{(A)} + w_k^{(B)} \cdot \hat{z}_k^{(B)}$$

$$\widehat{\text{SOH}}_{\text{est},k} = w_k^{(A)} \cdot \text{SOH}_A + w_k^{(B)} \cdot \text{SOH}_B$$

Step 2.4: EKF State Correction

$$\text{Update individual model states } \hat{x}_k^{(i)} \text{ using Kalman gain } K_k^{(i)}.$$


3. Return  $\widehat{\text{SOC}}_{\text{fusion},k}$  and  $\widehat{\text{SOH}}_{\text{est},k}$ .

---

## 4. Experimental Setup

### 4.1. Experimental Platform and Data Acquisition

To validate the proposed method using realistic data rather than public datasets, rigorous experiments were conducted on a professional test bench. The experimental platform comprised a LANHE CT6002A battery testing system (Wuhan Land Electronics Co., Ltd., Wuhan, China; 5 V/100 A, 0.05% accuracy) for precise charge–discharge control and a GDBell BTH-1000CT constant temperature and humidity chamber (Guangdong Bell Experiment Equipment Co., Ltd., Guangdong, China). As illustrated in Figure 8, the retired lithium-ion batteries were placed inside the thermal chamber to provide well-controlled ambient temperature conditions. Prior to data acquisition, the batteries were rested for at least 2 h to reach thermal equilibrium with the chamber environment. All experiments were subsequently performed at a constant temperature of  $25\text{ }^\circ\text{C} \pm 0.1\text{ }^\circ\text{C}$  to eliminate thermal variability. The test subjects were retired prismatic NCM (Ni–Co–Mn) lithium-ion batteries originally designed for automotive applications (nominal capacity: 3.0 Ah; voltage window: 2.75–4.20 V; see Table 1 for details [40]).



**Figure 8.** The experimental setup for battery testing. The red circle indicates the chamber work-space where the battery fixture is placed for temperature and humidity control.


**Table 1.** Specifications of the Retired Lithium-Ion Battery.

| Parameter                   | Value          |
|-----------------------------|----------------|
| Cathode Material            | NCM (Ni-Co-Mn) |
| Nominal Capacity            | 3000 mAh       |
| Nominal Voltage             | 3.7 V          |
| Charging Cut-off Voltage    | 4.2 V          |
| Discharging Cut-off Voltage | 2.75 V         |

#### 4.2. Dual-Anchor Identification and Blind Validation Scenario

The experimental design consists of two phases: anchor construction and blind validation. Prior to the experiments, the true SOH of each cell was rigorously calibrated. The calibration procedure involved three consecutive static capacity tests at 25 °C, consisting of a constant current–constant voltage (CC-CV) charge at 0.5 C to 4.2 V (cutoff 0.05 C) and a constant current (CC) discharge at 1 C to 2.75 V.

To ensure the reliability of the benchmark values, the capacity calibration test was repeated three times for each cell, yielding a standard deviation of less than 0.3%. The raw experimental data corresponding to these calibration tests is visualized in Figure 9, where the consistent voltage and current trajectories across the three consecutive cycles empirically verify the stability of the measurement setup.

**Figure 9.** Time-domain voltage and current profiles during the capacity calibration process.

First, to establish the parameter envelope, two retired cells representing the boundaries of the health status were selected: an aged cell (Anchor A, SOH  $\approx$  0.61) and a healthier cell (Anchor B, SOH  $\approx$  0.80). Their high-fidelity parameters were extracted using the DRIS strategy based on HPPC tests, serving as fixed references for the fusion model (as detailed in Section 2.4). To ensure reproducibility, the specific configuration parameters for the proposed Dual-Anchor Adaptive Fusion algorithm and the underlying EKF observers are explicitly detailed in Table 2.

**Table 2.** Configuration of key parameters for the adaptive fusion algorithm and EKF observers.

| Parameter                | Symbol                 | Value                                    | Justification/Source                                                                                                                                           |
|--------------------------|------------------------|------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Process Noise Covariance | $Q$                    | $\text{diag}[10^{-5}, 10^{-5}, 10^{-5}]$ | Tuned based on current sensor noise characteristics.                                                                                                           |
| Meas. Noise Covariance   | $R$                    | $10^{-4}$                                | Set conservatively higher than the physical sensor noise floor ( $\sim 10^{-6}$ ) to prioritize estimation stability and suppress high-frequency disturbances. |
| Voltage Tolerance        | $\sigma$               | 0.015 V                                  | Empirically determined to balance sensitivity and noise rejection.                                                                                             |
| Fading Memory Factor     | $\alpha$               | 0.99                                     | Sets a forgetting horizon of $\sim 100$ samples to track dynamic transients.                                                                                   |
| Initial Weights          | $w_0^{(A)}, w_0^{(B)}$ | 0.5                                      | Unbiased initialization for blind estimation.                                                                                                                  |
| Sampling Interval        | $\Delta t$             | 0.1 s                                    | Determined by the data acquisition system (10 Hz).                                                                                                             |

Subsequently, to rigorously evaluate the robustness and interpolation capability of the framework, a third battery (“Target A”) was selected for blind validation. Its true SOH was calibrated to be 0.7576.

Target A was strategically selected to lie strictly inside the anchor interval (SOH 0.61–0.80) and close to the mid-range. This selection ensures a valid test of the algorithm’s interpolation capability, as the target’s electrochemical parameters are distinct from both boundary models. The target battery was subjected to a Dynamic Stress Test (DST). It is worth noting that the DST profile is chosen for its comprehensive coverage of dynamic operating conditions, including rapid charge/discharge pulses, varying current rates, and rest periods. This complexity effectively simulates a wide range of real-world driving scenarios, making it a rigorous benchmark for assessing model generalization. To establish a reliable baseline for validation, the reference “True SOC” trajectory was calculated using the Coulomb counting method (Ampere-hour integration). The integration employed the actual discharge capacity of Target A (2.26 Ah, calibrated from the static tests) and relied on the high-precision current measurements from the battery tester (accuracy  $\pm 0.05\%$  F.S.), assuming negligible current sensor bias over the test duration. Furthermore, to eliminate initial offset errors, the initial SOC was strictly calibrated to 100% by fully charging the battery (CC-CV mode) and allowing a 2-h relaxation period before the commencement of the DST profile.

Crucially, this validation was conducted as a “blind test”: the true SOH of Target A was hidden from the fusion algorithm, which was initialized with unbiased weights ( $w_A = w_B = 0.5$ ). This setup forces the algorithm to infer the battery state solely from instantaneous voltage and current responses, providing a rigorous assessment of its “soft-sensing” capability.


## 5. Results and Discussion

### 5.1. Robust SOC Estimation Performance in Blind Test

To verify the robustness and generalization capability of the proposed framework, a rigorous blind validation test was conducted under the Dynamic Stress Test (DST) profile. Unlike data-driven methods that typically require a random split of training and testing datasets (e.g., 70%/30%) to learn aging patterns, the proposed Dual-Anchor framework operates in a completely calibration-free mode. The target battery (Target A, True SOH =

0.7576) was entirely unknown to the algorithm, and no specific data from this battery was used for model training. The algorithm's task was to estimate the state of this uncharacterized target solely by interpolating between the fixed boundary anchors (SOH 0.61 and 0.80).

The estimation results of the proposed framework are presented in Figure 10. It can be clearly observed that the single anchor models exhibit systematic biases due to parameter mismatch: the aged Anchor A (orange dot-dashed line) tends to underestimate the SOC, while the healthy Anchor B (blue dot-dashed line) tends to overestimate it.



**Figure 10.** Comparison of SOC estimation results between the proposed Dual-Anchor Fusion framework and static fixed-parameter models (Anchors and Validation) under DST cycles.

To further highlight the limitation of fixed-parameter approaches, the Validation (0.68) model (gray dashed line) is included as a control group. Although this intermediate model (calibrated at SOH 0.68) reduces the bias compared to the extreme anchors, it still fails to align perfectly with the target trajectory (Reference, SOH 0.75), exhibiting a persistent static offset. This confirms that a static parameter set, unless perfectly matched to the target's unknown SOH, cannot guarantee estimation accuracy.


In contrast, the Proposed Fusion (red solid line) successfully bridges this gap. By dynamically adjusting the weights based on real-time voltage feedback, the fusion algorithm automatically interpolates between the two boundaries, tracking the Reference (black solid line) trajectory with remarkable precision. The estimation error is effectively bounded within a narrow range, achieving an RMSE of 0.42%, which significantly outperforms the individual anchors.

It is noteworthy that the healthy Anchor B also yields a relatively low RMSE (0.59%). This is physically intuitive because the Target battery (SOH  $\approx$  0.76) is much closer to the

healthy state ( $\text{SOH} \approx 0.80$ ) than to the aged state ( $\text{SOH} \approx 0.61$ ). However, relying solely on Anchor B is risky; its performance would severely degrade if the target battery were closer to the aged boundary. In contrast, the Fusion framework not only further reduces the error by  $\sim 29\%$  (from 0.59% to 0.42%) but, more critically, guarantees consistent robustness across the entire aging spectrum, independent of the target's specific health state.

This verifies the framework's capability to 'lock onto' the true state of an uncalibrated battery solely through boundary constraints.

To further validate that the superior SOC accuracy stems from the physical fidelity of the model rather than solely from feedback correction, we conducted a decoupled analysis of the terminal voltage residuals, as shown in Figure 11.



**Figure 11.** Decoupled analysis of terminal voltage residuals.

The A Priori residual (blue line) reflects the open-loop prediction accuracy. Remarkably, the RMSE is compressed to 0.152 mV, a value that effectively aligns with the quantization noise limit (resolution floor) of the experimental hardware's ADC. This indicates that the DRIS-based anchor parameters have captured the electrochemical dynamics to the maximum extent resolvable by the sensing equipment, leaving virtually no residual error attributable to model structural mismatch.


Furthermore, the A Posteriori residual (red line) demonstrates the contribution of the EKF. With the feedback gain active, the residual is further compressed to 0.085 mV, effectively approaching the hardware resolution limit (quantization floor) of the ADC. It is worth noting that while the absolute measurement accuracy is bounded by  $\pm 2\text{--}3$  mV (bias), the tracking consistency represented by the RMSE has converged to the microvolt level ( $\sim 85$   $\mu\text{V}$ ), indicating that the model captures the battery dynamics with maximal fidelity allowed by the sensing granularity. This comparison confirms that the framework relies on a precise physical foundation, with the adaptive filter serving primarily to eliminate residual measurement uncertainties. The quantitative comparison of these voltage residuals is summarized in Table 3.

**Table 3.** Comparison of Voltage Residuals.

| Residual Type                   | Mathematical Definition               | RMSE (mV) | Physical Implication                                 |
|---------------------------------|---------------------------------------|-----------|------------------------------------------------------|
| A Priori (One-step Prediction)  | $U_{\text{meas},k} - \hat{U}_{k k-1}$ | 0.152     | Reflects high structural fidelity of DRIS parameters |
| A Posteriori (After EKF Update) | $U_{\text{meas},k} - \hat{U}_{k k}$   | 0.085     | Converges to hardware quantization limit (ADC floor) |

### 5.2. External Benchmarking: Comparison with State-of-the-Art Algorithms

To rigorously position the proposed framework, comparative experiments were conducted against two representative methodologies suggested by literature: a data-driven Support Vector Regression (SVR) and a model-based Adaptive Extended Kalman Filter (A-EKF), as shown in Figure 12.

**Figure 12.** Performance benchmarking against state-of-the-art SOC estimation methods under data-scarce conditions.

As observed in Figure 12a, the data-driven SVR (teal line) fails to generalize to the uncharacterized target battery. Due to the lack of training data covering the specific aging state of the target, the SVR model produces severe non-physical oscillations. This failure is fundamentally attributed to the ‘distribution shift’ between the source domain (training data) and the target domain (uncharacterized battery). Unlike physics-informed models,


pure data-driven approaches often lack the extrapolation capability to handle such shifts without extensive transfer learning. The A-EKF (purple dashed line), while physically interpretable, exhibits noticeable parameter drift under the dynamic DST profile, resulting in an RMSE of 1.53%.

Figure 12b further reveals the critical safety implications. While the A-EKF provides a reasonable average accuracy, the SVR exhibits a Maximum Estimation Error of 21.07%. Such unpredictability in extrapolation scenarios poses an unacceptable safety hazard for BMS. In sharp contrast, the proposed Dual-Anchor Fusion framework achieves superior robustness, yielding the lowest RMSE of 0.42% and strictly capping the Maximum Error at 1.05%.

These results confirm that the proposed physics-informed strategy effectively eliminates both the divergence risk of adaptive algorithms and the overfitting risk of pure data-driven models, making it a highly reliable solution for retired battery applications.

### 5.3. SOH Soft-Sensing Capability

Beyond robust SOC tracking, this section experimentally validates the ‘SOH Soft-Sensing’ capability proposed in Section 3.5. Instead of analyzing the raw fusion weights in isolation, this section focuses on the physical health metrics derived from them. By mapping the adaptive weights—which represent the instantaneous impedance match—onto the fixed anchor boundaries (Equation (17)), the framework continuously infers the battery’s real-time health status. Figure 13 presents the comprehensive soft-sensing results. Figure 13a illustrates the dynamic adaptive weight allocation mechanism, while Figure 13b displays the resulting SOH trajectory compared against the calibrated target.



**Figure 13.** Mechanism and validation of real-time SOH Soft-Sensing: (a) Dynamic evolution of adaptive fusion weights reflecting impedance matching; (b) Comparison of estimated SOH trajectory against ground truth.

As visualized in Figure 13b, the results are highly compelling. High-Fidelity Estimation: The mean estimated SOH over the test duration is 0.7513, which closely tracks the

ground truth (0.7576) with a relative error of only 0.84%. This confirms that the framework successfully interpolates the target battery's position within the parameter envelope defined by the DRIS-based anchors, achieving high accuracy without any prior calibration.

The fidelity of the model is further illuminated by the dynamic evolution of the fusion weights shown in Figure 13a. It can be observed that the weights are not static; instead, they exhibit rapid, physically explainable adjustments corresponding to high-dynamic load phases. When a sudden voltage drop occurs (e.g., in the Zoom-in region of Figure 13a), the algorithm instantaneously shifts the weight allocation towards the aged anchor (Weight A, orange area), which possesses higher internal resistance. This rapid adaptation confirms that the fusion mechanism is not merely fitting a static average but is performing a real-time “impedance matching” process, capturing the battery's dynamic characteristics with high sensitivity.

Furthermore, it is critical to substantiate the physical basis of this soft-sensing capability to rule out numerical coincidence. The underlying mechanism relies on the monotonic correlation between internal impedance and SOH in lithium-ion batteries. As established in Section 2.4, the aged anchor (Anchor A) inherently possesses significantly higher internal resistance than the healthy anchor (Anchor B). The fusion algorithm, by minimizing the real-time voltage residual ( $e_k = U_{\text{meas}} - U_{\text{est}}$ ), is effectively performing an instantaneous “impedance matching” process.

The adaptive weight  $w_k^{(A)}$  therefore quantifies the ‘impedance distance’ of the target battery relative to the aged boundary. Since impedance rise is the primary symptom of degradation in this aging stage, the weight-derived SOH ( $\text{SOH} \approx \sum w_i \text{SOH}_i$ ) serves as a physically grounded proxy for the true health state, robustly bridging the gap between mathematical optimization and electrochemical reality.

#### 5.4. Sensitivity and Robustness Analysis

Ideally, the anchor models serve as precise references; however, in practical second-life applications, the initial SOH labels of retired modules may contain measurement uncertainties. To rigorously evaluate the framework's robustness under such conditions, a quantitative sensitivity analysis was conducted, as illustrated in Figure 14. The analysis introduces a perturbation of up to  $\pm 10\%$  to the SOH labels of the anchor models while monitoring the induced bias in the final estimation.




Figure 14. Sensitivity analysis of SOH estimation bias versus anchor calibration errors.

The results reveal an intrinsic “Error Attenuation” mechanism inherent to the proposed fusion architecture. As shown in Figure 14, the sensitivity of the estimation bias is linear and strictly governed by the fusion weights ( $w$ ). For the target battery in this validation ( $\text{SOH} \approx 0.76$ ), which is electrochemically closer to the Healthy Anchor ( $\text{SOH} = 0.80$ ), the algorithm assigns a dominant weight to the healthy model ( $w_{\text{Healthy}} \approx 0.74$ , indicated by the steeper blue dashed line), while the Aged Anchor contributes less ( $w_{\text{Aged}} \approx 0.26$ , indicated by the flatter orange solid line).

Crucially, even within the significant perturbation range of  $\pm 5\%$  (highlighted in the shaded region), the maximum induced estimation error is strictly bounded. Specifically, a 5% calibration error in the dominant Healthy Anchor results in only a 3.72% estimation bias, while the same error in the Aged Anchor leads to a negligible 1.28% bias. This confirms that the output error is consistently lower than the input parameter error (i.e., Slope  $< 1$ ), verifying the Bounded Input Bounded Output (BIBO) stability of the framework. This characteristic ensures that the proposed method remains reliable even when deployed with imperfectly characterized retired batteries.

## 6. Discussion and Conclusions

**Theoretical Insights:** This study addresses the critical challenge of state estimation for retired batteries with heterogeneous aging characteristics by proposing a Dual-Anchor Adaptive Fusion Framework. By integrating offline high-fidelity feature extraction (DRIS) with online probabilistic fusion, the proposed method effectively bridges the gap between static modeling and the dynamic reality of second-life batteries. The core innovation lies in the discovery of “Physics-Informed Soft-Sensing,” where the adaptive fusion weights are interpreted not merely as mathematical coefficients but as physical health metrics. Unlike “black-box” data-driven models that often require massive labeled datasets for pre-training, our framework operates in a calibration-free mode, utilizing only two fixed boundary anchors to cover the entire aging space. Furthermore, by prioritizing the time-domain DRIS strategy over frequency-domain EIS, we ensure that the identified parameters are optimized specifically to minimize the EKF prediction residual, offering superior applicability for online state estimation. The ability of the framework to infer the target SOH with a relative error of 0.84% (Figure 13) functionally validates that the identified impedance parameters exhibit a strict monotonic relationship with degradation, serving as reliable proxies for the battery’s health state. To further clarify the positioning of this work, Table 4 provides a comprehensive comparison with mainstream state estimation methods.

**Table 4.** Qualitative comparison of the proposed framework against mainstream model-based and data-driven estimation strategies.

| Feature                   | Proposed Dual-Anchor Framework                                      | Data-Driven Methods (e.g., SVR, Neural Networks)                   | Adaptive EKF (Single Model)                          |
|---------------------------|---------------------------------------------------------------------|--------------------------------------------------------------------|------------------------------------------------------|
| Prerequisite Data         | None (calibration-free). Only requires 2 fixed boundary parameters. | Massive labeled datasets required for pre-training.                | None, but requires accurate initial parameters.      |
| Aging Adaptability        | High. Interpolates physically between aged/healthy states.          | Low. Performance degrades if test data deviates from training set. | Medium. Can track slow changes but risks divergence. |
| Physical Interpretability | Strong. Weights represent “Impedance Distance” (SOH).               | Weak. “Black-box” mapping.                                         | Strong. Estimates physical parameters.               |
| Computational Load        | Low. Two parallel EKFs + scalar weighting.                          | High. Complex matrix operations or deep layers.                    | Medium. Requires covariance matrix updates.          |

| Implementation Risk | Stable. Bounded by fixed anchors. | Overfitting Risk. | Divergence Risk (e.g., in flat OCV regions). |
|---------------------|-----------------------------------|-------------------|----------------------------------------------|
|---------------------|-----------------------------------|-------------------|----------------------------------------------|

**Limitations and Future Work:** While the proposed framework demonstrates robust performance, it is objectively important to acknowledge the constraints of the present study to define its valid application scope. First, regarding experimental conditions, the validation was conducted on a specific batch of retired NCM cells under strictly controlled laboratory temperatures (25 °C). While this successfully isolates aging-induced heterogeneity, it does not fully capture the complex coupling effects of varying ambient temperatures and thermal gradients often encountered in real-world battery packs. Second, regarding model dependence, the framework's baseline accuracy relies on the initial high-fidelity calibration of the anchor models. Although the sensitivity analysis confirms robustness against minor calibration errors (e.g.,  $\pm 5\%$ ), significant deviations in aging mechanisms (such as lithium plating vs. SEI growth) could potentially compromise the estimation accuracy. Third, the "SOH Soft-Sensing" capability relies on the assumption of piecewise linear impedance evolution between the two anchors. This assumption is physically valid for the specific "second-life" window investigated (SOH 0.61–0.80); however, the linearization error would inherently increase over wider SOH ranges (e.g., from 100% down to 50%) or in the presence of nonlinear aging "knees". To address these limitations, future research will focus on extending the validation to a larger population of cells with diverse chemistries (e.g., LFP) and form factors to verify the method's universality. Additionally, developing temperature-dependent anchor models that integrate thermal dynamics will be crucial for enabling robust estimation under wide-range temperature variations. Furthermore, exploring a scalable "Multi-Anchor" architecture—by inserting intermediate anchors to linearize the degradation path locally—will be investigated to maintain estimation precision across the full battery lifespan.

**Conclusions:** The experimental results support three key findings. (1) Resolution of the "E-point Selection Dilemma": The automated DRIS strategy effectively eliminates subjectivity in offline parameter identification, reducing the fitting RMSE from 6.22 mV (traditional method) to 3.39 mV and ensuring the construction of physically meaningful anchor models. (2) Robust Calibration-Free Estimation: For uncalibrated target batteries, the Dual-Anchor Fusion framework maintains high tracking stability with an RMSE of 0.42%. It effectively mitigates the parameter drift observed in the standard A-EKF (RMSE 1.53%), with the a posteriori voltage tracking error converging to  $\sim 0.085$  mV, effectively matching the hardware quantization limit. (3) Real-time SOH Inference: The adaptive fusion weights accurately reflect the battery's health status. The SOH is inferred with a relative error of 0.84% under dynamic loading, providing a cost-effective mechanism for online health monitoring while obviating the need for additional capacity test cycles.

**Author Contributions:** Conceptualization, H.W., R.L., Y.J. and J.L.; Investigation, H.W. and R.L. Validation, Y.G., Y.L. and J.C.; Writing—original draft preparation, H.W. and R.L.; Writing—review and editing, Y.J. All authors have read and agreed to the published version of the manuscript.

**Funding:** This research was funded by the Characteristic Innovation Project of Universities in Guangdong (No. 2024KTSCX031, No. 2023KTSCX154); the Zhaoqing University High-level Project Training Program Funding Project (No. GCCZK202414).

**Data Availability Statement:** The original contributions presented in the study are included in the article, further inquiries can be directed to the corresponding author.

**Conflicts of Interest:** The authors declare no potential conflicts of interest concerning this research, authorship, and/or publication of this article.

## Abbreviations

The following abbreviations are used in this manuscript:

|       |                                       |
|-------|---------------------------------------|
| ECM   | Equivalent Circuit Model              |
| DRIS  | Dynamic Relaxation Interval Selection |
| SOH   | State of Health                       |
| BMS   | Battery Management System             |
| SOC   | State of Charge                       |
| RLS   | Recursive Least Squares               |
| HPPC  | Hybrid Pulse Power Characterization   |
| CC    | Constant Current                      |
| CV    | Constant Voltage                      |
| OCV   | Open-Circuit Voltage                  |
| NCM   | Nickel-Cobalt-Manganese               |
| RMSE  | Root Mean Square Error                |
| EKF   | Extended Kalman Filter                |
| A-EKF | Adaptive Extended Kalman Filter       |
| SVR   | Support Vector Regression             |
| BIBO  | Bounded Input Bounded Output          |
| LFP   | Lithium Iron Phosphate                |
| ADC   | Analog-to-Digital Converter           |
| EV    | Electric Vehicle                      |

## References

1. Feng, H.; Xiong, Z. Opportunities and Development Strategies of New Energy Vehicle Industry under the Background of “Double Carbon”. *Decis. Inf.* **2022**, *5*, 68–76.
2. Li, Y.; Yu, H. Building International Strategic Corridors of Renewable Electricity and Hydrogen Energy for Security—In the Perspective of Great Power Competition. *J. Int. Relat.* **2023**, *6*, 60–80+154–155.
3. Sohaib, M.; Choi, W. Evaluating the Status of Lithium-Ion Cells Without Historical Data Using the Distribution of Relaxation Time Method. *Batteries* **2025**, *11*, 366.
4. Qi, J.; Xu, Y.; Chen, S.; Shen, J.; Yang, R.; Xu, H. A Comprehensive Review of Equalization Techniques for Reconfigured Second-Life Battery Systems. *Batteries* **2025**, *11*, 327.
5. Peng, F.; Luo, W. Study on Optimal Strategy of Low-Voltage Power Supply Management for Pure Electric Vehicles. *J. Guangxi Univ. Sci. Technol.* **2024**, *35*, 56–64.
6. Ma, L.; Liu, L. Dilemma and Strategies for the Recycling and Utilization of Power Battery. *Battery Bimon.* **2025**, *55*, 805–809.
7. Su, L. Modeling and State of Charge Estimation of Retired Lithium-Ion Battery. Master’s Thesis, Qilu University of Technology, Jinan, China, 2022.
8. Xiong, W. Research on Key Technologies for Management of Retired Lithium-Ion Battery Oriented for Second-Use. Master’s Thesis, Wuhan University of Technology, Wuhan, China, 2020.
9. Yao, Y. Research on State of Health Estimation and Cascaded Utilization of Retired Lithium-Ion Batteries. Master’s Thesis, Southeast University, Nanjing, China, 2023.
10. Wang, R. Research on Key Technologies for Echelon Utilization of Retired Battery Energy Storage Systems. Master’s Thesis, Chongqing Three Gorges University, Chongqing, China, 2022.
11. Salek, F.; Azizi, A.; Resalati, S. Mathematical Modelling and Simulation of Second Life Battery Pack with Heterogeneous State of Health. *Mathematics* **2022**, *10*, 3843.
12. Tanim, T.R.; Dufek, E.J.; Walker, L.K. Advanced Diagnostics to Evaluate Heterogeneity in Lithium-Ion Battery Modules. *eTransportation* **2020**, *3*, 100045.
13. Yuan, Y.; Li, P.; Gao, Y.; Wan, K.; Chen, L.; Liu, A.; Jin, M.; Zhang, H.; Zhang, F. Current Situation and Prospect of Safety Standards for Cascade Utilization of Retired Batteries in China. *Safety. Health Environ.* **2023**, *23*, 1–7.
14. Duan, X.; Zhang, J.; Zhuo, X.; Xiong, W. Patent Analysis for Technologies and Industry of Second Life Power Batteries. *Min. Metall. Eng.* **2023**, *43*, 182–185.
15. Li, Y.; Zhao, C.; Li, D.; Dan, J.; Deng, Y.; Deng, D.; Hu, B. Progress in Recycling Technology of Lithium Iron Phosphate Li-ion Battery. *Battery Bimon.* **2025**, *55*, 1004–1011.

16. Wang, Q.; Li, H.; Wang, X.; Ding, M. Research on Characteristics and Sorting Method of Retired Power Batteries. *Acta Energ. Sol. Sin.* **2025**, *46*, 273–283.
17. Liu, Q.; Chen, X.; Wu, J.; Li, X.; Chen, Y.; Chen, Q. Cascade Utilization of Retired Power Batteries under the “Dual Carbon” Goal: Current Status and Comprehensive Analysis. *Renew. Resour. Circ. Econ.* **2024**, *17*, 24–31.
18. Xue, X.; Wu, M. Parameter Identification of Power Lithium-Ion Battery Based on Least Squares Method. *Inf. Comput.* **2022**, *34*, 72–75.
19. Ruan, A.; Shi, Y.; Wang, F. SOC Estimation of Li-Ion Battery Parameters Based on FFRLS-AIEKF. *Battery Bimon.* **2025**, *55*, 529–535.
20. Xing, L.; Zhan, M.; Guo, M. SOC Estimation of Lithium Battery Based on FFMILS-MIUKF Algorithm. *Electron. Meas. Technol.* **2022**, *45*, 53–60.
21. Cao, A.; Li, X.; Feng, R.; Wang, Y. Parameter Identification of Lithium Battery Model Based on MOPSO-KF Algorithm. *Electr. Eng.* **2025**, *16*, 55–60.
22. Li, J.; Peng, Y.; Wang, Q.; Liu, H. Status and Prospects of Research on Lithium-Ion Battery Parameter Identification. *Batteries* **2024**, *10*, 194.
23. Cui, X.; Huang, Y.; Wu, X. Overview of State-of-Charge estimation Methods and Application for Lithium-Ion Batteries. *Electron. Meas. Technol.* **2024**, *47*, 41–59.
24. Wu, C.; Ma, Y.; Chang, Z.; Yang, T.; Meng, J.; Chang, Y.; Wang, L.; He, X. High Precision Estimation of SOP of Lithium-Ion Batteries Using Multi Constraint Collaborative Optimization and SSA-ELM Dynamic Compensation. *Energy Storage Sci. Technol.* **2025**, *in press*.
25. Wang, Y.; Lu, W.; Ni, S.; Yang, H.; Wu, E. Parameter Identification of Lithium Battery Based on Improved Multi-Population Genetic Algorithm. *Electr. Eng.* **2023**, *16*, 33–36.
26. Xu, A.; Dai, J.; Gu, C.; Leng, X.; Wei, J. Research on SOC Estimation of Lithium-ion Battery Based on WOA Optimized Extended Kalman Algorithm. *J. Power Supply* **2025**, *23*, 232–239.
27. Zhang, M.; Yang, D.; Du, J. A Review of SOH Prediction of Li-Ion Batteries Based on Data-Driven Algorithms. *Energies* **2023**, *16*, 3167.
28. Oji, T.; Zhou, Y.; Ci, S. Data-Driven Methods for Battery SOH Estimation: Survey and a Critical Analysis. *IEEE Access* **2021**, *9*, 126903–126916.
29. Guo, L.; Wang, B. Parameter Identification Method of Second-Order RC Equivalent Circuit of Lithium Battery. *J. Shaoyang Univ. (Nat. Sci.)* **2025**, *22*, 11–18.
30. Li, J.; Ye, M.; Ma, X. SOC Estimation and Fault Diagnosis Framework of Battery Based on Multi-Model Fusion Modeling. *Energy Storage* **2023**, *65*, 107296.
31. Lin, M.; Wu, D.; Meng, J. A Multi-Feature-Based Multi-Model Fusion Method for State of Health Estimation of Lithium-Ion Batteries. *Power Sources* **2022**, *518*, 230774.
32. Chen, T. Research on SOC Estimation Method for Equivalent Circuit Model and Simplified Electrochemical Model of Lithium-Ion Battery. Master’s Thesis, Hunan University, Changsha, China, 2022.
33. Zhang, L. Research on Parameter Identification and SOC Estimation of Equivalent Circuit Model of Lithium Batteries. Master’s Thesis, Tianjin University of Technology, Tianjin, China, 2024.
34. Liu, M. Research on Lithium Iron Phosphate Power Battery Model Based on Deep Learning LSTM Network. Master’s Thesis, Tianjin University of Science and Technology, Tianjin, China, 2023.
35. Wang, W.; Huang, H. Parameter Identification of Battery Considering Current Sensor Bias Fault. *Battery Bimon.* **2025**, *55*, 245–252.
36. Kitagawa, H.; Takagishi, Y.; Nishiuchi, M.; Saeki, K.; Baba, R.; Yamaue, T. Modelling of Thermal Runaway Propagation in Li-Ion Battery Cells Considering Variations in Thermal Property Measurements. *Batteries* **2025**, *11*, 386.
37. Press, W.H.; Teukolsky, S.A.; Vetterling, W.T.; Flannery, B.P. *Numerical Recipes in Fortran 77: The Art of Scientific Computing*, 2nd ed.; Cambridge University Press: Cambridge, UK, 1992; pp. 650–655.
38. Plett, G.L. Extended Kalman Filtering for Battery Management Systems of LiPB-Based HEV Battery Packs: Part 3. State and Parameter Estimation. *J. Power Sources* **2004**, *134*, 277–292.

39. Plett, G.L. *Battery Management Systems, Volume I: Battery Modeling*; Artech House: Norwood, MA, USA, 2015; pp. 46–50.
40. Zhang, Y. Research on Critical Technologies for Power-Battery Charging Control. Master's Thesis, Henan Polytechnic University, Jiaozuo, China, 2023.

**Disclaimer/Publisher's Note:** The statements, opinions and data contained in all publications are solely those of the individual author(s) and contributor(s) and not of MDPI and/or the editor(s). MDPI and/or the editor(s) disclaim responsibility for any injury to people or property resulting from any ideas, methods, instructions or products referred to in the content.