

Supplementary material for

Bisphenol A: quantification in complex matrices and removal by anaerobic sludges

Justus Hardegen ^{1,2}, Patrick Bräutigam ³, Christian Abendroth ^{1,4,*} and Thomas Wichard ^{2,*}

1 Robert Boyle Institute e.V., Jena, Germany

2 Institute for Inorganic and Analytical Chemistry, Friedrich Schiller University Jena, Germany

3 Center for Energy and Environment, Friedrich Schiller University Jena, Germany

4 Institute of Waste Management and Circular Economy, Technische Universität Dresden, Germany

* Correspondence: abendroth.ca@gmail.com, thomas.wichard@uni-jena.de

Table S1 Seeding sludges and plant parameters. DSS, Digested sewage sludge; CoD, Co-digester; OLR, Organic loading rate; VS, Volatile solids; HRT, Hydraulic retention time; understudied; T, Temperature; CSTR, Continuous Stirred-Tank Reactor.

Inoculum		Dry mass	OLR	HRT	Feed	T	System
		%	kg VS m ⁻³ d ⁻¹	d		°C	
Digested sludge	DSS1	2.7	1.80	30	Municipal sewage sludge from CAS treatment. Wastewater partially industrial.	37	CSTR
Digested sludge	DSS2	3.4	0.96	29		37	CSTR
Digested sludge	DSS3	3.4	1.67	19		37	CSTR
Co-digester sludge	CoD1	11.7	3.00	87	Silage, farm manure, and farming waste	37	CSTR
Co-digester digestate	CoD2	3.8	1.00	20- 30	Food wastes. Partially packaged	42	Autonomous hydraulically mixed system
Co-digester leachate	CoD3	3.5	0.90	33	Organic fraction of municipal solid waste	37	Dry fermentation