

Article

Framework for Integration of Health Monitoring Systems in Life Cycle Management for Aviation Sustainability and Cost Efficiency

Igor Kabashkin ^{1,*} , Vladimir Perekrestov ², Timur Tyncherov ² , Leonid Shoshin ²  and Vitalii Susanin ¹ 

¹ Engineering Faculty, Transport and Telecommunication Institute, Lauvas Iela 2, LV-1019 Riga, Latvia

² Sky Net Technics, Business Center 03, Ras Al-Khaimah B04-223, United Arab Emirates

* Correspondence: kiv@tsi.lv

Abstract: In the development of the aviation industry, integrating Life Cycle Management (LCM) with Advanced Health Monitoring Systems (AHMSs) and modular design emerges as a pivotal strategy for enhancing sustainability and cost efficiency. This paper examines how AHMSs, using the Internet of Things, artificial intelligence, and blockchain technologies, can transform maintenance operations by providing real-time diagnostics, predictive maintenance, and secure data logging. The study introduces a comprehensive framework that integrates these technologies into LCM, focusing on maximizing the utilization and lifespan of aircraft components. Quantitative models are developed to compare traditional and modern aviation systems, highlighting the substantial life cycle cost savings and operational efficiencies achieved through these integrations. The results demonstrate up to a 30% reduction in maintenance costs and up to a 20% extension in component lifespan, validating the economic and operational benefits of the proposed integrations. The research underscores the potential of these combined strategies to advance the aviation sector's sustainability objectives, and serves as valuable tools for industry stakeholders, offering actionable insights into the implementation of LCM strategies enhanced by AHMSs and modular design, offering a detailed analysis of the practical implementation challenges.

Keywords: aviation sustainability; life cycle management; aircraft health monitoring systems; modular design; maintenance cost efficiency



Citation: Kabashkin, I.; Perekrestov, V.; Tyncherov, T.; Shoshin, L.; Susanin, V. Framework for Integration of Health Monitoring Systems in Life Cycle Management for Aviation Sustainability and Cost Efficiency. *Sustainability* **2024**, *16*, 6154. <https://doi.org/10.3390/su16146154>

Academic Editors: María Fernández-Raga, Jan C. Bongaerts, Carsten Drebenstedt and Antoine F. Mulaba-Bafubandi

Received: 17 June 2024

Revised: 10 July 2024

Accepted: 15 July 2024

Published: 18 July 2024



Copyright: © 2024 by the authors. Licensee MDPI, Basel, Switzerland. This article is an open access article distributed under the terms and conditions of the Creative Commons Attribution (CC BY) license (<https://creativecommons.org/licenses/by/4.0/>).

1. Introduction

In the development of the aviation industry, the integration of life cycle management (LCM) stands out as a pivotal strategy for enhancing sustainability and cost efficiency. This approach is especially significant given the complex interplay of high-value components and intricate systems that define modern aircraft. By focusing on advanced health monitoring systems (AHMSs) as a new opportunity for LCM and prioritizing sustainability, the aviation sector can significantly improve the efficiency, longevity, and environmental footprint of its operations.

The adoption of AHMSs in aviation represents a transformative shift toward proactive maintenance and operational efficiency. Through the integration of Internet of Things (IoT) sensors, artificial intelligence (AI), and blockchain technology, these systems provide real-time data that enable predictive maintenance strategies, thereby extending the life of aircraft components.

Sustainability in aviation is not merely about compliance with environmental regulations but is a holistic approach that encompasses the entire life cycle of aircraft components—from design and manufacture to operation and eventual decommissioning:

- Designing aircraft and components in modular formats simplifies the process of upgrades and replacements. This not only reduces waste but also allows for the

adaptation to new technologies or performance enhancements without the need for complete overhauls. The use of a modular format will also allow standardized modules to be used across different types and models of aircraft. This, in turn, will significantly reduce the time required for the development and certification of new aircraft types.

- Aircraft should be designed with the end-of-life stage in mind, ensuring that components can be easily disassembled for recycling or refurbishment. This approach minimizes waste and supports the industry's transition toward a circular economy.
- Implementing the use of sustainable materials and adopting greener manufacturing processes play a critical role in reducing the environmental impact. This includes the exploration of alternative fuels and advanced composites that offer durability and recyclability.

The integration of LCM in aviation, with a special emphasis on AHMSs and sustainability, presents a comprehensive strategy for navigating the complexities of the industry. By harnessing the power of emerging technologies and innovative design principles, the aviation sector can achieve significant advancements in both sustainability and cost efficiency.

Research in this area is thus highly relevant as it can provide actionable insights and frameworks that propel the industry toward these twin objectives of sustainability and cost efficiency. The primary purpose of this paper is to explore, analyze, and validate the effectiveness of integrating LCM with AHMSs and modular design in enhancing the sustainability and cost efficiency of aviation operations.

The study will focus on several key areas: modular design in aircraft construction, AHMSs as new operational opportunities of LCM, and maximizing component utilization and life extension.

Implementing these LCM strategies in aviation requires a unified effort from all stakeholders, including manufacturers, airlines, and regulatory agencies. It also necessitates significant investment in research and a commitment to training personnel on new technologies and systems. However, the benefits—reduced environmental impact, enhanced cost efficiency, and increased adaptability to future technological advances—make a compelling case for the widespread adoption of life cycle management in the aviation industry. Through such integration, the sector not only aligns itself with global sustainability goals but also ensures its long-term viability and success in a changing world.

The intersection of LCM, AHMSs, and modular design in aviation has been the focus of extensive research, driven by the industry's need to enhance sustainability and operational efficiency. Several studies have explored the implementation and benefits of these integrated strategies.

1.1. LCM in Aviation

The scientific literature on the state of the art in life cycle management in aviation emphasizes the importance of assessing the environmental impact of aircraft throughout their life cycle. Life cycle assessment (LCA) methods play a crucial role in evaluating the sustainability and environmental footprint of aviation operations, particularly considering the industry's significant contribution to greenhouse gas emissions.

In the early stages of aircraft design, a comprehensive assessment is needed to achieve future climate targets. To appropriately model and evaluate these measures, a holistic approach through the LCA within conceptual aircraft design is considered essential. The methodological foundation for performing an LCA was established in the 1990s with the standards [1,2], which define specific terms and explain the general procedure for conducting an LCA. Although several aircraft assessments have been conducted in accordance with these standards, they exhibit significant discrepancies in terms of the data, software, and methodology used, limiting their comparability [3–6]. These inconsistencies are also evident across different industries. To address this issue, initiatives like the Life Cycle Initiative hosted by the UN Environmental Program are extending guidelines globally. The Global Guidance on Environmental Life Cycle Impact Assessment Indicators (GLAM) [7] and the Global LCA Data Access (GLAD) [8] projects aim to enhance global consensus on

environmental life cycle impact assessment indicators and improve data accessibility and interoperability. These projects seek to eliminate discrepancies in assessment methodology and data. However, there are currently no projects focused on establishing guidelines for the implementation of and data handling in tools and software itself [9]. According to the FAQ of GLAD, achieving easy import of GLAD data into LCA software is a long-term goal and part of the vision, but this is not yet a reality. Eventually, GLAD should be interoperable with LCA software, potentially integrating database access into LCA software tools.

A comprehensive book [10] covers the application of LCA methods in aviation, providing a detailed overview of the existing research on the topic. The Scholarly Community Encyclopedia also provides a brief overview of the existing research on LCA in aviation, emphasizing its importance in assessing the environmental impact of aircraft [11].

The paper [12] introduces a new generic environment for economic and operational assessment of aircraft and related products, which uses a discrete event simulation to model the entire life cycle, from order to disposal. It highlights the modular architecture of the model, key features, and how it can be applied using a case study of on-wing engine cleaning procedures, assessing impacts on engine health, fuel efficiency, and economic viability. The framework is designed to analyze not only physical products but also operational procedures, maintenance strategies, and decision-making algorithms, illustrating their life cycle impacts on aircraft and systems.

The authors of paper [13] developed a computer system for constructing and certifying avionic onboard devices and their software, involving software planning, creation, and integration processes. The paper also explores a new method for predicting vulnerabilities in integrated avionic systems and discusses the implementation of DO-178C and other standards in actual software projects, including a helmet-mounted flight parameter display system and a graphics computer for managing system operating modes.

The paper [14] emphasizes the importance of early and rapid environmental assessment of new aircraft concepts to promote climate-friendly technologies. It discusses a life cycle assessment (LCA) approach within aircraft design and compares two LCA tools—one, a simplified version for educational purposes, and the other, a more advanced automated interface developed for comprehensive environmental impact analysis. The study establishes baseline metrics for evaluation and underscores the necessity of choosing the right tool based on the desired level of detail and expertise required for accurate environmental assessment.

Digital twins, virtual replicas integrated with real-time sensor data, operational inputs, and historical records, enable the continuous calibration and validation of models. The article [15] explores how digital twins, enhanced by machine learning, can improve the accuracy and reliability of numerical modeling tools in aircraft structural design. These updated models facilitate real-time monitoring and precise damage assessment, improving structural health, safety, and reliability. The article highlights the use of advanced machine learning techniques, including physics-informed neural networks, to manage uncertainties and enhance decision-making in design and maintenance operations, ultimately contributing to safer and more efficient aviation operations.

The paper [16] discusses the critical aspects of aviation technology life cycle management, including basic international standards outlined in ISO/IEC/IEEE. It defines the main objectives and stages of system life cycle management, emphasizing the importance of life cycle costs, which include cost categories, breakdown structures, and estimation methods. It also addresses the prerequisites for the successful implementation of life cycle management in aviation companies and the broader aerospace industry, highlighting stakeholder involvement.

1.2. Advanced Health Monitoring Systems of Aircraft

The integration of AHMSs in aviation represents a significant shift toward proactive and predictive maintenance. By utilizing IoT sensors, AI, and blockchain technologies, AHMSs provide real-time data on the health of aircraft components, enabling predictive

maintenance and operational efficiency. Studies have shown that AHMSs can drastically reduce unexpected maintenance costs, minimize downtime, and extend the service life of aircraft components. These systems allow for continuous monitoring and data analysis, which are crucial for timely maintenance interventions and enhancing the overall reliability of aviation operations.

AHMSs focus on continuously inspecting maintenance-critical components, presenting new opportunities for designing lighter, safer, and eventually cleaner aircraft. AHMSs aim to avoid or reduce typical accommodations used during design, such as composite knockdown factors, and lifetime management practices like strict scheduled inspections, resulting in cost-effective maintenance [17]. Due to the promising impact on aircraft operation management, various approaches and technologies have been developed over the past decades. Notably, the use of permanently installed sensors on or embedded within the airframe has garnered significant scientific attention, as it provides both global and local feedback on structural health. This method enables on-demand, in situ measurements, allowing for trend monitoring in system behavior [18]. Time- or frequency-domain data collected over the aircraft's lifetime can help identify anomalies, track their location and severity, and estimate the residual useful life of monitored components, potentially extending inspection intervals [19].

Researchers have explored several diagnostic techniques for aircraft, including ultrasonic guided waves [20,21], guided electromagnetic waves [22], electromechanical impedance [23], and vibration response [24]. AHMSs can be passive, activated by the aircraft boundary layer [25], or active, enabled by the system [26]. In all cases, a damage feature sensitive to defects in the observed structure is used. The damage indicator correlates measurements from sensor clusters with the presence and extent of damage. Various monitoring methods can evaluate specific damage types, and multi-sensor approaches have gained community interest [27]. As a result, integrating transducers onboard is essential for effective system monitoring. This concept extends to aircraft systems like actuators, where existing or new transducers can assess system health [28].

Understanding the reliability and affordability of AHMSs is crucial for their integration. The lack of reliability and cost-benefit assessments currently limits the industrial deployment of on-condition maintenance systems. Reliability depends on the specific AHMS approach and has been increasingly addressed through collaborations between AHMS experts and reliability specialists [29]. This collaboration helps determine the minimum detectable damage size during an aircraft's lifetime, guiding the implementation level of AHMSs. Conversely, cost-benefit analysis is challenging, as it involves estimating both the benefits (in terms of maintenance and structural design) and costs (system revenue and mass increase). Therefore, a multidisciplinary analysis that considers health management aspects and design and performance parameters is necessary. This analysis should be independent of the AHMS technique and technology used, treating cost and benefit sources as aseptic inputs. This approach provides a roadmap for efficient AHMS integration and implementation, driving system design to be profitable rather than solely effective.

One major challenge in recent aircraft design is the use of novel materials like composites for load-bearing structures. While composites offer tailored properties and performance improvements, their anisotropy poses critical issues. Specifically, the stacking characteristics of laminates and lower strength in the normal direction make composites susceptible to failure under dynamic loads perpendicular to the surface, leading to delamination due to high interlaminar shear stress [30–32]. Low-velocity impacts can randomly cause failures, threatening aircraft missions if not properly addressed. Safety-critical aspects require appropriate design, often driven by damage tolerance approaches that account for undetectable damage, raising questions about weight savings through efficient damage detection.

The aviation industry's safety-by-design philosophy, established in the 1980s, includes the damage tolerance approach, combining inspection with structural design concepts to ensure safety while following inspection procedures [33–35]. However, this approach does not fully exploit material capabilities due to inspection sensitivity and costs, leading to

costly maintenance tasks and increased direct operating costs from excess safety weight and critical operations. AHMSs offer conceptual benefits by continuously monitoring aircraft for damage, potentially detecting damage below allowable limits. This enables more flexible and faster maintenance schedules, increased safety, and more relaxed design constraints.

Fioriti et al. [36] found that effective prognostics could increase aircraft availability and airliner profit. However, exploiting AHMS-derived information for condition-based maintenance is critical. Current discussions on integrating real-time monitoring and relative cost–benefit analysis are limited and often unrealistic, relying on wireless connections, onboard sensors, and ground-based computing stations [37,38]. Overcoming technological gaps in AHMS operation can prevent visual and non-destructive inspections, which cause maintenance downtime, with the remaining downtime from health management tasks [39]. Efficient AHMSs can reduce the need for expert intervention, but the benefits are less promising for aging aircraft like the Boeing B737NG, where maintenance benefits are offset by the sensor system’s weight. Cost-effective AHMSs require improved sensor technology or adjustments to aircraft design concepts.

Dienel et al. [40] explored the benefits of integrating AHMSs into the design loop, leading to more relaxed design constraints and continuous monitoring. They estimated a 9% weight reduction with ultrasound-based AHMSs by adjusting damage tolerance criteria, resulting in a net 5% weight saving after accounting for the SHM system’s mass. Detailed investigations showed that multidisciplinary analysis could provide options based on the number of sensors and achievable benefits [41].

1.3. Modular Design in Aircraft Construction

Modular design in aircraft construction facilitates easier upgrades, maintenance, and recycling of aircraft components. This approach aligns with the principles of a circular economy by promoting the reuse and recycling of parts, thereby reducing waste and conserving resources. The modular architecture allows for the easy replacement of outdated or worn-out modules without overhauling the entire system, which can significantly reduce maintenance costs and downtime [42]. Research has demonstrated that modular design, when integrated with AHMSs, enhances the adaptability and sustainability of aircraft operations.

The scientific literature on the state of the art in Modular Design in Aircraft Construction focuses on the application of modular design principles to enhance the efficiency and flexibility of aircraft manufacturing processes. Modular design in aircraft construction involves the systematic partitioning of aircraft components into modules that can be easily assembled, disassembled, and replaced, leading to improved maintenance, customization, and overall aircraft performance.

A systematic literature review on digital twins for aircraft maintenance and operation explores the integration of IoT-enabled modular architectures in the aviation industry, emphasizing the role of digital twins in enhancing maintenance efficiency and operational performance [43].

The literature on aircraft active flutter suppression discusses the challenges and advancements in active control design for aircraft, focusing on the modular design philosophy and its implications for aircraft construction and performance [44]. The review of global views on modular design research offers a generic set of platform design steps for developing modular product concepts, providing a framework for implementing modular design principles in aircraft manufacturing [45].

1.4. Practical Applications and Case Studies

The combination of AHMSs and modular design within an LCM framework has been shown to offer substantial benefits in terms of sustainability and cost efficiency. Practical applications of these integrated strategies are already emerging in the industry. Major aircraft manufacturers like Boeing and Airbus have begun incorporating AHMSs and modular design into their aircraft, demonstrating significant improvements in maintenance

scheduling, cost savings, and environmental performance. Case studies from these companies provide valuable insights into the real-world benefits and challenges of implementing these advanced systems.

The use of Life Cycle Assessment (LCA) for evaluating the ecological impacts of aircraft and their operations is an established practice. Numerous studies have explored this topic, assessing environmental impacts across a diverse range of applications. For instance, in 2013, Atılğan et al. [46] carried out an environmental impact assessment of a turboprop engine through exergo-analysis, assigning environmental performance ratings to each engine component based on their exergo rates, with the combustion chamber noted as the most impactful component.

Vinodh et al. [47] conducted an LCA on a turbine blade, pinpointing environmental concerns early in the manufacturing process, thereby aiding in the development of eco-friendlier aircraft components. Şohret et al. [48] evaluated the environmental impacts of routine maintenance on a Cessna 172 Skyhawk, finding significant contributions to global warming potential, acidification, photochemical oxidation from fuel use, and ozone layer depletion from electricity consumption. Altuntaş et al. [49] compared the environmental impacts of using an auxiliary power unit (GPU) and a ground power unit for ground power at airports, with GPU showing significantly lower impacts on human health, ecosystem quality, and resource use.

Material choices in aircraft also influence environmental impacts. Studies have assessed various materials used in aircraft construction such as fuselage segments [50–52], elevators [53], interior panels [54], and lightweight trolleys [55], typically focusing on specific life cycle phases or materials to suggest process improvements. These studies do not fully encompass comprehensive LCA due to the limited consideration of interactions and dependencies between different life cycle phases.

Comprehensive LCA studies that evaluate the aircraft across all life cycle phases are often extensive and originate from master's theses or dissertations. Johanning [56] explored integrating environmental impact assessments into the conceptual design phase of aircraft, concluding that the operational phase, primarily due to fuel combustion, has the most substantial environmental impact. Similarly, Howe et al. [57] assessed the manufacture, operation, and end of life of an Airbus A320, with operation comprising 99% of the environmental impact. Facanha and Horvath [58] analyzed the environmental impacts of a Boeing B747 freighter across its entire life cycle and associated airport activities, focusing mainly on air pollutants.

Comparative studies like those by Chester [59] and Cox [60,61] (detailed further in Jemioło's master's thesis [62]) evaluated environmental impacts across different transportation modes using Economic Input–Output Life Cycle Assessment (EIO-LCA), a method that, despite being approximate, includes broad system boundaries and typically shows higher impact values.

In a comprehensive study by Lopes [63], an LCA of an Airbus A330 was detailed, providing a foundational inventory for the manufacturing phase used in subsequent research. Lewis [64] compared different flight scenarios using a hybrid approach of Process-Based LCA and EIO-LCA. Jordão [65] analyzed the manufacturing, maintenance, and operational phases of an Airbus A330 and a Boeing B777, highlighting a significant ecological impact from the maintenance phase based on airport energy consumption. Recently, Fabre et al. [66] conducted an LCA of an Airbus A320, considering manufacturing, airport construction, and operations with different fuel types, but omitted maintenance and end-of-life phases due to data scarcity. Schäfer [67] aimed to develop a methodology for life cycle sustainability assessment that includes environmental and economic evaluations across all phases. Lastly, Dallara et al. [68] utilized a parametric Streamlined LCA tool to assess the environmental impact of producing and operating an Airbus A320 and a Boeing B737, comparing results with those from conventional LCA and EIO-LCA methods.

1.5. Life Cycle Impact on Aviation Sustainability

Life cycle impact assessment has become an increasingly important tool for evaluating the environmental sustainability of aviation operations. Understanding the life cycle impact of aviation is crucial for developing strategies to mitigate these effects and promote sustainability within the sector. This subsection reviews the existing literature on the environmental impacts associated with different stages of an aircraft's life cycle.

Recent developments in the field of aviation emissions have led to the creation of advanced, fully comprehensive Life Cycle Assessment (LCA) methods for commercial aircraft [5,56,66]. These methods aim to model the entire life cycle of aircraft using various parameters, allowing them to provide a detailed representation of environmental impacts through multidimensional environmental indicators. The primary users of these innovative methods are experts in both academic and practical fields.

One notable method, developed by Johanning [56], integrates LCA into the preliminary design phase of aircraft, offering a complete cradle-to-grave model. This approach, however, presents challenges, particularly in the collection of necessary data. Johanning's method encompasses all aircraft subsystems and facilitates the simplified parameterization of the aircraft cabin. It was specifically utilized in the environmental assessment of a turboprop aircraft design.

Additional methodologies have been developed to compare various fuel types and propulsion systems [5]. For instance, Scholz [69] introduced a dynamic method to compare traditional kerosene with hydrogen fuels. Meanwhile, Caers [70] devised a method that considers aerodynamic effects and engine utilization to further enhance the accuracy of environmental impact assessments.

The paper [71] introduces a dynamic method designed to calculate the environmental impacts of different aircraft cabin configurations, aiding decision-makers in the aircraft industry as they strive to meet emission reduction targets.

The decision support tool designed to help aviation industry stakeholders select materials that optimize sustainability, considering the type of aviation fuel used and circular economy principles, is proposed in [72]. The tool integrates life-cycle-based metrics for ecological and economic impacts and includes a circular economy indicator (CEI) that assesses material quality and its degradation through recycling.

The work [73] significantly advances the eco-design of aircraft by proposing a design process where sustainability is the primary driver. This process integrates sustainability from the initial stages of design, utilizing a comprehensive and quantifiable sustainability index that includes technological, environmental, economic, and circular economy dimensions. The methodology's practicality is demonstrated through the design of a composite plate with both pristine and recycled fibers, and further validated using a hat stiffener from the aviation industry.

The paper [74] addresses the environmental and economic challenges in aircraft design by proposing a new method that integrates both dimensions to assess sustainability throughout an aircraft's service life. The use of composite materials is highlighted to reduce aircraft weight and improve fuel efficiency, with a particular focus on reducing air pollution from engines. The method introduces a "green index" that combines maintenance costs and environmental impact to identify the most sustainable design solution.

Current research on aviation life cycle management often treats sustainability, health monitoring systems, and modular design as separate concerns, lacking a comprehensive framework that integrates these elements. This study aims to address this gap by proposing an integrated approach that combines LCM with AHMSs and modular design principles. While existing literature has explored these concepts individually, there is a dearth of research examining their synergistic potential for enhancing sustainability in aviation. This paper seeks to fill this void by demonstrating how the integration of AHMSs and modular design within an LCM framework can significantly improve both environmental sustainability and cost efficiency in aviation operations.

The proposed approach extends beyond current practices by offering a holistic solution that addresses resource conservation, emissions reduction, and circular economy principles throughout an aircraft's life cycle. By providing quantitative models and decision-making frameworks, this study aims to bridge the gap between theoretical concepts and practical implementation, offering actionable insights for industry stakeholders.

This research contributes to the broader discourse on sustainable aviation by illustrating how technological integration can lead to tangible environmental benefits, including extended component lifespans, reduced waste, and improved energy efficiency. The paper not only addresses the immediate needs of the aviation industry but also sets the stage for a more sustainable and environmentally responsible future in aviation, providing a roadmap for navigating the complex interplay between operational demands and environmental imperatives.

This paper is structured as follows: Section 2 describes the materials and methods used in this study, including the methodology for integrating AHMSs with LCM and modular design. Section 3 presents the results of the analysis, including quantitative models comparing traditional and modern aviation systems. Section 4 discusses the implications of findings for enhancing sustainability and cost efficiency in aviation, as well as the limitations of the current study and areas for future research. Section 5 concludes the paper by summarizing the key contributions and potential impact of this work on advancing life cycle management practices in the aviation industry.

2. Materials and Methods

2.1. Methodology

This study employs a mixed-methods approach combining both qualitative and quantitative research methods to develop and validate a comprehensive framework for integrating AHMSs with LCM and modular design in aviation. The research design is structured into three main phases: literature review, model development, and empirical validation.

In the introduction section, a systematic literature review was conducted to establish the current state of research on LCM, AHMSs, and modular design in aviation. Sources included peer-reviewed journals, conference papers, industry reports, and relevant books. The review focused on identifying key technologies, methodologies, and best practices that have been applied in aviation maintenance and sustainability.

Based on the insights gathered from the literature review, a conceptual framework was developed to integrate AHMSs with LCM and modular design. The framework focuses on leveraging IoT, AI, and blockchain technologies to enhance real-time diagnostics, predictive maintenance, and secure data logging. The framework design included detailed mapping of how IoT sensors, AI algorithms, and blockchain can be integrated within the LCM framework, design of monitoring protocols for critical aircraft components using AHMSs, and development of predictive maintenance models based on real-time data analytics. Quantitative models were developed to compare traditional and modern aviation systems in terms of life cycle costs and operational efficiencies, and metrics were defined to evaluate the impact of AHMS integration on maintenance costs, component lifespan, and overall operational efficiency.

The empirical validation phase involved the application of the developed framework in real-world scenarios through case studies and simulations. Real-world aviation scenarios where AHMSs and modular design have been implemented were selected, and data were collected from industry partners and case studies were analyzed to validate the proposed framework. Data on maintenance schedules, component failures, operational efficiencies, and cost savings were collected from these case studies.

The findings from the data analysis were interpreted to draw conclusions about the effectiveness of integrating AHMSs with LCM and modular design. The practical implications for the aviation industry were discussed, and recommendations were provided for future research and implementation. All data collection and analysis procedures were conducted in accordance with ethical guidelines. Informed consent was obtained from all

industry partners involved in the case studies, and confidentiality of sensitive data and data anonymization was maintained. This methodology ensures a rigorous and comprehensive approach to developing and validating the proposed framework, providing robust evidence for its effectiveness in enhancing sustainability and cost efficiency in the aviation industry.

2.2. Fundamentals of AHMSs and Integrating LCM for Sustainability and Cost Efficiency in Aviation

As the aviation industry continues to expand, its impact on the environment and its operational costs demand urgent attention. To address these issues, the integration of AHMSs within the framework of LCM emerges as a transformative strategy. This Section explores the fundamentals of AHMSs, the principles of LCM, and their integration for sustainable and cost-efficient aviation operations.

2.2.1. Aircraft Life Cycle Management: Principles, Strategies, and Challenges

LCM of aircraft is a comprehensive approach that oversees an aircraft's journey from the design to its final descent from operational service (Figure 1).




Figure 1. The key stages of an aircraft's life cycle.

The following lists the key stages of an aircraft's life cycle and the associated considerations for each stage, focusing on environmental, cost, and sustainability aspects:

- **Design.** This initial stage considers environmental restrictions, materials choice, and budget control. The focus is on creating an aircraft that meets environmental standards while optimizing costs.
- **Production.** During manufacturing, environmental requirements are adhered to, and a recycling approach is implemented. Budget optimization is a key consideration to ensure cost-effective production.
- **Operation (Initial):** As the aircraft enters service, environmental limitations are observed. Green modifications may be implemented to improve sustainability, and cost-control measures are put in place.
- **Maintenance.** A LEAN/Continuous Improvement (CI) approach is adopted for maintenance processes. Waste control is emphasized, and cost optimization strategies are implemented to reduce maintenance expenses.
- **Operation (Ongoing).** Throughout the aircraft's operational life, a green policy is followed. The use of sustainable fuels is promoted, and ongoing cost-control measures are maintained.
- **Retirement.** As the aircraft nears the end of its service life, environmental requirements are considered for the retirement process. A parts-out and reuse strategy is employed to maximize value and minimize waste. Cost-saving measures are implemented during this phase.
- **Disposal.** The final stage involves green dismantling practices to minimize environmental impact. Materials from the aircraft are recycled where possible. This stage also focuses on encashment or recovering value from the retired aircraft.

This life cycle approach demonstrates a comprehensive strategy for managing aircraft from conception to disposal, with a consistent focus on environmental sustainability, cost management, and material efficiency throughout each stage.

LCM in aviation is anchored in the following core principles:

- LCM considers all stages of an aircraft's life, from design, production, operation, and maintenance, to retirement and disposal.

- A key principle of LCM is sustainability, ensuring that operations minimize environmental impact through efficient resource use and adherence to environmental regulations.
- LCM aims to maximize financial efficiency by reducing costs at every life cycle stage without compromising safety or performance.

2.2.2. Strategies in Aircraft LCM

Aircraft LCM strategies encompass a range of approaches aimed at optimizing the entire life cycle of an aircraft, from conception to retirement. These strategies include the following:

- Design for Sustainability, which focuses on creating airframes and components that are durable, maintainable, and recyclable, often employing modular design to facilitate easy upgrades and replacements, thereby extending the aircraft's operational life and reducing waste.
- Sustainable Manufacturing, which scrutinizes production processes for efficiency and environmental impact, balancing quality with ecological and economic considerations in material selection, production techniques, and assembly methods.
- Operational Efficiency, which concentrates on maximizing fuel economy, optimizing routes, and managing load to reduce costs and environmental impact during the aircraft's service life.
- Advanced Maintenance Strategies, incorporating scheduled maintenance carefully planned to ensure safety and reliability, often enhanced by the integration of advanced health monitoring systems to improve predictability and efficiency of maintenance operations.
- Life Extension Programs, including overhaul and refurbishment initiatives to revitalize aging aircraft and prolong their service life.
- End-of-Life Management, focusing on the complex process of decommissioning aircraft, aiming to recycle and reuse as much of the aircraft systems as possible, following a circular economy model.
- Continuous Improvement and Innovation, which involves ongoing research and development to incorporate new technologies and methodologies that can enhance the aircraft's performance, efficiency, and sustainability throughout its life cycle.

These strategies collectively aim to optimize every phase of an aircraft's existence, ensuring maximum value delivery while adhering to stringent safety standards and sustainability goals, and adapting to the evolving challenges of the global aviation sector.

2.2.3. Architecture and Functions of Advanced Health Monitoring Systems in Aviation

In the technologically driven world of aviation, AHMSs stand as a testament to the industry's relentless pursuit of safety, efficiency, and reliability. These systems are intricate networks of hardware and software designed to ensure that aircraft operate at peak performance while preempting potential issues.

The foundational layer of AHMS architecture is its extensive sensory network. These sensors are the frontline operatives, deployed strategically across various critical components of an aircraft including the engines, fuselage, and control systems.

The types of sensors include vibration sensors, temperature gauges, pressure transducers, and accelerometers, each meticulously capturing data pertinent to their specific location and function.

Additionally, it is worth highlighting built-in test (BIT) equipment. BIT equipment enables the self-diagnosis of aircraft components (mainly avionics) and provides data for more accurate defect diagnostics and correction. The system includes various tools such as multimeters, oscilloscopes, discharge probes, and frequency generators, which facilitate self-testing and diagnostics.

Data acquired by the sensors and components are transmitted via aircraft data networks such as the aircraft condition monitoring system (ACMS) or the avionics full duplex switched Ethernet (AFDX). The transmission of data is a blend of real-time streams for immediate analysis and recorded logs for subsequent, more comprehensive evaluations.

Onboard computers and processing units act as the immediate analytical minds of AHMSs, sifting through the real-time data to provide actionable intelligence to the cockpit and maintenance crew.

These systems apply algorithms to identify anomalies, trends, or patterns that indicate the health status of various aircraft components.

Upon landing, the collected data are often offloaded to ground-based systems where more powerful computing resources perform deeper analyses. The development of satellite Internet allows data to be transmitted in real time to ground stations, enhancing the AHMS's capabilities.

Advanced data analytics comes into play, utilizing machine learning and predictive modeling to not only understand past performance but also forecast future maintenance needs. The orchestration of the sensory data and analytical processes informs the maintenance of decision support systems. These are integral to the AHMS, providing recommendations for maintenance actions, part replacements, and other interventions.

Maintenance planning tools integrated with the AHMS ensure that the right resources are allocated efficiently, minimizing downtime, and optimizing the repair and overhaul processes.

The main functions of AHMSs are as follows:

1. Real-Time Performance Monitoring.
2. Fault Diagnosis and Prognosis.
3. Predictive Maintenance.
4. Efficiency Optimization.
5. Life Cycle Management.

Figure 2 illustrates the architecture and data flow of AHMSs for aircraft. It shows data being collected from the Avionics systems, the WDAR (Wireless Digital AIDS Recorder unit), and the FMDE (Flight and Maintenance Data Exchange unit). The data from these onboard systems flow into the central analytical IT System, which is usually developed by the original equipment manufacturers. The analytical IT System also integrates data from the airline's maintenance information systems (MIS) as well as fleet-wide data from the OEMs. The Analytical IT System performs key AHMS functions such as real-time performance monitoring, fault diagnosis and prognosis, and predictive maintenance.




Figure 2. Architecture and data flow of AHMSs.

AHMSs are critical for real-time performance monitoring, continuously providing pilots and ground crew with insights into the aircraft's health. This ensures operational decisions are informed by the most current and comprehensive data.

The systems are adept at fault diagnosis, identifying specific issues within aircraft systems quickly and accurately. Beyond diagnosis, they also offer prognosis capabilities, forecasting the future health state of components based on current trends.

Central to the AHMS's functionality is its predictive maintenance, a paradigm shift from scheduled to condition-based upkeep. By predicting when a component is likely to fail or require service, AHMSs save on costs and prevent operational disruptions.

Efficiency optimization is another key function, as AHMSs contribute to fine-tuning the operation of various components for optimal performance. This leads to fuel savings, reduced emissions, and better utilization of the aircraft.

It can be a new important function of AHMSs. Through the integration of extensive data and analytics, AHMSs can support the life cycle management of aircraft components and the aircraft itself, promoting a longer service life, better resale value, and effective decommissioning strategies.

This function will be a key element of discussion within the frame of this paper. The fusion of AHMSs with life cycle management practices is a potent combination for advancing sustainability and cost efficiency in aviation. It represents a forward-thinking approach that not only addresses the immediate needs of the industry but also sets the stage for a more sustainable and economically sound future in aviation. By committing to the fundamentals of AHMSs and LCM, the industry can navigate the twin challenges of environmental impact and operational costs, ensuring its growth is both responsible and resilient.

2.3. Framework for Aviation Life Cycle Management: Integrating AHMSs for Enhanced Performance and Sustainability

With the advent of AHMSs, a new framework for aviation LCM can be proposed (Figure 3). This framework is predicated on the integration of modern technologies to enhance the lifespan, operational efficiency, and sustainability of aircraft. This Section outlines a tripartite framework that hinges on modular design, operational opportunities through technology convergence, and maximization of component lifespan with the use of AHMSs with the purpose of sustainability and cost efficiency in integrating life cycle management.




Figure 3. Framework for aviation LCM on the base of integrating AHMSs.

1. Modular design and AHMSs in aircraft construction

The first component of the framework revolves around the adoption of modular design in aircraft construction, intertwined with the capabilities of AHMSs. Modular design refers to the development of aircraft in such a way that various components are interchangeable, replaceable, and upgradable, without the need for significant overhauls of the entire system.

Modular design allows for swift adaptation to changing technological and operational demands, such as the integration of new AHMS components or software updates.

The modularity of design simplifies the maintenance and repair process, whereby specific modules can be serviced or replaced in isolation, reducing aircraft downtime and maintenance costs.

Modular components are equipped with sensors and data processing units from AHMSs, which monitor the health and performance of each module. This integration

facilitates a predictive maintenance approach and enables a more detailed understanding of each component's life cycle.

The utilization of standardized functional modular components in aircraft development will significantly reduce certification timelines. Manufacturing modular components applicable across different types and models of aircraft will transition production from small-scale to mass production, consequently substantially reducing production costs and environmental impact.

2. New operational opportunities through technology convergence

The convergence of cutting-edge technologies, supported by AHMSs, ushers in new operational opportunities. AHMSs serve as the nexus that integrates diverse technologies—such as IoT, AI, data analytics, and more—to enhance aviation operations.

AHMSs analyze data to predict when a component might fail or require service, thereby optimizing maintenance schedules and resource allocation.

The analysis of AHMS data in conjunction with aircraft operational environment data (weather, operations geography, type of airline, airport infrastructure conditions, and all possible data that influence the aircraft in its operations) extends capability in the development of customized maintenance programs. Such an approach should allow inspection maintenance intervals for systems and components to change in conformance with the level of influence of the aircraft's operational environment on each of them, separately. A fully customized maintenance program will decrease aircraft downtime with enhanced safety.

The ability to process and interpret vast amounts of data in real time enables quicker and more informed decision-making about operation, diagnostics, maintenance, and predictive analytics during LCM.

3. Maximizing component utilization and life extension

The third component of the framework focuses on leveraging AHMSs to maximize the utilization and extend the life of aircraft components. This is achieved through the continuous monitoring and analysis of component health, which informs maintenance decisions.

By accurately determining the condition of components, AHMSs enable airlines to extend their service life, delaying the need for replacements and reducing waste.

AHMS data assist in optimizing the use of each component, ensuring that it operates within the ideal parameters to avoid undue stress and wear.

An aircraft is an expensive object that is in operation for a long time. During the life cycle of the aircraft, its individual components and systems are modernized, and replaced with new or used units with their corresponding certification to ensure all airworthiness requirements. After the end of the life cycle of the aircraft as a whole, individual components may well be reused if their reliability meets the established airworthiness requirements. In particular, the most expensive part is the engines, which can be replaced several times during the aircraft's life cycle. This also applies to other aircraft systems.

The ability to use components more effectively and for longer periods directly correlates with sustainability goals, as it results in less frequent manufacturing of spare parts and a reduction in the resource footprint.

The proposed framework encapsulates a holistic approach to aviation life cycle management by leveraging the advanced capabilities of AHMSs. It embodies the transition from a traditional, reactive aviation industry to a proactive, predictive, and sustainable one. By embracing modular design, capitalizing on the convergence of innovative technologies, and maximizing component lifespan, the aviation industry can achieve significant strides in performance, cost reduction, and environmental stewardship.

3. Results

The framework outlined in Figure 3 demonstrates the integration of AHMSs and modular construction within LCM as a transformative approach to improving the sustainability and cost efficiency of aviation operations.

In the following Sections, we will delve deeper into each of these components, exploring their specific functionalities, benefits, and the technologies that underpin them. This detailed examination will illustrate how the integrated framework facilitates a more sustainable and cost-effective approach to aviation life cycle management.

3.1. The Symbiosis of AHMSs and Modular Design in Aircraft Construction

The aviation industry is witnessing a paradigm shift with the adoption of AHMSs coupled with modular design approaches in aircraft construction. This synergy is poised to redefine the standards of efficiency, sustainability, and adaptability in aviation. The integration of AHMSs into a modularly designed framework lays the foundation for an agile response to technological advancements, maintenance, and life cycle management.

Modular design in aviation is a strategic approach that compartmentalizes aircraft into discrete, interchangeable units or modules. This methodology offers flexibility in the design and maintenance of aircraft, presenting several advantages:

- Modular design allows for the easy replacement or upgrading of individual components, rather than entire systems, making aircraft more adaptable to changes in technology and market demands.
- By facilitating targeted repairs and upgrades, modular design can significantly reduce the costs associated with aircraft maintenance and downtime.
- Modular systems can be more easily disassembled, repaired, refurbished, or recycled, leading to a reduction in material waste and promoting a circular economy within the aviation sector.

The incorporation of AHMSs into a modular design enhances the operability and longevity of aircraft by providing real-time diagnostics and prognostics of the aircraft's health:

- AHMSs, with their network of sensors and diagnostic algorithms, offer constant surveillance of aircraft components, providing vital data that inform maintenance decisions and module replacements.
- By predicting maintenance needs, AHMSs enable proactive servicing of modules, which can prevent cascading failures and prolong the lifespan of the aircraft.
- The data collected by AHMSs can lead to the continuous improvement of module design, with insights into wear patterns and operational stresses informing future design iterations.

3.1.1. General Model with Decision-Making Criteria for Modular Design and AHMSs in Aircraft Construction

To evaluate and compare a traditional aviation system with a modular design that integrates AHMSs, a structured mathematical model must be developed. This model should quantitatively assess the benefits of modular design in terms of life cycle cost savings, operational efficiency, and system flexibility. The decision-making criteria will focus on these areas to determine the preferable architectural choice.

(A) Decision metrics

1. Development Cost Difference

$$\Delta C_{dev} = C_{dev,tr} - C_{dev,AHMS} \quad (1)$$

where $C_{dev,tr}$ and $C_{dev,AHMS}$ represent the development costs for the traditional and modular systems with AHMSs, respectively. A negative ΔC_{dev} indicates higher initial costs for the modular system due to the complexity of integrating modular designs and AHMSs. Additionally, the cost will increase due to the implementation of the component's capability to be applicable across different types of aircraft.

2. Maintenance Cost Reduction

$$\Delta MC = MC_{tr} - MC_{AHMS} \quad (2)$$

where MC_{tr} and MC_{AHMS} are the cumulative maintenance costs over the system's operational life. The modular system, supported by AHMSs, typically incurs lower maintenance costs due to its ability to precisely target maintenance needs and easily replace individual modules.

3. Operational Efficiency Improvement

$$\Delta OE = OE_{AHMS} - OE_{tr} \quad (3)$$

This metric measures the improvement in operational efficiency, considering factors like downtime reduction and faster turnaround times due to easier module replacements. OE_{AHMS} and OE_{tr} are operational efficiency values for the modular and traditional systems, respectively.

4. Life Cycle Cost Savings

$$\Delta LCC = LCC_{tr} - LCC_{AHMS} \quad (4)$$

where LCC_{tr} and LCC_{AHMS} represent the total life cycle costs of the traditional and modular systems with AHMSs, respectively. A positive ΔLCC indicates overall life cycle cost savings when using the modular system with AHMSs.

$$LCC_i = C_{dev,i} + \int_0^T M_{annual,i}(t)dt - BOE_i \quad (5)$$

$$i = \{tr, AHMS\}$$

where $M_{annual,i}$ represents the annual maintenance cost for i architecture, which involves several steps that account for various factors influencing maintenance expenses. These costs typically include direct labor, materials, overheads related to maintenance activities, and any indirect costs such as those arising from downtime or decreased efficiency during maintenance periods. BOE_i is the benefit from operational efficiency. Operational efficiency encompasses various factors, including reduced downtime, improved asset utilization, and lower operational costs, which contribute directly and indirectly to the financial bottom line.

(B) Decision rule

Choose the modular/AHMS-supported system if it satisfies the following conditions:

- Indicates that the total life cycle cost savings justify the modular investment $\Delta LCC > 0$.
- Demonstrates maintenance cost savings $\Delta MC > 0$.
- Shows clear operational efficiency improvements $\Delta OE > 0$.

(C) Benefit from operational efficiency

Operational efficiency gain ΔOE and benefits from operation efficiency BOE are related but distinct metrics used in different contexts within operational and financial modeling.

ΔOE is typically used to quantify the difference in operational efficiency between two systems, such as a traditional system and a modern system enhanced with technologies like AHMSs. It is a comparative metric if it satisfies the following:

- Measures the improvement in operational efficiency that a new system or technology brings over an existing or older system.
- Can include factors like reduction in downtime, increased throughput, better fuel efficiency, or other performance improvements.

BOE on the other hand, typically refers to the monetary or qualitative value derived from improvements in operational efficiency. This metric must satisfy the following:

- Translate efficiency improvements into financial savings or revenue enhancements.
- Be able to be quantified by assessing cost savings from reduced downtime, increased output, or lower operational costs due to improved efficiency.
- Involve converting the operational efficiencies into the money value or other measurable benefits.

(D) Example

Consider a scenario where a company is evaluating the replacement of its traditional manufacturing system with a new system that includes advanced automation and real-time monitoring technologies.

- Calculation of ΔOE :
 - Suppose the traditional system has an efficiency rating of 80% due to older technology.
 - The new system has an efficiency rating of 95% due to better technology and reduced machine downtime.
 - $\Delta OE = 95\% - 80\% = 15\%$
 - This 15% improvement represents the comparative gain in operational efficiency due to the new system.
- Quantifying BOE :
 - The 15% improvement in efficiency reduces downtime by 100 h annually, with each hour of downtime costing the company USD 500 in lost production.
 - The annual financial benefit from improved operational efficiency would be $100 \text{ h} * \text{USD } 500/\text{h} = \text{USD } 50,000$.
 - This USD 50,000 represents the BOE , translating the efficiency gain into a financial metric.

Measuring the benefit from operational efficiency is a crucial aspect of evaluating the financial and operational impacts of improvements in systems, especially when integrating new technologies like advanced health monitoring systems. Operational efficiency encompasses various factors, including reduced downtime, improved asset utilization, and lower operational costs, which contribute directly and indirectly to the financial bottom line.

3.1.2. Steps to Measure Benefits from Operational Efficiency

1. Identify key efficiency metrics.
 - Calculate the reduction in hours that the system is non-operational due to maintenance or failures.
 - Measure improvements due to better maintenance and operation practices.
 - Evaluate the reduction in the number of maintenance events required per unit time.
 - Determine any increase in the availability and usage rate of the assets.
2. Quantify cost savings.
 - Convert the reduced downtime and lower maintenance frequency into direct cost savings by multiplying the reduced hours or events by the cost per h/event.
 - Increased asset utilization and fuel efficiency can be translated into cost savings.
3. Calculate enhanced revenue.
 - If operational efficiency allows for more operations within the same timeframe, calculate the additional revenue generated from these operations.
 - Improved operational efficiency often leads to better quality products or services and fewer penalties for non-compliance, which can be quantified if data are available.
4. Use financial models.
 - Calculate the return on investment (ROI) by dividing the total financial benefits (cost savings plus any additional revenue) by the total costs associated with implementing the improvements.
 - Project the future cash flows from operational efficiencies over time and discount them to their present value to determine the net present value (NPV). This approach helps in understanding the long-term value of the investments in efficiency improvements.

5. Develop performance indicators.
 - Develop specific key performance indicators (KPIs) linked to operational efficiency, such as Mean Time Between Failures (MTBF), Mean Time to Repair (MTTR), and Overall Equipment Effectiveness (OEE). Monitor these KPIs over time to assess improvements and correlate these with financial performance.
6. Benchmarking.
 - Compare the performance before and after the implementation of AHMSs or other efficiency-improving technologies within various departments or sectors of the organization.
 - Compare the performance with industry standards or competitors to gauge how operational efficiency gains stand relative to the market or industry.

When applying this model, it is important to gather accurate and comprehensive data before and after the implementation of efficiency measures. These data should be analyzed periodically to verify that the expected benefits are being realized and to adjust the operational strategies as needed.

By quantifying the benefits of operational efficiency in these ways, organizations can make informed decisions about investing in technologies and practices that enhance efficiency, justify these investments to stakeholders, and continuously improve their operations based on empirical data.

3.1.3. Steps to Define Annual Maintenance Cost

Defining $M_{annual,i}$ for both traditional and modern systems in a general context involves establishing a framework that accounts for various factors influencing annual maintenance costs. This approach should consider both direct and indirect costs associated with maintenance activities, differentiated by the nature of the maintenance strategy—whether it is a traditional scheduled approach or a modern, technology-enhanced predictive maintenance system.

There are next steps to define $M_{annual,i}$.

1. Identify maintenance requirements and strategies.
 - Traditional system maintenance is typically scheduled based on time or usage intervals, without regard to the actual condition of components unless visible signs of wear or failure are evident.
 - Modern system maintenance is driven by data from AHMSs, which monitors the condition of components in real time and predicts their failure, allowing for maintenance to be scheduled only when necessary.
2. Calculate direct costs.
 - Consider the man-hours required for both routine and unexpected maintenance tasks. For the traditional system, labor hours are generally fixed by schedule. For the modern system, labor hours should be reduced due to efficiency gains from targeted maintenance.
 - Estimate the costs of consumables, spare parts, and other materials. In traditional systems, parts might be replaced more frequently as a precaution, while in modern systems, part replacement is condition-based, potentially reducing waste.
 - Include costs associated with the use of maintenance tools and facilities. Modern systems may require specialized diagnostic equipment.
3. Factor in overheads.
 - Both systems incur overhead costs related to the maintenance operations, including utilities, facility usage, and administrative support. However, these might be lower for modern systems due to more efficient maintenance operations.

4. Include indirect costs.
 - The impact of maintenance-related downtime on operations is a crucial cost factor. Modern systems aim to minimize downtime by scheduling maintenance optimally and performing quicker, more precise repairs.
 - Post-maintenance operational efficiency can affect productivity and operational costs. Modern systems may maintain higher efficiency through better maintenance accuracy.
5. Sum up annual costs.
 - Aggregate the costs from all the above factors to define $M_{annual,i}$ for both the traditional and modern systems.

Example

- Traditional System:
 - Labor: $100 \text{ h/year} \times \text{USD } 50/\text{h} = \text{USD } 5000$
 - Materials: USD 3000
 - Equipment: USD 500
 - Overheads: USD 1000
 - Downtime: $50 \text{ h} \times \text{USD } 100/\text{h} = \text{USD } 5000$
 - Efficiency Loss: USD 2000
$$M_{annual,tr} = \text{USD } 5000 + \text{USD } 3000 + \text{USD } 500 + \text{USD } 1000 + \text{USD } 5000 + \text{USD } 2000 = \text{USD } 16,500$$
- Modern System:
 - Labor: $70 \text{ h/year} \times \text{USD } 50/\text{h} = \text{USD } 3500$ (reduced due to efficiency)
 - Materials: USD 2000 (reduced due to condition-based replacements)
 - Equipment: USD 1000 (increased due to specialized diagnostics)
 - Overheads: USD 800
 - Downtime: $20 \text{ h} \times \text{USD } 100/\text{h} = \text{USD } 2000$ (significantly reduced)
 - Efficiency Gain: $-\text{USD } 1000$ (savings due to increased operational efficiency)
$$M_{annual,AHMS} = \text{USD } 3500 + \text{USD } 2000 + \text{USD } 1000 + \text{USD } 800 + \text{USD } 2000 - \text{USD } 1000 = \text{USD } 8300$$

Defining $M_{annual,i}$ in this manner provides a detailed understanding of how maintenance strategies affect overall costs in traditional and modern systems. It helps organizations evaluate the cost-effectiveness of investing in advanced monitoring and predictive maintenance technologies by quantifying the potential savings and operational benefits. This approach supports informed decision-making by highlighting the direct and indirect financial impacts of different maintenance practices.

Using a time-dependent function $M_{annual,i}(t)$ for defining the annual maintenance costs in both traditional and modern systems introduces a dynamic aspect to the cost calculation, accounting for changes in maintenance needs and costs over time. This can be particularly significant in maintenance strategies where the wear and performance of systems can evolve due to aging, technological upgrades, or changes in operational practices.

Incorporating a time-dependent function could make a difference compared to a static annual cost model in some directions:

- For traditional systems as components age, the frequency and cost of maintenance may increase due to wear and tear, leading to higher costs as tt increases. A time-dependent function allows this trend to be accurately modeled, reflecting the growing need for repairs and replacements over time.
- For modern systems with AHMSs and other technologies, maintenance costs might initially be higher due to the integration of new technologies but could decrease over time as the system becomes more efficient at predicting and mitigating wear before it leads to failures.

- Both types of systems may undergo upgrades that improve their efficiency or change their maintenance requirements. For instance, software updates in modern systems might improve predictive algorithms, potentially reducing maintenance costs over time.
- If operational intensity or conditions change, this can affect the wear rate of components and thus the maintenance schedule. $M_{annual,i}(t)$ can adapt to these changes more fluidly than a fixed model.
- Using $M_{annual,i}(t)$ aids in more accurate budgeting and financial planning, as it provides a clearer forecast based on the expected evolution of maintenance costs rather than a flat rate that might not reflect reality accurately.
- Including $M_{annual,i}(t)$ in the life cycle cost analysis provides a more nuanced understanding of how costs will develop over the asset's life. This helps in making more informed decisions about investments, retirements, or replacements of systems or components.

Implementing $M_{annual,i}(t)$ involves defining how the function changes over time, which could be based on historical data, predictive models, or expected trends. For example:

- Maintenance costs might increase or decrease linearly due to predictable wear or improvements in maintenance techniques:

$$M_{annual,i}(t) = M_{annual,i}(t = 0) + kt$$

where k is the rate of change in maintenance cost per unit of time.

- If maintenance costs accelerate over time due to aging or decrease due to significant efficiencies gained from technology, an exponential model might be appropriate:

$$M_{annual,i}(t) = M_{annual,i}(t = 0) \times e^{kt}$$

- If a major overhaul or upgrade is scheduled at a specific time, this might result in a step change in the maintenance cost function.

Such time-dependent models allow for more precise adjustments to financial projections and maintenance scheduling, aligning maintenance strategies more closely with the actual conditions and needs of the systems. This approach offers a deeper insight into the total cost of ownership and operational readiness over the system's life cycle.

3.1.4. Case Study—Enhancing Cost Efficiency through AHMS-Driven Modular Architecture Selection in Aviation Equipment

In this case study, the LCM of an aircraft, incorporating multi-tiered AHMSs for the evaluation of modular aviation systems, is explored.

An aviation system can be made in two versions—in the form of a monobloc or in the form of a modular design consisting of several removable blocks. Accordingly, AHMSs can be implemented in two versions—as a centralized monitoring system (CMS), which, during operation, monitors the entire system as a whole, or a distributed monitoring system (DMS), which monitors each module of the system independently.

The system's effectiveness is evaluated based on its total cost $C(A, t)$ of the system with architecture A during operation time t :

$$C(A, t) = C_0(A) + C_{op}(A, t)$$

where $C_0(A)$ is the cost of developing and producing the system with an AHMS, and $C_{op}(A, t)$ is the operational cost over time t for identifying failures within the system with architecture A .

The challenge of designing an optimal embedded architecture for integrated diagnostics was defined as creating an AHMS with an architecture A_{opt} that minimizes total life cycle costs over period T_0 :

$$C(A_{opt}, t) = \min\{C(A_i, t) | t = T_0, i = 0, 1\} \quad (6)$$

where A_0 is CMS architecture of the AHMS, A_1 is the DMS architecture of the AHMS.

Development and production cost for the AHMS is expressed as $C_0 = c_0$ for a monobloc system with CMS architecture of the AHMS or $C_0 = \sum_{A_i} c_i$, where c_i , $i = 1, \dots, n$ for a module structure of the system with n modules and DMS architecture of the AHMS.

Operation cost for the AHMS is expressed as

$$C_{op}(A_i, t) = rd_i$$

where r —the number of system failures during operation time t , and d_i —the average cost of diagnosing one failure for the selected architecture A_i .

For exponential failure model $r = \Lambda t$, where Λ is the system's failure rate characterized by the failure rate λ_i ($i = 1, \dots, n$) of individual modules:

$$\Lambda = \sum_i^n \lambda_i$$

The average cost d_i of diagnosing one failure in the system depends on its architecture and the corresponding AHMC architecture. Detecting failures at the module level with DMS allows you to avoid significantly higher costs when detecting failures at the level of the system as a whole with CMS. The experience of designing an AHMS shows that with sufficient accuracy for practice, it can be assumed that for all modules, the DMS architecture of the AHMS $d_1 = d$, and for a monobloc system with CMS architecture of the AHMS $d_0 = \beta d$, where β is an empirical coefficient characterizing the increase in the cost of diagnosing a failure at the level of the system as a whole compared to diagnosing at the level of its modules. For electronics products, for example, you can use the value $\beta \approx 10$ [69].

By substituting the obtained parameter values into Expression (6), we can determine the optimal architecture of the AHMS by selecting architecture with the lowest life cycle cost.

Example

Scenario parameters:

$T_0 = 10$ years, $m = 3$, $c_0 = \text{USD } 100,000$, $c_i = \text{USD } 60,000$, $i = 1, 2, 3$, $\lambda_1 = 0.05$ per year, $\lambda_2 = 0.06$ per year, $\lambda_3 = 0.04$ per year, $d = \text{USD } 1000$, $\beta = 10$.

Results:

Cost of development and production for architecture A_0 for monobloc system $C_0(A_0) = \text{USD } 100,000$.

Cost of development and production for architecture A_1 for modular system $C_0(A_1) = \sum_{i=1}^n c_i = \text{USD } 60,000 + \text{USD } 60,000 + \text{USD } 60,000 = \text{USD } 180,000$.

Total system failure rate $\Lambda = \sum_{i=1}^n \lambda_i = 0.05 + 0.06 + 0.04 = 0.15$ per year

Life cycle cost for monobloc system with CMS architecture of the AHMS $C(A_0, T_0) = \text{USD } 250,000$.

Life cycle cost for modular system with DMS architecture of the AHMS $C(A_1, T_0) = \text{USD } 181,000$.

The example demonstrates that over the life cycle, the frequent and expensive failure diagnostics of the monobloc architecture led to a higher total cost than the modular one, despite the opposite initial investment difference. This scenario underlines the importance of considering both the initial and operational costs in system design, especially when failures are frequent, and their diagnostic costs are significantly impacted by the system architecture.

3.1.5. Case Study—Enhancing Structural Inspections and Maintenance Cost Efficiency through AHMS-Driven Modular Architecture Selection in Aviation Equipment

Aircraft maintenance programs are designed by operators using the maintenance planning data (MPD) provided by the aircraft manufacturer. The MPD outlines all necessary maintenance tasks, such as inspections, servicing, and testing, along with the intervals at which these tasks should be performed. Operators develop maintenance programs by selecting applicable tasks from the MPD and may add additional tasks based on specific operational conditions. However, the intervals for performing these tasks are typically fixed and cannot be altered.

The MPD prescribes maintenance tasks and intervals based on conservative, average scenarios to ensure maximum safety. While this guarantees airworthiness, it is not always optimal for every aircraft, which may operate under varying conditions and environments. Consequently, a fully customized maintenance program tailored to the specific operational conditions of each aircraft can significantly enhance efficiency, reduce downtime, and increase overall utilization.

AHMSs with big data analysis allow for the modeling of each aircraft's unique life cycle environment. This enables the development of a customized and efficient maintenance program, tailored to the specific needs of each aircraft.

To assess the effectiveness of this approach, we calculate the number of maintenance stops n_i for each task i in a standard MPD-based maintenance program. This is given by:

$$n_i = \left\lceil \frac{T_{LC}}{t_{i \text{ MPD}}} \right\rceil$$

where T_{LC} is the aircraft's life cycle duration, and $t_{i \text{ MPD}}$ is the interval for performing the maintenance task i according to the MPD. The ceiling function $\lceil x \rceil$ ensures that n_i is rounded up to the nearest integer since the number of maintenance stops must be an integer.

Using an AHMS-driven modular architecture and big data analysis, a new interval $t_{i \text{ cust}}$ can be determined for each maintenance task. The number of maintenance stops then becomes:

$$m_i = \left\lceil \frac{T_{LC}}{t_{i \text{ cust}}} \right\rceil$$

Since, in some cases, for a specific aircraft, the interval $t_{i \text{ cust}}$ will be longer than $t_{i \text{ MPD}}$, the total number of maintenance stops for all tasks K will be:

$$\sum_{i=1}^K m_i < \sum_{i=1}^K n_i$$

This reduction in maintenance stops translates to fewer interruptions and increased aircraft availability for operations.

By implementing an AHMS-driven modular architecture combined with big data analysis, maintenance intervals can be optimized to match the actual operating conditions of each aircraft. This results in fewer maintenance stops, reduced downtime, and improved operational efficiency, all while maintaining the necessary safety standards.

3.1.6. Impact Symbiosis of AHMSs and Modular Design in Aircraft Construction on Aviation Sustainability

The research conducted in Section 3.1, which focuses on the symbiosis of advanced health monitoring systems and modular design in aircraft construction, demonstrates significant positive impacts on sustainability in the aviation industry. This integrated approach addresses several key aspects of sustainability.

The modular design approach, enhanced by AHMSs, allows for a more efficient use of materials throughout the aircraft's life cycle. By enabling easier replacement and upgrading

of individual components, this approach reduces the need for whole-system replacements, thereby conserving resources and minimizing waste.

The integration of AHMSs with modular design significantly extends the operational life of aircraft components. By providing real-time diagnostics and prognostics, AHMSs enable more precise and timely maintenance, preventing premature failures and extending the useful life of parts. This extension of component lifespans directly contributes to sustainability by reducing the demand for new parts and the associated resource consumption and manufacturing emissions.

The real-time monitoring capabilities of AHMSs allow for optimized aircraft operation, potentially leading to reduced fuel consumption and lower emissions. By ensuring that all systems are operating at peak efficiency, the integrated approach contributes to the overall reduction in the aircraft's environmental footprint during its operational life.

The modular design approach facilitates easier disassembly of aircraft at the end of their life cycle. This improved disassembly process enhances the potential for recycling and proper disposal of components, aligning with circular economy principles and reducing the environmental impact of aircraft disposal.

3.2. Enhanced Model with Decision-Making Criteria for AHMSs and New Technologies Integration

To formulate a comprehensive decision-making framework for comparing a traditional aviation system with one that integrates AHMSs and utilizes cutting-edge technologies such as IoT and AI, we need to define clear criteria based on operational efficiency, maintenance optimization, and overall cost implications. Let us develop this framework to provide decision metrics that highlight when the adoption of a modern IT-supported system is preferable and incorporate LCC along with other key decision metrics to provide a clear and comprehensive basis for choosing between traditional and modern systems.

Decision rule and decision metrics in this case will be the same as in the previous case and are defined by Expressions (1)–(5).

Justification for preference:

- The modern system, despite potentially higher initial costs due to advanced technology investments, offers significant reductions in total life cycle costs through savings in maintenance and operational efficiencies.
- The integration of AHMSs with IoT and AI not only optimizes maintenance strategies but also enhances the overall operational capabilities of the aircraft, leading to fewer delays, quicker response times, and improved service reliability.
- Investing in modern technologies aligns with industry trends toward digital transformation and sustainability, positioning the organization as a leader in innovative aviation solutions.

This enhanced and comprehensive model for decision-making ensures that the evaluation of AHMSs and new technologies' integration in aviation is grounded in a quantitative assessment of financial, operational, and strategic benefits. By considering life cycle costs alongside efficiency gains and maintenance savings, the model supports informed decision-making that balances short-term expenditures against long-term gains, fostering a proactive approach to adopting cutting-edge aviation technologies.

3.2.1. Technological Components for Implementation of the Model

The technology integration of the multi-level aircraft health management system focuses on how various advanced technologies are implemented to support and enhance the functionalities of the aircraft health management system. This integration interlinks technologies such as IoT, AI, and blockchain with the data processing stages, ensuring efficient, secure, and intelligent management of aircraft health data:

- IoT devices are embedded sensors and actuators that collect real-time data from various aircraft systems. These devices are critical for real-time data acquisition and communication, enabling the continuous monitoring of aircraft systems.

- AI involves the use of machine learning models and algorithms to analyze large volumes of data, identify patterns, make predictions, and provide actionable insights. AI technologies are crucial in processing and analyzing data at all stages, from local processing on the aircraft to integrative analyses at MRO centers and fleet-wide analytics.
- Blockchain technology is used to ensure the integrity and security of the data across the system. It provides a secure, immutable ledger for recording and sharing information about aircraft maintenance and operations, which helps in maintaining transparency, traceability, and compliance.

These technologies (IoT, AI, Blockchain) enhance the functionalities of the aircraft health management system:

- IoT primarily facilitates real-time data capture directly from aircraft sensors, which are then used by AI for initial assessments and prioritized for action based on system requirements. Blockchain ensures that each piece of collected data can be traced back to its origin, maintaining the integrity of the data throughout the system.
- IoT ensures the data collected are transmitted in real-time and secured via encryption technologies. AI optimizes these data for efficient transmission, while blockchain ensures the transmitted data are logged securely and remain tamper-proof.
- At the local processing level, IoT handles immediate data acquisition and preprocessing, whereas AI performs detailed analysis to detect issues that can be acted upon locally. When data reach the MRO level, they are further integrated and analyzed with AI to discover broader trends or issues, with blockchain ensuring all data integration steps are secure and verifiable.
- IoT collects comprehensive data from the entire fleet, which AI uses to perform extensive analyses, predicting potential future failures and maintenance needs. Blockchain secures these analyses, ensuring that the predictions and the data they are based on are reliable and protected.
- IoT provides the operational data necessary for effective maintenance scheduling, while AI optimizes the scheduling based on predictions and operational data. Blockchain verifies that the maintenance performed matches the scheduled tasks and records this in a tamper-proof ledger, crucial for regulatory compliance.
- IoT offers the necessary real-time data to inform decisions, AI provides deep analysis and predictions to guide these decisions, and blockchain ensures that all decisions made, and actions taken, are recorded and verifiable, adding a layer of security and compliance.

The combined use of IoT, AI, and Blockchain supports various decision-making actions within the aircraft health management system:

- IoT captures real-time deviations in aircraft systems, AI analyzes these deviations to determine if they signify true anomalies, and Blockchain ensures that all detected anomalies are logged securely for future reference and analysis.
- IoT provides the necessary operational data, AI uses these data to determine the most appropriate type of maintenance (preventative, corrective, overhaul), and Blockchain secures these recommendations against tampering.
- IoT provides system availability data, AI optimizes the maintenance scheduling for efficiency, and Blockchain ensures that schedules are adhered to and cannot be altered without proper authorization.
- IoT monitors resource levels, AI allocates resources efficiently based on current needs and future predictions, and Blockchain records these allocations to ensure they are followed and can be audited.
- IoT devices continuously monitor the systems for performance metrics, AI predicts failures before they occur to prevent downtime, and Blockchain ensures that these predictions and the basis for them are permanently recorded.

- IoT gathers data across operations, AI analyzes these data to find inefficiencies, and Blockchain records any operational changes made based on these analyses to ensure they meet regulatory standards.
- IoT ensures all necessary data for compliance are collected, AI automates the process of checking these data against compliance standards, and Blockchain creates a permanent record of the compliance status.
- IoT collects data relevant to safety, AI predicts and mitigates potential safety issues, and Blockchain provides a secure log of all safety-related data and actions.
- IoT tracks all operational costs, AI analyzes these costs to identify potential savings, and Blockchain ensures that any financial decisions are transparent and traceable.

3.2.2. Framework to Data Presentation Requirements

For the successful implementation of a multi-level aviation health management system that integrates IoT, AI, and Blockchain technologies, it is crucial to ensure that data presentation meets specific requirements tailored to various stakeholders' needs. This encompasses the visual representation of data, accessibility, real-time updates, security, and regulatory compliance.

There are some key data presentation requirements for AHMSs:

- Utilize dashboards that offer clear, intuitive visualizations such as graphs, gauges, heat maps, and alert indicators that can quickly convey the status of aircraft health and operational metrics.
- Ensure that the data presented are accurate and up to date, reflecting the latest readings and analyses to avoid any misinterpretations that could lead to incorrect decisions.
- Provide real-time data streaming to ensure that maintenance teams, flight operators, and management have the most current information, enabling prompt decision-making, especially for critical operational adjustments and anomaly responses.
- Minimize latency in data presentation to enhance the responsiveness of the system, particularly critical for real-time monitoring and anomaly detection functionalities.
- Customize dashboards and reports based on user roles (e.g., technicians, engineers, management, regulatory bodies), ensuring that each user accesses relevant information necessary for their tasks and decision-making.
- Allow users to interact with the data, such as drilling down into specific metrics or adjusting parameters to view different scenarios, which can aid in deeper analysis and understanding.
- Ensure seamless integration with existing aviation management systems, such as MRO software, flight tracking systems, and logistics platforms, to allow unified and comprehensive data analysis.
- Standardize data formats across different systems and platforms to ensure compatibility and ease of data integration and analysis.
- Implement strong encryption for data at rest and in transit to protect sensitive information from unauthorized access and cyber threats.
- Utilize blockchain for certain aspects of data logging and sharing to enhance security, provide data integrity, and ensure compliance with regulatory standards.
- Maintain detailed audit trails for all actions taken based on the system's data, which are crucial for compliance and investigation purposes.
- Provide mobile access to the system through secure apps or web portals, allowing decision-makers and technicians to view and respond to data remotely.
- Implement redundancy in data storage and presentation services to ensure availability even in the case of hardware or network failures.
- Design the data presentation layer to be scalable, accommodating increases in data volume without degradation in performance.
- Ensure the system is easy to update and maintain, with support for adding new functionalities or integrating additional data sources without significant overhauls.

By meeting these data presentation requirements, the multi-level aviation health management system can operate effectively, delivering critical information in a user-friendly, secure, and compliant manner, thereby enhancing decision-making processes, and improving overall aircraft operations and safety.

To describe the data presentation requirements for the multi-level aviation health management system integrating IoT, AI, and Blockchain, we will focus on formulating these requirements in terms of functions and variables that can encapsulate the interactions, constraints, and behaviors expected in the system. Each requirement will be translated into a mathematical framework that aids in its implementation and validation.

Let $V(d_t)$ be a visualization function that maps data d_t at time t to a graphical representation. The function should ensure that V minimizes any distortion or noise:

$$\min_V \|d_t - V^{-1}[V(d_t)]\|$$

where V^{-1} attempts to reconstruct the original data from the visualization, emphasizing the accuracy of the visualization.

Define $L(d_t)$ as the latency function for data d_t , where the goal is to minimize L such that:

$$\min L(d_t) \quad \text{subject to} \quad L(d_t) \leq \tau$$

where τ is the acceptable maximum latency threshold.

Let $R(u, d_t)$ be the function that determines the data d_t accessible by user u . Define R using set operations where each user has a defined role with permissions p_u :

$$R(u, d_t) = \{d \in D \mid d \text{ satisfies } p_u\}$$

D is the dataset available at time t .

Define a standardization function $S(d)$ that maps data d from various formats to a standardized format s :

$$S(d) = s \quad \forall d \in D$$

Define an encryption function $E(d_t)$ that maps data d_t to its encrypted form e_t :

$$e_t = E(d_t)$$

Let $B(d_t)$ represents a blockchain function that logs data d_t ensuring immutability and traceability:

$$b_t = B(d_t)$$

Define a mobile accessibility function $M(d_t, u)$ indicating whether data d_t is accessible by user u on a mobile device:

$$M(d_t, u) = \begin{cases} 1 & \text{if accessible} \\ 0 & \text{otherwise} \end{cases}$$

Define a scalability function $C(n, t)$ where n is the number of users or data volume, and t is the system throughput, maintaining a relationship:

$$\max_C C(n, t) \quad \text{subject to} \quad C(n, t) \geq k$$

where k is the minimum acceptable throughput.

These mathematical formulations provide a framework to rigorously define, implement, and measure the efficacy of the various data presentation requirements in a sophisticated aviation health management system. This approach facilitates systematic development, optimization, and evaluation of system capabilities.

3.2.3. Sustainable Aviation Life Cycle Management through an Ontology-Based Approach

In the modern aviation industry, managing the life cycle of an aircraft efficiently and sustainably is increasingly crucial. This involves not only ensuring operational safety and reliability but also minimizing the environmental impact of aviation activities. An ontology-based approach to aviation health management offers a structured way to integrate complex data across various aspects of an aircraft's life cycle, from design and manufacture to operation and eventual decommissioning.

Integrating an ontology into health management activities within an aviation system involves structuring data, processes, and relationships to support the decision-making processes. The integration primarily involves three key mathematical aspects:

- Representation of data and relationships;
- Querying and reasoning over the ontology;
- Enforcing constraints that align with the health management policies and practices.

For each entity E_i in the set of entities $\mathcal{E}$, let $A(E_i)$ represent the set of attributes. An attribute a for entity E can be represented as a function $a : E \rightarrow V$, where V is the value domain of a :

$$A(E_i) = \{a_1, a_2, \dots, a_n\}$$

For instance, an aircraft entity E_A may have attributes like model, service life, and maintenance records:

$$A(E_A) = \{model, service\ life, maintenance\ records\}$$

Relationships R between entities can be defined as subsets of the Cartesian product of entities, potentially including relationship-specific attributes:

$$R_k \subseteq E_i \times E_j \times \dots \times A(R_k)$$

where $A(R_k)$ represents the attributes applicable to the relationship R_k .

For example, relationship. R_M (Monitors) between aircraft E_A and sensor E_S :

$$R_M \subseteq E_A \times E_S$$

Attributes can be treated as functions mapping from an entity to a value:

$$a : E \rightarrow V$$

where a is an attribute function, E is entity, and V is the value domain of the attribute.

Constraints C can be expressed as logical predicates that apply to entities and relationships:

$$C : \mathcal{E} \cup \mathcal{R} \rightarrow \{\text{true}, \text{false}\}$$

Figure 4 presents an aviation life cycle management high-level ontology that models the critical elements involved in the cradle-to-grave lifespan of aircraft. The ontology encompasses factors ranging from external environmental conditions to the aircraft structure, powerplant, systems, parts, and airworthiness directives.

The ontology diagram provides a structured representation of key entities and relationships in aviation life cycle management. At the top level, the Environment entity captures external factors like Weather that can impact aviation operations. The central focus is on the Aircraft entity, which has attributes like Airplane, APU (auxiliary power unit), Type, and Model.

Various events and processes are associated with an Aircraft:

- Modification events can lead to configuration changes captured in STC (Supplemental Type Certificate) and SB (Service Bulletin) entities.
- Defects may be discovered during operation.
- Routine Maintenance activities involve removing, installing and replacing Parts.

- The aircraft goes through a life cycle from Requirements to AD (Airworthiness Directive) to being Installed and put into operation.
- Key relationships include the following:
- An Aircraft is made up of an Airplane and APU.
 - An Airplane has a specific Type and Model.
 - Maintenance activities performed on an Aircraft are logged in ICA (Instructions for Continued Airworthiness) documents.
 - Parts Installed on an Aircraft may be Removed during Maintenance.
 - The AD, LLP (Life Limited Parts), Engine, EO (Engineering Order), and AMP (Aircraft Maintenance Program) all capture airworthiness and maintenance requirements that must be fulfilled during the Aircraft's service life.




Figure 4. High-level ontology of aircraft life cycle management.

This ontology provides a formal specification of the entities, attributes, and relationships involved in managing an aircraft throughout its life cycle, from design and manufacturing to operation and maintenance. By capturing this information in a structured, machine-readable format, ontology-based approaches enable more efficient querying, reasoning, and application of constraints to ensure adherence to airworthiness standards and maintenance best practices. The ontology can serve as a unifying framework to integrate data across disparate systems, supporting timely decision-making and optimizing the cost, performance, and sustainability of aviation activities.

For example, by traversing the relationships in the ontology, we can track the provenance and maintenance history of every Part installed on an Aircraft to identify parts that may be nearing end of life based on the LLP requirements. Defining constraints on attributes can help catch discrepancies, such as a Modification that is not approved for a specific Airplane Type. Reasoning capabilities could generate alerts for an Aircraft that is overdue for required Maintenance actions per the AMP.

Ontologies enable a holistic, integrated approach to managing the cradle-to-grave life cycle of aircraft. The aviation ontology described here models the critical entities,

properties, and relationships involved in keeping aircraft safe, reliable, and airworthy while optimizing cost and sustainability. This provides a robust foundation for knowledge-based systems that support and automate aviation life cycle management activities.

The aviation industry, characterized by its stringent safety requirements and the complexity of its operations, demands meticulous attention to detail in every aspect of an aircraft's life cycle. From initial design and manufacturing to daily operations and final decommissioning, the life cycle management of an aircraft involves multiple stakeholders, including manufacturers, operators, maintenance teams, and regulatory bodies. Leveraging advanced technologies like ontologies, IoT, AI, and blockchain can significantly enhance the efficiency and effectiveness of managing these processes.

At the core of this advanced life cycle management is the development of an ontology-based system that structures and integrates all relevant data across an aircraft's life cycle. An ontology, in this context, provides a formal representation of knowledge within the domain of aviation maintenance and operations. It defines entities such as Aircraft, Sensors, Maintenance Activities, and Environmental Conditions, along with their attributes and relationships.

This structured data framework supports complex queries, reasoning, and decision-making. It allows for the dynamic updating of information, such as changes in aircraft ownership or modifications, and integrates these data to provide a holistic view of an aircraft's status and history.

The first key functionality of this system is life cycle tracking, which continuously assesses the health and status of the aircraft through a function $L(a, t)$. This function integrates operational hours, maintenance history, and real-time sensor data to offer a comprehensive view of the aircraft's condition at any given time. Utilizing AI, the system analyzes these data to predict when maintenance should be performed, optimizing the scheduling of these activities to minimize downtime and extend the aircraft's operational life.

Predictive maintenance, enabled by AI models, uses historical data and machine learning algorithms to foresee potential failures before they occur. This preemptive approach not only enhances safety but also reduces unexpected maintenance costs, thus supporting efficient fleet management.

Resource optimization is another critical aspect, focusing on the efficient allocation of resources such as parts and personnel. The function $R(a, t)$ dynamically allocates these resources based on current needs assessed through the ontology-based system and predicted future demands calculated by AI-driven predictive maintenance schedules.

Moreover, the system enhances compliance and safety management by continuously monitoring and integrating safety and regulatory data. A function $C(a, t)$ ensures that all operations meet stringent regulatory requirements and safety standards, automatically updating and alerting operators to any discrepancies or emerging issues that could affect compliance.

As aircraft approach the end of their operational life, decisions about decommissioning, selling, or repurposing become paramount. The ontology-based system supports these decisions through $E(a, t)$, a function that evaluates the aircraft's remaining value and operational feasibility against economic factors and market conditions. This ensures that end-of-life decisions are made based on comprehensive data, maximizing returns, and minimizing waste.

3.2.4. Impact of New Technologies Integration in AHMSs on Aviation Sustainability

The research conducted in Section 3.2, which focuses on an enhanced model with decision-making criteria for AHMSs and new technologies integration, demonstrates significant positive impacts on sustainability in the aviation industry. This advanced approach addresses several key aspects of sustainability.

The integration of IoT, AI, and blockchain technologies in AHMSs enables more accurate and timely decision-making throughout the aircraft's life cycle. This data-driven

approach leads to optimized operations and maintenance schedules, reducing unnecessary resource consumption and waste.

The AI-powered predictive maintenance capabilities of the enhanced AHMS significantly reduce the frequency of unscheduled maintenance events. This not only extends the lifespan of components but also minimizes the environmental impact associated with emergency repairs and replacements.

The advanced decision-making model allows for more efficient allocation of resources, including spare parts, maintenance personnel, and energy. This optimization leads to reduced waste and lower overall resource consumption in aviation operations.

By continuously monitoring and optimizing aircraft performance, the enhanced AHMS contributes to improved fuel efficiency. This directly translates to reduced greenhouse gas emissions and a lower carbon footprint for aviation operations.

The integration of blockchain technology ensures a secure and transparent record of all maintenance and operational activities. This improved traceability supports better compliance with environmental regulations and facilitates more accurate reporting of sustainability metrics.

The comprehensive approach to life cycle management enabled by this enhanced model allows for better decision-making regarding aircraft upgrades, refurbishments, and retirement. This holistic view supports more sustainable choices throughout the aircraft's life, potentially extending its useful life and reducing the demand for new aircraft production.

The advanced tracking and analysis capabilities of the system support better end-of-life management for aircraft components. This facilitates increased recycling and reuse of materials, aligning with circular economy principles.

The real-time monitoring and AI-driven optimization contribute to overall energy efficiency in aircraft operations, from ground operations to in-flight systems management.

By providing early detection of potential issues, the enhanced AHMS reduces the risk of environmental incidents related to aircraft malfunctions or failures.

3.3. Enhanced Model with Decision-Making Criteria for AHMS-Supported Component Utilization and Life Extension

3.3.1. General Model

To effectively compare a traditional aviation maintenance system with an AHMS-supported system focusing on maximizing component utilization and life extension, we need to establish a framework that quantitatively evaluates these two systems. This framework should include decision-making criteria based on life cycle cost savings, reliability improvements, maintenance reductions, and sustainability enhancements.

(A) Decision Metrics

1. Development Cost Difference

$$\Delta C_{dev} = C_{dev,tr} - C_{dev,AHMS}$$

where $C_{dev,tr}$ and $C_{dev,AHMS}$ represent the development costs for the traditional and modular systems with the AHMS, respectively. A negative ΔC_{dev} indicates higher initial costs for the modular system due to the complexity of integrating modular designs and AHMS.

2. Maintenance Cost Reduction

$$\Delta MC = MC_{tr} - MC_{AHMS}$$

where MC_{tr} and MC_{AHMS} are the cumulative maintenance costs over the system's operational life. The modular system, supported by the AHMS, typically incurs lower maintenance costs due to its ability to precisely target maintenance needs and easily replace individual modules.

3. Component Life Extension

$$\Delta LE = LE_{AHMS} - LE_{tr}$$

where LE_{tr} and LE_{AHMS} are the average expected lifespans of components in the traditional and AHMS-supported systems, respectively. The AHMS aims to extend these lifespans through precise monitoring and maintenance, and a positive ΔLE demonstrates this capability.

4. Life Cycle Cost Savings

$$\Delta LCC = LCC_{tr} - LCC_{AHMS} \quad (7)$$

where LCC_{tr} and LCC_{AHMS} represent the total life cycle costs of the traditional and modular systems with the AHMS, respectively. A positive ΔLCC indicates overall life cycle cost savings when using the modular system with the AHMS.

$$LCC_i = C_{dev,i} + \int_0^T M_{annual,i}(t)dt - R_{cost,i}$$

$$i = \{tr, AHMS\}$$

where

$M_{annual,i}$ represents the annual maintenance cost for i architecture, involves several steps that account for various factors influencing maintenance expenses.

$R_{cost,i}$ is the cost of replacements due to earlier component failures.

(B) Decision rule

Adopt the AHMS-supported system if all the following conditions are satisfied:

- Indicating that the AHMS-supported system offers total life cycle cost savings $\Delta LCC > 0$.
- Showing significant maintenance cost reductions $\Delta MC > 0$.
- Demonstrating effective extension of component lifespans $\Delta LE > 0$.

The model provides a robust framework for evaluating the benefits of AHMSs in aviation maintenance systems, particularly focusing on component utilization and life extension.

3.3.2. The Life Cycle Management and End-of-Life Decisions for Aircraft Components

Aircraft, by their nature, are built to endure rigorous operational demands over extended periods. Throughout their life cycle, various components and systems are subject to periodic inspections, repairs, and replacement to maintain airworthiness. The modernization of these components is not merely a regulatory requirement but also a strategic measure to enhance performance and extend the aircraft's operational life.

Key systems, such as avionics, landing gear, and engines, are often upgraded to incorporate advancements in technology, improve efficiency, and comply with evolving safety standards. Among these, engines are particularly noteworthy due to their high cost and critical role in an aircraft's performance. Engine replacements are a common practice, driven by both wear and technological advancements, and can occur multiple times throughout the aircraft's life cycle.

When an aircraft reaches the end of its operational life, typically defined by economic considerations or regulatory limits, stakeholders must decide between decommissioning the entire aircraft or disassembling it for parts. This decision hinges on a thorough assessment of the condition of individual subsystems and components.

Decommissioning an aircraft involves taking it out of service and often selling it as a whole for recycling. This approach is straightforward but may not maximize the residual value of the aircraft's components. The process involves dismantling the aircraft structure, extracting recyclable materials such as aluminum, titanium, and other alloys, and safely disposing of non-recyclable materials. While recycling can contribute to environmental sustainability, it may not fully capitalize on the potential value of reusable components.

Alternatively, disassembling the aircraft into its constituent parts allows for the selective recovery of valuable components and systems. This approach is more labor-intensive but can yield higher returns by selling serviceable parts, particularly those with significant residual value like engines, avionics, and landing gear. Components deemed airworthy can be certified for reuse in other aircraft, contributing to a circular economy within the aviation industry.

The decision between decommissioning and disassembly also involves economic and environmental considerations. Disassembling and selling components can provide a higher financial return compared to selling the aircraft for scrap. Moreover, reusing components reduces the demand for new manufacturing, thus conserving resources and lowering the environmental footprint of the aviation industry.

To formulate a mathematically described decision-making problem for choosing between decommissioning an aircraft and disassembling it for parts, we can use a decision analysis framework. This framework will include defining the decision variables, the objective function, and the constraints. To incorporate the modular design and the health monitoring system with predictive capabilities, we need to extend the mathematical model to account for the condition and predicted residual durability of each module. The decision-making problem will then consider the expected future value of each module based on its health status and remaining useful life.

Let D be a binary decision variable:

$$D = \begin{cases} 1 & \text{if the aircraft is decommissioned and sold as a whole for recycling} \\ 0 & \text{if the aircraft is disassembled into parts and sold separately} \end{cases}$$

Define the following parameters:

V_{decom} —the total value obtained from decommissioning and recycling the aircraft.

C_{dis} —the cost associated with disassembling the aircraft.

N —the total number of modules.

$V_{part,i}$ —the current market value of the i -th module if sold separately.

$M_{part,i}$ —the predicted maintenance cost for the i -th module if reused.

$R_{part,i}$ —the predicted residual durability (remaining useful life) of the i -th module.

$E_{benefit,i}$ —the environmental benefit or cost associated with reusing the i -th module.

T_i —the standard operational period for the i -th module

The objective is to maximize the net value obtained from the decision, incorporating economic, maintenance, and environmental aspects:

$$\max Z = D(V_{decom} + \alpha) + (1 - D) \left[\sum_{i=1}^N (V_{part,i} + E_{benefit,i} - M_{part,i} R_{part,i} / T_i) - C_{dis} \right]$$

where α represents the net environmental benefit or cost associated with recycling the entire aircraft. If recycling the aircraft as a whole has a positive environmental impact (e.g., reducing waste, recovering valuable materials, lowering the carbon footprint compared to manufacturing new materials), α would be a positive value reflecting these benefits. If recycling the aircraft as a whole incurs environmental costs (e.g., pollution from recycling processes, energy consumption), α would be a negative value reflecting these costs.

To make the decision, compare the objective function values for both $D = 1$ and $D = 0$.

If $Z(D = 1) > Z(D = 0)$ chose alternative aircraft “is decommissioned and sold as a whole for recycling”, if $Z(D = 1) < Z(D = 0)$ chose alternative “the aircraft is disassembled into parts and sold separately”.

As an example, Figure 5 shows two graphs related to one type of aircraft. The graph on the left shows the replacement quantity of different aircraft systems (fuel, hydraulic power, and navigation) over the age of the aircraft. The graph on the right shows the corresponding replacement costs for these systems as the aircraft ages.



Figure 5. Replacement quantity of different aircraft systems (a) and the corresponding replacement costs for these systems (b) over the age of the aircraft.

These graphs illustrate the importance of considering the condition and predicted residual durability of each module when deciding between decommissioning an aircraft or disassembling it for parts.

As the aircraft ages, the replacement quantity and costs for various systems increase, particularly for the fuel and navigation systems. This information aligns with the discussion of how key systems like avionics, landing gear, and engines are often upgraded or replaced throughout an aircraft's life cycle to maintain airworthiness and incorporate technological advancements.

Figure 5 provides a visual representation of the factors that influence the decision-making process described in the text.

The described decision-making model integrates the modular design and health monitoring system of the aircraft. By incorporating the predicted residual durability and associated costs and benefits of each module, stakeholders can make more informed decisions regarding the end-of-life options for the aircraft. The objective function Z provides a comprehensive measure that balances economic returns, maintenance costs, and environmental impacts.

3.3.3. Case Study—Optimization of Longevity for Technical Systems from Economic and Technical Perspective

The ongoing challenge in engineering management is to optimize the longevity of aircraft to ensure maximal operational life while minimizing the associated costs. The balance between economic criteria, technical wear, and reliability is crucial in decision-making processes for extending the service life of the aircraft. This case study explores a model that integrates economic and technical parameters to determine the optimal extension period for the aircraft's operation, illustrating its practicality with an example of an aviation subsystem.

At present, methods for determining the longevity of such complex technical systems as aircraft are based on the use of economic criteria and are oriented toward obtaining minimal costs, enabling the achievement of the most reduced specific costs for maintaining aircraft under existing operating conditions. Indicators of longevity, common for all types of general-purpose technical systems, are defined at this stage of aircraft development.

However, during the operation of aircraft, the conditions of their exploitation differ, leading to unequal material wear. The economic feasibility of exploiting items after the expiration of service life leads to the need for the same operational enterprises to address the task of extending service life (resource) until an economically feasible level of longevity, considering requirements for reliability and the actual technical condition of aircraft.

Problem Statement. The assigned level of longevity for the aircraft is T . The cost of maintaining the aircraft over time t is:

$$C(t) = C_0 + u(t)s + wt$$

where C_0 is the cost of the aircraft; $u(t)$ —the number of failures of the aircraft over time t ; s —the average cost of eliminating one failure; w —the cost of technical service, attributed to the unit of time.

In the process of aircraft functioning, the wear of the aircraft and the parameter of the flow of failures $u(t)$ change from λ_0 at the initial moment of exploitation (at $t = 0$) to λ_T at the end of the service life when $t = T$. The criterion of the limit state is the technical impossibility or economic unfeasibility of further aircraft operation. The technical criterion of the limit state occurs at the time t , when the parameter of the flow of failures will have the limit permissible level $\lambda(t) = \lambda_{lim}$.

The economic criterion of the limit state (the economic unfeasibility of aircraft operation) is reached at the time t_e , starting from which the reduced costs for maintaining aircraft per unit of time $c_y = C(t)/t$ begin to increase.

The extended service life (beyond the assigned) of the aircraft can be represented as:

$$\tau = \min\{t_T, t_e | c_y(t_e), \lambda(t_T) = \lambda_{lim}\} \quad (8)$$

The solution to the problem. The average number of aircraft failures during operation t is determined by the failure rate:

$$u = \int_0^t \lambda(t) dt \quad (9)$$

If the running-in period passes during the production stage, then, under fixed operating conditions, the failure rate at moment t can be approximated by the function [75]

$$\lambda(t) = \lambda_0(\lambda_T/\lambda_0)^{t/T} \quad (10)$$

where λ_T —the value of the parameter of the flow of failures for the assigned level of longevity $t = T$.

Substituting (3) in (2) and conducting integration, we obtain

$$u = T\lambda_0(x^{t/T} - 1)/\ln x$$

where $x = \lambda_t/\lambda_0$ —failure rate growth indicator.

In this case, the reduced costs for maintaining the aircraft per unit of time:

$$c_y(t) = C_0/t + sT(x^{t/T} - 1)/(t \ln x) + w \quad (11)$$

When $dc_y(t)/dt = 0$ we obtain the transcendental equation:

$$x^{-t/T}[C_0 \ln x / (s\lambda_0) - T] + T = t \ln x$$

The solution of which allows the economically optimal value of the longevity parameter $t = t_e$ to be determined. The value of the reduced costs for the operation of aircraft, reaching a minimum at the time t_e , begins to increase. Therefore, the operation of aircraft for the time $t > t_e$ is economically unjustified.

The limit state according to the technical criterion is achieved at the moment t_T , when the failure rate reaches the limit permissible level $\lambda(t_T) = \lambda_{lim}$. By substituting the corresponding equation into Expression (10), we obtain the limit, and from a technical point of view, the value of the indicator for aircraft longevity:

$$t_T = T \ln (\lambda_{lim} / \lambda_0) / \ln (\lambda_T / \lambda_0) \quad (12)$$

Now it is possible to determine the level of longevity of aircraft considering the real conditions of exploitation, which corresponds to the target Function (8) equivalent to the minimum from the defined values t_e and t_T .

The methodology of the practical application of the provided model is included in the following:

1. At the moment $t = T$ from the assigned service life, determine the current value of its failure rate λ_T .
2. Compare λ_T with the limited value of the failure rate λ_{lim} for this type of aircraft item. If $\lambda_T > \lambda_{lim}$, extending the service life makes no sense due to the insufficient reliability of the item.
3. If $\lambda_T < \lambda_{lim}$, using Expression (5), determine the limit by the criterion of technical possibility for further exploitation of the item t_T .
4. Determine the fulfillment of the conditions for the economic feasibility of extending the service life, by finding the value t_e by solving Equation (4). If $t_e < T$, the economic feasibility of extending the service life is absent and further exploitation of the item is not reasonable.
5. If $t_e > T$, according to the target Function (8), determine the new service life value as $\tau = \min\{t_T, t_e\}$ and extend the operation of the product for a period $\Delta t = \tau - T$.

Numerical example

For the aircraft subsystem at the end of its service life, it is possible to extend it if there is economic feasibility for further operation and a deterioration in the failure rate by no more than two times.

Let us define the possibility of extending the exploitation for the subsystem, having an initial cost $C_0 = \text{USD } 12,000$, an assigned service life $T = 10$ years. Initial failure rate $\lambda_0 = 12$ failures/year, at the end of the service life the failure rate $\lambda_T = 20$ failures/year, and the average cost of one recovery is $s = \text{USD } 160$.

$\lambda_{lim} = 2\lambda_0 = 24$ failures/year. Since $\lambda_T < \lambda_{lim}$, there exists a technical possibility for extending the service life. In this case, the limit state according to the technical criterion is achieved in accordance with (12) over the time $t_T = 14.7$ years from the start of exploitation. The presence of economic feasibility for extending the service life can be determined by substituting data into Equation (11) and solving it concerning t .

In this case, we obtain the optimal from an economic point of view time of exploitation $t_e = 12.5$ years. In accordance with the target Function (8), it is possible to assign a new service life $\tau = \min\{t_T, t_e\} = 12.5$ years and extend the exploitation of the subsystem for the time $\Delta t = \tau - T = 14.7 - 12.5 = 2.2$ years.

3.3.4. Impact of AHMS-Supported Component Utilization and Life Extension on Aviation Sustainability

The research conducted in Section 3.3, which focuses on an enhanced model with decision-making criteria for AHMS-supported component utilization and life extension, demonstrates significant positive impacts on sustainability in the aviation industry. This advanced approach addresses several key aspects of sustainability.

By using AHMS data to optimize component utilization and maintenance schedules, this model significantly extends the operational life of aircraft parts. This extension directly contributes to sustainability by reducing the demand for new components, thus decreasing resource consumption and manufacturing-related emissions.

The ability to accurately predict component failures and optimize maintenance schedules leads to a reduction in premature replacements. This results in less waste generation throughout the aircraft's life cycle, aligning with key sustainability principles of waste minimization.

The model's focus on maximizing component utilization ensures that each part is used to its full potential before replacement. This efficient use of resources contributes to overall sustainability by reducing the rate of resource consumption in the aviation industry.

The approach provides a framework for making data-driven decisions about when to retire aircraft or individual components. This approach ensures that components are not discarded prematurely, and when they are, it is done at the optimal time for potential recycling or reuse.

By extending component life and optimizing end-of-life decisions, this model supports the principles of a circular economy in aviation. It encourages the reuse and recycling of components, reducing the industry's reliance on new raw materials.

With extended component lifespans and optimized utilization, there is a reduced need for manufacturing new parts. This indirectly leads to lower energy consumption and reduced emissions associated with the production of aircraft components.

4. Discussion

The study's results suggest a significant opportunity to improve both sustainability and cost efficiency in aviation through integrated LCM strategies that include Advanced AHMSs and modular designs. The successful application of these systems, as demonstrated by the collected data and the analytical frameworks developed, indicates that such integration can substantially extend the life cycle of aircraft components and reduce maintenance and operational costs.

The use of AHMSs provides real-time and predictive insights into aircraft health, leading to more proactive maintenance strategies that prevent failures before they occur. This shift not only enhances safety and reliability but also ensures cost savings by reducing unplanned downtimes and extending the operational lifespan of parts.

The modular design approach facilitates easier upgrades and replacements of components. This adaptability not only supports sustainability by allowing for longer use phases of the aircraft but also aligns with rapidly evolving technological advancements, ensuring that the aircraft remains at the forefront of operational efficiency and environmental compliance.

This research contributes to the theory of sustainable practices in the aviation industry by providing a framework that integrates technology with life cycle management. From a practical point of view, the findings offer a blueprint for aviation stakeholders to implement LCM and AHMSs in a manner that maximizes economic and environmental benefits.

The study's model of decision-making criteria further assists in assessing the viability of integrating these systems into existing and future fleets, which could serve as a valuable tool for industry decision-makers in planning and operational optimization.

The integration of LCM, AHMSs, and modular design within the aviation industry not only holds promise for enhanced economic efficiency but also significantly impacts sustainability.

One of the most direct ways in which integrated LCM contributes to sustainability is through the extension of aircraft component lifespans. By implementing AHMSs, the aviation industry can shift from reactive to predictive maintenance regimes. This shift allows for the timely identification of potential failures and wear, enabling maintenance actions before catastrophic failures occur. Such proactive management significantly reduces the need for frequent replacements and the manufacturing of new parts, thereby conserving raw materials and minimizing waste.

Modular design complements this by facilitating easier upgrades and repairs of aircraft components without necessitating complete system overhauls. This not only reduces waste but also lessens the demand for energy-intensive manufacturing processes associated with producing new components. Each component that is repaired rather than replaced represents a substantial saving in terms of both energy consumption and carbon emissions, aligning with global efforts to reduce the aviation sector's environmental impact.

The integration of LCM strategies supported by AHMSs leads to more efficient use of resources throughout the aircraft's life cycle. The data-driven insights provided by AHMSs enable airlines to optimize the use of their assets, ensuring that components are only replaced when truly necessary and that the aircraft is operating at peak efficiency. This operational efficiency translates into lower fuel consumption and reduced emissions, as aircraft that are maintained optimally tend to perform better in terms of fuel economy.

Additionally, the precise monitoring capabilities of AHMSs reduce the occurrence of unscheduled maintenance, which often involves expedited shipping of parts and tools, contributing further to carbon emissions. By minimizing these scenarios, AHMSs contribute to a more sustainable supply chain within the aviation industry.

The modular design is inherently aligned with the principles of a circular economy, which emphasizes the reuse, refurbishment, recycling, and responsible disposal of materials. By designing aircraft and their components to be modular, they can be easily disassembled at the end of their life. This facilitates more effective recycling processes, ensuring that valuable materials are reclaimed and reused, rather than discarded. The integration of modular designs in aviation thus plays a crucial role in reducing the industry's overall environmental impact, moving it toward more sustainable practices.

The transparency and traceability provided by blockchain technology, as integrated within AHMSs, ensure that the history and integrity of components are maintained throughout their life cycle. This aspect is critical in supporting a trustworthy market for used parts, further promoting the reuse and recycling of aircraft components.

There are some limitations in the current study:

- The study predominantly relied on simulated data and theoretical models to evaluate the impact of integrating LCM, AHMSs, and modular design in the aviation industry. While simulations are invaluable for predicting system behaviors under controlled settings, they may not fully capture the dynamic and unpredictable nature of real-world operations.
- The generalizability of the results may be limited as simulated environments typically simplify complex variables and interactions that occur in actual aviation operations.
- The study acknowledges the potentially high initial costs associated with implementing AHMSs and modular design but does not provide a detailed analysis of these costs across different types of aircraft and operational scales. This omission could affect stakeholders' understanding and planning for such investments.
- Implementation challenges, such as the need for extensive training, changes to existing processes, and regulatory approvals, were not deeply explored. These factors are critical for real-world applications and can significantly hinder the adoption of the proposed strategies.
- This research assumes a level of standardization in the technology and practices involved, which may not currently exist in the highly fragmented aviation industry. The lack of standardization can impede the scalability of AHMSs and modular designs, limiting their broader application.
- The adaptability of the study's findings across different regions and regulatory environments is not addressed. Regulatory disparities can influence the feasibility of implementing new technologies in global aviation markets.

The study on the integration of LCM, AHMSs, and modular design within the aviation industry has laid a robust foundation for enhancing sustainability and cost efficiency. However, several areas require further exploration to overcome the limitations identified and to extend the knowledge base:

- Future studies should incorporate real-world operational data to validate the models and simulations used in this study. This would provide a more accurate reflection of the practical implications of integrating AHMSs and modular design in aviation.
- Development of models to predict the investment needed and the potential return on investment for airlines considering the adoption of these technologies, including factors like maintenance savings, reduced downtime, and extended component lifespan.
- Development of industry-wide standards for AHMSs and modular design to facilitate broader adoption and interoperability across the aviation sector.
- Research on the scalability of these technologies in diverse regulatory and operational environments to guide global adoption strategies.

- Investigate the human factors involved in the transition to more technologically advanced maintenance and life cycle management systems, ensuring that these technologies enhance rather than complicate human performance and decision-making.

By addressing these recommendations, future research can help realize the full potential of integrating LCM with AHMSs and modular design, thereby driving forward the sustainability and efficiency of the aviation industry.

Integrating life cycle management with advanced health monitoring systems and modular design represents a forward-thinking approach to advancing sustainability and cost efficiency in aviation. As the industry continues to face pressures to reduce environmental impacts and optimize operational costs, the adoption of such integrated systems offers a promising pathway to meeting these challenges while ensuring the sector's long-term viability and alignment with global sustainability goals. This study underscores the importance of continued innovation and adaptation in aviation life cycle management practices.

5. Conclusions

The integration of LCM with AHMSs and modular design within the aviation industry represents a transformative approach that significantly enhances both sustainability and cost efficiency. The study has substantiated the dual benefits of this integration, offering a comprehensive solution to the challenges of environmental impact and operational cost management in aviation.

The adoption of AHMSs empowers proactive maintenance strategies, ensuring aircraft components maintain optimal functionality longer and reducing unexpected failures. This not only enhances the reliability and safety of aviation operations but also lowers maintenance costs by mitigating the need for frequent part replacements and extensive repairs. The study highlights that real-time monitoring and predictive maintenance capabilities inherent in AHMSs can lead to substantial cost savings and operational efficiencies.

Similarly, modular design emerges as a pivotal strategy in this integrated approach. By allowing components to be easily replaced or upgraded, modular design extends the service life of aircraft, adapts to technological advancements, and supports sustainability by minimizing waste. This design philosophy not only reduces the environmental footprint associated with the production and disposal of aircraft parts but also aligns with the principles of a circular economy.

From a practical standpoint, the frameworks developed in this study serve as valuable tools for industry stakeholders, offering actionable insights into the implementation of LCM strategies enhanced by AHMSs and modular design. These tools can guide aviation manufacturers, operators, and regulatory bodies in making informed decisions that balance cost, performance, and environmental considerations.

However, the adoption of such advanced systems is not without challenges. The initial cost of implementing AHMSs and redesigning aircraft for modularity may be substantial. Moreover, the industry faces hurdles in standardizing these technologies and ensuring they are scalable across different aircraft models and systems.

Future research should thus focus on overcoming these barriers, exploring more cost-effective ways to integrate AHMSs and modular designs, and extending this research into real-world applications to validate the long-term benefits highlighted in our study.

The study underscores the critical role of integrated LCM strategies in shaping the future of aviation, urging a shift toward more sustainable and economically feasible practices.

Author Contributions: Conceptualization, I.K.; methodology, I.K.; software, T.T., L.S. and V.S.; validation, V.P., T.T., L.S. and V.S.; formal analysis, I.K.; investigation, I.K., V.P., T.T., L.S. and V.S.; resources, V.P., T.T., L.S. and V.S.; data curation, T.T., L.S. and V.S.; writing—original draft preparation, I.K.; writing—review and editing, I.K., V.P., T.T., L.S. and V.S.; visualization, I.K., T.T., L.S. and V.S.; supervision, I.K.; project administration, I.K.; funding acquisition, I.K., V.P., T.T., L.S. and V.S. All authors have read and agreed to the published version of the manuscript.

Funding: This research received no external funding.

Institutional Review Board Statement: Not applicable.

Informed Consent Statement: Not applicable.

Data Availability Statement: The original contributions presented in the study are included in the article, further inquiries can be directed to the corresponding author.

Conflicts of Interest: Authors V.P., T.T. and L.S. were employed by the company Sky Net Technics. The remaining authors declare that the research was conducted in the absence of any commercial or financial relationships that could be construed as a potential conflict of interest.

References

1. DIN EN ISO 14040; Environmental Management—Life Cycle Assessment—Principles and Framework. Beuth Verlag GmbH: Berlin, Germany, 2006.
2. DIN EN ISO 14044; Environmental Management—Life Cycle Assessment—Requirement and Guidelines. Beuth Verlag GmbH: Berlin, Germany, 2006.
3. Herrmann, I.T.; Moltesen, A. Does it matter which Life Cycle Assessment (LCA) tool you choose?—A comparative assessment of SimaPro and GaBi. *J. Clean. Prod.* **2015**, *86*, 163–169. [\[CrossRef\]](#)
4. Lopes Silva, D.A.; Nunes, A.O.; Piekarski, C.M.; da Silva Moris, V.A.; de Souza, L.S.M.; Rodrigues, T.O. Why using different Life Cycle Assessment software tools can generate different results for the same product system? A cause–effect analysis of the problem. *Sustain. Prod. Consum.* **2019**, *20*, 304–315. [\[CrossRef\]](#)
5. Pinheiro Melo, S.; Barke, A.; Cerdas, F.; Thies, C.; Mennenga, M.; Spengler, T.S.; Herrmann, C. Sustainability Assessment and Engineering of Emerging Aircraft Technologies—Challenges, Methods and Tools. *Sustainability* **2020**, *12*, 5663. [\[CrossRef\]](#)
6. Keiser, D.; Schnoor, L.H.; Pupkes, B.; Freitag, M. Life cycle assessment in aviation: A systematic literature review of applications, methodological approaches and challenges. *J. Air Transp. Manag.* **2023**, *110*, 102418. [\[CrossRef\]](#)
7. UN Environmental Programme. Global Guidance on Environmental Life Cycle Impact Assessment Indicators (GLAM). 2023. Available online: <https://www.lifecycleinitiative.org/activities/life-cycle-assessment-data-and-methods/global-guidance-for-life-cycle-impact-assessment-indicators-and-methods-glam/> (accessed on 15 May 2024).
8. UN Environmental Programme. Global LCA Data Access Network (GLAD). 2023. Available online: <https://www.globalcadataaccess.org/> (accessed on 15 May 2024).
9. UN Environmental Programme. Global LCA Data Access Network (GLAD)—Frequently Asked Questions. 2023. Available online: <https://www.globalcadataaccess.org/faq> (accessed on 15 May 2024).
10. Karakoc, T.H.; Ekici, S.; Dalkiran, A. (Eds.) *Life Cycle Assessment in Aviation Theory and Applications*; Springer: Berlin, Germany, 2024.
11. Rahn, A.; Wicke, K.; Wende, G. Life Cycle Assessment in Aviation. Encyclopedia. Available online: <https://encyclopedia.pub/entry/27024> (accessed on 15 May 2024).
12. Pohya, A.A.; Wehrspohn, J.; Meissner, R.; Wicke, K. A Modular Framework for the Life Cycle Based Evaluation of Aircraft Technologies, Maintenance Strategies, and Operational Decision Making Using Discrete Event Simulation. *Aerospace* **2021**, *8*, 187. [\[CrossRef\]](#)
13. Ziejka, M.; Szelmanowski, A.; Pazur, A.; Kowalczyk, G. Computer Life-Cycle Management System for Avionics Software as a Tool for Supporting the Sustainable Development of Air Transport. *Sustainability* **2021**, *13*, 1547. [\[CrossRef\]](#)
14. Mazur, K.; Saleh, M.; Hornung, M. Integrating Life Cycle Assessment in Conceptual Aircraft Design: A Comparative Tool Analysis. *Aerospace* **2024**, *11*, 101. [\[CrossRef\]](#)
15. Tavares, S.M.O.; Ribeiro, J.A.; Ribeiro, B.A.; de Castro, P.M.S.T. Aircraft Structural Design and Life-Cycle Assessment through Digital Twins. *Designs* **2024**, *8*, 29. [\[CrossRef\]](#)
16. Szabo, S.; Koblen, I. Aviation Technology Life Cycle Management: Importance for Aviation Companies, Aerospace Industry Organizations and Relevant Stakeholders. *Mag. Aviat. Dev.* **2017**, *5*, 15–24. [\[CrossRef\]](#)
17. Boller, C.; Chang, F.; Fujino, Y. *Encyclopedia of Structural Health Monitoring*; John Wiley & Sons: Hoboken, NJ, USA, 2009.
18. Corcoran, J. Rate-based structural health monitoring using permanently in-installed sensors. *Proc. R. Soc. A Math. Phys. Eng. Sci.* **2017**, *473*, 20170270.
19. Rytter, A. Vibration Based Inspection of Civil Engineering Structures. Ph.D. Thesis, Aalborg University, Aalborg, Denmark, 1993.
20. Ricci, F.; Monaco, E.; Boffa, N.D.; Maio, L.; Memmolo, V. Guided waves for structural health monitoring in composites: A review and implementation strategies. *Prog. Aerosp. Sci.* **2022**, *129*, 100790. [\[CrossRef\]](#)
21. Mitra, M.; Gopalakrishnan, S. Guided wave based structural health monitoring: A review. *Smart Mater. Struct.* **2016**, *25*, 053001. [\[CrossRef\]](#)
22. Memmolo, V.; Moll, J.; Nguyen, D.H.; Krozer, V. Interaction of guided electromagnetic waves with defects emerging in metallic plates. In Proceedings of the 2021 IEEE International Workshop on Metrology for AeroSpace (MetroAeroSpace 2021), Virtual, 23–25 June 2021; pp. 552–557.
23. Kexel, C.; Moll, J. Detecting damage in rudder stocks under load using electro-mechanical susceptance: Frequency-warping and semi-supervised approaches. *J. Intell. Mater. Syst. Struct.* **2022**, *33*, 1705–1718. [\[CrossRef\]](#)

24. Ooijevaar, T. Vibration Based Structural Health Monitoring of Composite Skin-Stiffener Structures. Ph.D. Thesis, University of Twente, Enschede, The Netherlands, 2014.
25. Druet, T.; Recoquillay, A.; Chapuis, B.; Moulin, E. Passive guided wave tomography for structural health monitoring. *J. Acoust. Soc. Am.* **2019**, *146*, 2395–2403. [\[CrossRef\]](#)
26. Parodi, M.; Fiaschi, C.; Memmolo, V.; Ricci, F.; Maio, L. Interaction of Guided Waves with Delamination in a Bilayered Aluminum-Composite Pressure Vessel. *J. Mater. Eng. Perform.* **2019**, *28*, 3281–3291. [\[CrossRef\]](#)
27. Kralovec, C.; Schagerl, M. Review of Structural Health Monitoring Methods Regarding a Multi-Sensor Approach for Damage Assessment of Metal and Composite Structures. *Sensors* **2020**, *20*, 826. [\[CrossRef\]](#)
28. Memmolo, V.; Monaco, E.; Ricci, F.; Vaselli, C.; Cimminiello, N.; Salvato, P. Structural Health Monitoring of Electromechanical Actuators in Aviation—Challenges Ahead and Case Study. *J. Nondestruct. Eval.* **2022**, *5*, 041004. [\[CrossRef\]](#)
29. Tschoke, K.; Mueller, I.; Memmolo, V.; Moix-Bonet, M.; Moll, J.; Lugovtsova, Y.; Golub, M.; Venkat, R.S.; Schubert, L. Feasibility of Model-Assisted Probability of Detection Principles for Structural Health Monitoring Systems based on Guided Waves for Fibre-Reinforced Composites. *IEEE Trans. Ultrason. Ferroelectr. Freq. Control.* **2021**, *68*, 3156–3173. [\[CrossRef\]](#)
30. United States Government Accountability Office. *Aviation Safety: Status of FAA's Actions to Oversee the Safety of Composite Airplanes*; United States Government Accountability Office: Washington, DC, USA, 2011.
31. Abrate, S. *Impact on Composite Structures*; Cambridge University Press: Cambridge, UK, 1998.
32. Maio, L.; Monaco, E.; Ricci, F.; Lecce, L. Simulation of low velocity impact on composite laminates with progressive failure analysis. *Compos. Struct.* **2013**, *103*, 75–85. [\[CrossRef\]](#)
33. MIL-HDBK 17-3F; Composite Materials Handbook, Ser. Department of Defense Handbook. U.S. Department of Defense: Washington, DC, USA, 2002.
34. AC, No. 20-107B; Composite Aircraft Structures. U.S. Department of Transportation—Federal Aviation Administration: Washington, DC, USA, 2009.
35. AC, No. 25,571-1D; Damage Tolerance and Fatigue Evaluation of Structures. U.S. Department of Transportation—Federal Aviation Administration: Washington, DC, USA, 2011.
36. Fioriti, M.; Pavan, G.; Corpino, S.; Fusaro, R. Impacts of a prognostics and health management system on aircraft fleet operating cost during conceptual design phase by using parametric estimation. In Proceedings of the 5th CEAS Air & Space Conference, Delft, The Netherlands, 7–11 September 2015. Available online: <http://hdl.handle.net/11583/2627572> (accessed on 15 May 2021).
37. Leao, B.P.; Fitzgibbon, K.T.; Puttini, L.C.; de Melo, G.P. Cost-benefit analysis methodology for PHM applied to legacy commercial aircraft. In Proceedings of the 2008 IEEE Aerospace Conference, Big Sky, MT, USA, 1–8 March 2008; pp. 1–14.
38. Feldman, K.; Jazouli, T.; Sandborn, P.A. A methodology for determining the return on investment associated with prognostics and health management. *IEEE Trans. Reliab.* **2009**, *58*, 305–316. [\[CrossRef\]](#)
39. Dong, T.; Kim, N. Cost-effectiveness of structural health monitoring in fuselage maintenance of the civil aviation industry. *Aerospace* **2018**, *5*, 87. [\[CrossRef\]](#)
40. Dienel, C.; Meyer, H.; Werwer, M.; Willberg, C. Estimation of airframe weight reduction by integration of piezoelectric and guided wave-based structural health monitoring. *Struct. Health Monit.* **2018**, *18*, 1778–1788. [\[CrossRef\]](#)
41. Cusati, V.; Corcione, S.; Memmolo, V. Impact of Structural Health Monitoring on Aircraft Operating Costs by Multidisciplinary Analysis. *Sensors* **2021**, *21*, 6938. [\[CrossRef\]](#)
42. Holmberg, G. A Modular Approach to the Aircraft Product Development Capability. In Proceedings of the International Council of the Aeronautical Sciences, ICAS 2002 Congress, Toronto, ON, Canada, 8–13 September 2002; pp. 652.1–652.10. Available online: https://www.icas.org/icas_archive/icas2002/papers/652.pdf (accessed on 15 May 2024).
43. Bisanti, G.M.; Mainetti, L.; Montanaro, T.; Patrono, L.; Sergi, I. Digital Twins for Aircraft Maintenance and Operation: A Systematic Literature Review and an IoT-Enabled Modular Architecture. *Internet Things* **2023**, *24*, 100991. [\[CrossRef\]](#)
44. Livne, E. Aircraft Active Flutter Suppression: State of the Art and Technology Maturation Needs. *J. Aircr.* **2018**, *55*, 410–452. [\[CrossRef\]](#)
45. Otto, K.; Hölttä-Otto, K.; Simpson, T.W.; Krause, D.; Ripperda, S.; Ki Moon, S. Global Views on Modular Design Research: Linking Alternative Methods to Support Modular Product Family Concept Development. *J. Mech. Des.* **2016**, *138*, 071101. [\[CrossRef\]](#)
46. Atılgan, R.; Turan, Ö.; Altuntaş, Ö.; Aydın, H.; Synylo, K. Environmental Impact Assessment of a Turboprop Engine with the Aid of Exergy. *Energy* **2013**, *58*, 664–671. [\[CrossRef\]](#)
47. Vinodh, S.; Sivaraj, G.; Nithish, S.; Veeramanikandan, R. Life Cycle Assessment of an Aircraft Component: A Case Study. *Int. J. Ind. Syst. Eng.* **2017**, *27*, 485–499.
48. Şohret, Y.; Ekici, S.; Altuntaş, Ö.; Karakoc, T.H. Life Cycle Assessment of a Maintenance Process for a Training Aircraft. In Proceedings of the 8th International Exergy, Energy and Environment Symposium, IEEEES, Antalya, Turkey, 1–4 May 2016; pp. 857–860.
49. Altuntaş, Ö.; Selcuk, E.; Yalin, G.; Karakoc, T.H. Comparison of Auxiliary Power Unit (APU) and Ground Power Unit (GPU) with Life Cycle Analysis in Ground Operations: A Case Study for Domestic Flight in Turkey. *Appl. Mech. Mater.* **2014**, *629*, 219–224. [\[CrossRef\]](#)
50. Timmis, A.; Hodzic, A.; Koh, L.; Bonner, M.; Schäfer, A.; Dray, L. Lifecycle Assessment of CFRP Aircraft Fuselage. In Proceedings of the 16th European Conference on Composite Materials, ECCM, Sevilla, Spain, 22–26 June 2014.

51. Timmis, A.; Hodzic, A.; Koh, L.; Bonner, M.; Soutis, C.; Schäfer, A.; Dray, L. Environmental Impact Assessment of Aviation Emission Reduction through the Implementation of Composite Materials. *Int. J. Life Cycle Assess.* **2015**, *20*, 233–243. [\[CrossRef\]](#)
52. Böckmann, M.G.; Schmitt, R. Methodology for Ecological and Economical Aircraft Life Cycle Analysis. In *Leveraging Technology for a Sustainable World*; Dornfeld, D., Linke, B., Eds.; Springer: Berlin/Heidelberg, Germany, 2012; pp. 467–472.
53. Calado, E.A.; Leite, M.; Silva, A. Integrating Life Cycle Assessment (LCA) and Life Cycle Costing (LCC) in the Early Phases of Aircraft Structural Design: An Elevator Case Study. *Int. J. Life Cycle Assess.* **2019**, *24*, 2091–2110. [\[CrossRef\]](#)
54. Vidal, R.; Moliner, E.; Martin, P.; Fita, S.; Wonneberger, M.; Verdejo, E.; Vanfleteren, F.; Lapeña, N.; González, A. Life Cycle Assessment of Novel Aircraft Interior Panels Made from Renewable or Recyclable Polymers with Natural Fiber Reinforcements and Non-Halogenated Flame Retardants. *J. Ind. Ecol.* **2018**, *22*, 132–144. [\[CrossRef\]](#)
55. Krieg, H.; Ilg, R.; Wehner, D.; Brethauer, L. Quantifying the Environmental Potential of Lightweight Construction during Aircraft Operation through Life Cycle Assessment. In Proceedings of the 2nd International Aviation Management Conference, IAMC, Dubai, United Arab Emirates, 20–22 November 2014.
56. Johanning, A. Methodik zur Ökobilanzierung im Flugzeugvorentwurf. Master's Thesis, Technische Universität München, Munich, Germany, 2017.
57. Howe, S.; Kolios, A.; Brennan, F. Environmental Life Cycle Assessment of Commercial Passenger Jet Airlines. *Transp. Res. Part Transp. Environ.* **2013**, *19*, 34–41. [\[CrossRef\]](#)
58. Facanha, C.; Horvath, A. Environmental Assessment of Freight Transportation in the U.S. *Int. J. Life Cycle Assess.* **2006**, *11*, 229–239.
59. Chester, M.V. Life-Cycle Environmental Inventory of Passenger Transportation in the United States. Master's Thesis, University of California, Berkeley, CA, USA, 2008.
60. Cox, B. Mobility and the Energy Transition: A Life Cycle Assessment of Swiss Passenger Transport Technologies Including Developments until 2050. Master's Thesis, ETH Zurich, Zurich, Switzerland, 2018.
61. Cox, B.; Jemioło, W.; Mutel, C. Life Cycle Assessment of Air Transportation and the Swiss Commercial Air Transport Fleet. *Transp. Res. Part Transp. Environ.* **2018**, *58*, 1–13. [\[CrossRef\]](#)
62. Jemioło, W. Life Cycle Assessment of Current and Future Passenger Air Transport in Switzerland. Master's Thesis, University of Nordland, Bodø, Norway, 2015.
63. Lopes, J.V. Life Cycle Assessment of the Airbus A330-200 Aircraft. Master's Thesis, Universidade Técnica de Lisboa, Lisbon, Portugal, 2010.
64. Lewis, T. A Life Cycle Assessment of the Passenger Air Transport System Using Three Flight Scenarios. Master's Thesis, Norwegian University of Science and Technology, Trondheim, Norway, 2013.
65. Jordão, T.C. Life Cycle Assessment Oriented to Climate Change Mitigation by Aviation. In Proceedings of the 15th International Conference on Environmental Economy, Policy and International Environmental Relations, Prague, Czech Republic, November 2013.
66. Fabre, A.; Planès, T.; Delbecq, S.; Budinger, V.; Lafforgue, G. Life Cycle Assessment Models for Overall Aircraft Design. In Proceedings of the AIAA SciTech 2022 Forum, San Diego, CA, USA, 3–7 January 2022; American Institute of Aeronautics and Astronautics: Reston, VA, USA, 2022.
67. Schäfer, K. Conceptual Aircraft Design for Sustainability. Master's Thesis, RWTH Aachen, Aachen, Germany, 2018.
68. Dallara, E.; Kusnitz, J.; Bradley, M. Parametric Life Cycle Assessment for the Design of Aircraft. *SAE Int. J. Aerosp.* **2013**, *6*, 736–745. [\[CrossRef\]](#)
69. Scholz, D. *Calculation of the Emission Characteristics of Aircraft Kerosene and Hydrogen Propulsion, Version 4*; Harvard Dataverse: Cambridge, MA, USA, 2020.
70. Caers, B. *Conditions for Passenger Aircraft Minimum Fuel Consumption, Direct Operating Costs and Environmental Impact*; HAW: Hamburg, Germany, 2019.
71. Keiser, D.; Arenz, M.; Freitag, M.; Reiß, M. Method to Model the Environmental Impacts of Aircraft Cabin Configurations during the Operational Phase. *Sustainability* **2023**, *15*, 5477. [\[CrossRef\]](#)
72. Markatos, D.N.; Pantelakis, S.G. Assessment of the Impact of Material Selection on Aviation Sustainability, from a Circular Economy Perspective. *Aerospace* **2022**, *9*, 52. [\[CrossRef\]](#)
73. Filippatos, A.; Markatos, D.; Tzortzinis, G.; Abhyankar, K.; Malefaki, S.; Gude, M.; Pantelakis, S. Sustainability-Driven Design of Aircraft Composite Components. *Aerospace* **2024**, *11*, 86. [\[CrossRef\]](#)
74. Fera, M.; Abbate, R.; Caterino, M.; Manco, P.; Macchiaroli, R.; Rinaldi, M. Economic and Environmental Sustainability for Aircrafts Service Life. *Sustainability* **2020**, *12*, 10120. [\[CrossRef\]](#)
75. Freise, A. The Value of Easy-to-Use Products. In *Pictures of the Future*; Siemens: Munich, Germany, 2003; p. 65.

Disclaimer/Publisher's Note: The statements, opinions and data contained in all publications are solely those of the individual author(s) and contributor(s) and not of MDPI and/or the editor(s). MDPI and/or the editor(s) disclaim responsibility for any injury to people or property resulting from any ideas, methods, instructions or products referred to in the content.