

Article



# A Possibilistic Approach for Aggregating Customer Opinions in Product Development

## Md. Mamunur Rashid<sup>1</sup> and AMM Sharif Ullah<sup>2,\*</sup>

- <sup>1</sup> Bangladesh Institute of Management, 4 Sobhanbag, Mirpur Road, Dhanmandi Dhaka-1207, Bangladesh; mamun87245@gmail.com
- <sup>2</sup> Kitami Institute of Technology, Koen-cho 165, Kitami, Hokkaido 090-8507, Japan
- \* Correspondence: ullah@mail.kitami-it.ac.jp; Tel./Fax: +81-157-269-207

## Academic Editor: Paul G. Ranky Received: 10 December 2015; Accepted: 15 March 2016; Published: 23 March 2016

**Abstract:** One of the major tasks of product development is to collect the opinions of potential customers and to then find out the status of certain product features. The status of a product feature means whether or not it must, should, or could be included in the product, or even avoided. In doing so, a simple relative frequency-based computing approach is not sufficient. Rather, a logical computing approach is a better option. Based on this contemplation, this study describes a methodology to identify the status of a product feature in terms of must-be, should-be, or could-be categories, where the collected customer opinions are computed using a logical approach. Possibility distributions (*i.e.*, fuzzy numbers) play a significant role in the logical computation. A Kano-model-based questionnaire is employed to collect the customer opinions. Through a case study, it is demonstrated that the proposed approach is effective in dealing with both the subjectivity and controversy that the customer opinions may exhibit. The results of this study are useful for making decisions in the early stage of a product development process in a lucid manner.

Keywords: product development; customer needs; Kano model; fuzzy logic; information content

## 1. Introduction

Product development is a field of study where the activities underlying a product life cycle are studied in a concurrent manner [1–3]. The internal customers (personnel of the concerned organization) first determine the needs of the external customers (the real potential customers who will use the product for their own ends). At the same time, the internal customers suggest numerous solutions for satisfying the needs of the external customers. Therefore, a customer needs assessment and product solution identification have been two critical problems of product development and studied by numerous authors [4–18]. In certain cases, the issues of mass customization, growing and variable customer demands, and optimal mix of products have been emphasized in dealing with customer needs [4–7]. The issue of sustainability has also been integrated with the aforementioned activities [8,17]. Some authors have put an emphasis on the customer needs models, e.g., the Kano model [9], and other related issues, e.g., the issue of customer preferences aggregation [10–15,18], the issue of missing customer opinion simulation [16], and the issue of uncertainty quantification in customer needs assessment [11–15].

However, as mentioned, a product development process must start by elucidating the customer needs. The elucidated customer needs must assist the subsequent processes of product realization (design, manufacturing, and assembly). Usually, a selected segment of potential customers (hereinafter referred to as respondents) is asked to answer a set of questions. Afterward, a computational approach is applied for aggregating the respondents' answers to identify which features of the product (or a family of products) are useful and to what extent they satisfy the customers' needs.

taste and motivation of the respondents are not the same, a great deal of variability in the answers is found [16,18]. Sometimes, the answers of certain respondents are unavailable because the respondents did not answer on time or at all [13,16]. Sometimes, the answers do not make sense (*i.e.*, controversial or questionable answers). Sometimes, the answers are less informative, *i.e.*, the respondents just took a neutral position (less opinionative answers). Therefore, the frequency-based simple calculation may be misleading in aggregating the answers of the respondents. As an alternative, customer answers can logically be analyzed. This article aims to show how this can be done.

The remainder of this article is organized as follows: Section 2 describes the mathematical entities needed for the better understanding of the arguments used in this article. Section 3 describes the logical formulations by which the answers regarding customer needs are aggregated toward a decisive conclusion. Section 4 describes, and discusses the implications of, the results. Section 5 concludes this study.

#### 2. Preliminaries

This section describes the mathematical entities needed to better understand the arguments used in this article.

## 2.1. State of a Product Feature

In this study, a product feature takes one of the following states: *must-be, should-be, could-be,* and *unreliable*. A *must-be feature* means that the feature *must be included* in the product. Similarly, a *should-be feature* means that the feature *should be included* in the product. A *could-be feature* means that the feature *should be included* in the product. A *could-be feature* means that the feature *should be included* in the product. Similarly, a *should-be feature* means that the feature should be *included* in the product. Finally, an *unreliable* feature means that the feature entails controversial answers from the respondents. Therefore, the following set of states denoted as *State* = {must-be feature, should-be feature, could-be feature, unreliable feature} is considered in this study.

## 2.2. Numerical and Linguistic Truth-Value or Degree of Belief of a Feature

Let  $p(F_i, S_j)$  be a proposition of the form  $F_i$  is  $S_j$  where  $F_i$  is the *i*-th feature of a product and  $S_j \in State$ . Let *T* be a process as follows:

$$p(F_i, S_j) \xrightarrow{T} DoB(F_i, S_j)$$
(1)

The process *T* defined in Equation (1) determines the *Degree of Belief* (*DoB*) of each proposition  $p(F_i,S_j)$ , i = 1,2, ..., j = 1,...,4,  $DoB(.) \in [0,1]$ . This means that each proposition  $p(F_i,S_j)$  has a truth-value (or *DoB*) in the interval [0,1], and the process denoted as *T* determines it.

The *DoB* of a compound proposition can be determined as follows:

$$p(F_{i}, \neg S_{j}) \rightarrow 1 - DoB(F_{i}, S_{j})$$

$$p(F_{i}, S_{j}) \vee p(F_{i}, S_{k}) \rightarrow \max(DoB(F_{i}, S_{j}), DoB(F_{i}, S_{k}))$$

$$p(F_{i}, h \cdot S_{j}) \rightarrow \sqrt{DoB(F_{i}, S_{j})}$$
(2)

In Equation (2),  $S_k$  is a state drawn from *State*, and *h* is a hedge called "more or less" or "somewhat."

However, the truth-value or *DoB* of the above-mentioned propositions can be assigned either numerically or linguistically. The description is as follows.

Let  $F_i$  be sedan (a feature of a car), *i.e.*,  $F_i$  = sedan. Using the states defined in *State*, the following four propositions can be considered:  $p_1$ (sedan, must-be feature),  $p_2$ (sedan, should-be feature),  $p_3$ (sedan, could-be feature), and  $p_4$ (sedan, unreliable feature). A numerical value that lies in the interval [0, 1] can be assigned to each proposition subjectively or following a computation approach as its truth-value or *DoB*. Let, for instance, *DoB*s of the propositions be *DoB*(sedan, must-be feature) = 0.2, *DoB*(sedan, should-be feature) = 0.7, *DoB*(sedan, could-be feature) = 0.95, and *DoB*(sedan, unreliable feature) = 0.05.

Linguistically, DoB = 0.2 means that "it is quite false that sedan is a must-be feature of a car," *i.e.*, DoB = 0.2 refers to a linguistic truth-value "quite false." Similarly, DoB = 0.7 means that "it is somewhat true that sedan is a should-be feature of a car," *i.e.*, DoB = 0.7 refers to a linguistic truth-value "somewhat true." Similarly, DoB = 0.95 means that "it is mostly true that sedan is a could-be feature of a car," *i.e.*, DoB = 0.7 refers to a linguistic truth-value "somewhat true." Similarly, DoB = 0.95 means that "it is mostly true that sedan is a could-be feature of a car," *i.e.*, DoB = 0.95 refers to a linguistic truth-value "mostly true." Finally, DoB = 0.05 means that "it is mostly false that the opinions obtained on the car feature called sedan is unreliable," *i.e.*, DoB = 0.05 refers to a linguistic truth-value "mostly false."

Thus, a crisp *DoB*, *i.e.*, a numerical value in the interval [0, 1], can be interpreted in terms of a linguistic expression (e.g., mostly false, somewhat true, and alike), which is referred to as linguistic truth-value. This means that a linguistic truth-value of a crisp *DoB* is its linguistic interpretation or counterpart. The linguistic counterpart (L(c)) of a crisp *DoB* ( $c = DoB(F_{i,r})$ ) is given as

$$c = DoB(F_i, .) \max_{i=1,2} (DoB(LT_i(c))) \to L(c)$$
(3)

Using a set of fuzzy numbers defined in the universe of discourse [0, 1], the linguistic truth-values  $LT_i$ , i = 1, 2, ... can be defined. In this study, a set of seven linguistic truth-values are considered that are given by the membership functions (or *DoBs*) of the seven fuzzy numbers [16,19–22] labeled "mostly false (*mf*)," "quite false (*qf*)," "somewhat false (*sf*)," "neither true nor false (*tf*)," "somewhat true (*st*)," "quite true (*qt*)," and "mostly true (*mt*)." The membership functions are illustrated in Figure 1.



Figure 1. Linguistic truth-values.

The definitions of the membership functions shown in Figure 1 are as follows:

$$DoB_{mf}(c) = \max\left(0, \min\left(1, \frac{0.1 - c}{0.1 - 0}\right)\right)$$
(4)

$$DoB_{qf}(c) = \max\left(0, \min\left(\frac{c-0}{0.1-0}, \frac{0.3-c}{0.3-0.1}\right)\right)$$
(5)

$$DoB_{sf}(c) = \max\left(0, \min\left(\frac{c - 0.1}{0.3 - 0.1}, \frac{0.5 - c}{0.5 - 0.3}\right)\right)$$
(6)

$$DoB_{tf}(c) = \max\left(0, \min\left(\frac{c - 0.3}{0.5 - 0.3}, \frac{0.7 - c}{0.7 - 0.5}\right)\right)$$
(7)

$$DoB_{st}(c) = \max\left(0, \min\left(\frac{c - 0.5}{0.7 - 0.5}, \frac{0.9 - c}{0.9 - 0.7}\right)\right)$$
(8)

$$DoB_{qt}(c) = \max\left(0, \min\left(\frac{c - 0.7}{0.9 - 0.7}, \frac{1 - c}{1 - 0.9}\right)\right)$$
(9)

$$DoB_{mt}(c) = \max\left(0, \min\left(1, \frac{c - 0.9}{1 - 0.9}\right)\right)$$
(10)

In Equations (4)–(10), a numerical truth-value is denoted as c, *i.e.*,  $c \in [0, 1]$ . Let the linguistic counterpart of c be L(c). If the condition underlying Equation (1) is applied, then the linguistic counterpart of  $c \in [0, 0.05]$  is mostly false (*mf*). Similarly, the linguistic counterpart of  $c \in (0.05, 0.2]$  is quite false (*qf*). The linguistic counterpart of  $c \in (0.2, 0.4]$  is somewhat false (*sf*). The linguistic counterpart of  $c \in (0.4, 0.6]$  is neither true nor false (*tf*). The linguistic counterpart of  $c \in (0.6, 0.8]$  is somewhat true (*st*). The linguistic counterpart of  $c \in (0.8, 0.95]$  is quite true (*qt*). Finally, the linguistic counterpart of  $c \in (0.95, 1]$  is mostly true (*mt*). A linguistic counterpart of c, as described above, has an expected (crisp) value denoted as E(L(c)) that is often calculated by the centroid method. The expected values of the linguistic true-values shown in Figure 1 are as follows: E(mf(c)) = 0.033, E(af(c)) = 0.133, E(sf(c)) = 0.3, E(tf(c)) = 0.5, E(st(c)) = 0.7, E(qt(c)) = 0.867, and E(mt(c)) = 0.967, according to the centroid method.

#### 3. Logical Aggregation Process

Based on the concept of possibility [19–25] and the formulations described in Sections 2 and 3 this section describes the logical processes (*i.e.*, *T* defined in Equation (1)) needed to aggregate the answers of the respondents. The goal is to determine the state of a product feature taking a state from *State*. The aggregation process relies on *DoBs*, as defined in Equation (1). The *DoBs* can also be processed by the formulations in Equations (2) and (3) and thereby the formulations in Equations (4)–(10). Since the answers of the respondents are obtained by using a definite customer needs model, the logical formulations must be consistent with an underlying customer needs model. This means that the logical aggregation processes are customer-needs-model dependent. In this study, the Kano model [9,16,18] is used to obtain the answers of the respondents are considered in this study.

#### 3.1. The Kano Model

As mentioned, in this study to obtain customer opinion a customer needs model called the Kano model [9,16,18] is used. This subsection describes this model. It consists of both a classification scheme of customer needs and a matrix defining the relations among different types of customer needs. These two constituents of the Kano model are described in Figure 2 and Table 1.

As shown from Figure 2 and Table 1, the Kano model classifies a product feature  $F_i$  into one of the following types: *Class* = {One-dimensional (O), Attractive (A), Must-be (M), Indifferent (I), Reverse (R), Questionable (Q)}. As seen from Figure 2, a feature is considered *Must-be* if its absence produces absolute dissatisfaction, and its presence does not increase the satisfaction. A feature is considered *One-dimensional* if its fulfillment helps increase the satisfaction and *vice versa*. A feature is considered *Attractive* if it leads to a greater satisfaction but is not expected to be in the product. A feature is considered *Indifferent* if its presence or absence does not contribute to the customers' satisfaction. A feature is considered *Reverse* if its presence causes dissatisfaction and *vice versa* [10,19,26]. To know whether  $F_i$  is one of the classes drawn from *Class*, a respondent needs to answer two questions. One of the questions deals with the scenario that refers to  $F_i$  being present in the product, and the other deals with the scenario that refers to  $F_i$  being present in the product. The respondent needs to choose an answer drawn from *Answer* = {Like, Must-be, Neutral, Live-with, Dislike} for both questions [16,18]. The relationship between the two-answer and classification is listed in Table 1 [16,18]. Note the row and column in Table 1 marked by dark colors that refer to the answer called Neutral for both cases (Present and Not Present).



Figure 2. The Kano model [16].

**Table 1.** Classification of  $F_i$  based on present-not-present answers [16].

Procent (1)	Not Present				
Tiesent (↓)	Like	Must-be	Neutral	Live-with	Dislike
Like	Q	А	А	А	0
Must-be	R	Ι	Ι	Ι	М
Neutral	R	Ι	Ι	Ι	М
Live-with	R	Ι	Ι	Ι	М
Dislike	R	R	R	R	Q

#### 3.2. Probability-Possibility Transformation

There is a relationship between the concept of *probability* and *possibility*, and the degree of possibility can be interpreted in terms of probability and *vice versa* [19–25]. In this study, the concept of probability means a relative frequency-based probability. However, if we know the answers of the respondents, we know the relative frequencies of a feature  $F_i$  in terms of O, A, M, I, R, and Q. A relative frequency denoted as  $f_r(F_i, C_k)$  of a feature  $F_i$  in terms of  $C_k \in \{O, A, M, I, R, Q\}$  is not the truth-value or *DoB* of the proposition " $F_i$  is  $C_k$ ". It is possible to determine the *DoB* using the information of the relative frequency. To do this, the probability-possibility consistency principle can be used [19–25]. The probability-possibility consistency principle implies that the degree of possibility (or degree of belief) is always greater than or equal to the degree of probability, *i.e.*, what is probable must be possible with a higher or equal degree of possibility, *prob*(.)  $\leq \pi$ (.). The degree of probability, *prob*(.), is, in fact, the *Degree of Belief* (*DoB*) or truth-value of a proposition [20–22]. The degree of probability, *prob*(.), is difficult to determine and in most real-life cases, the relative frequencies are taken as an estimation of the degree of probability. Based on this contemplation, the *DoB* of  $C_k$  is given as

$$DoB(F_{i}, C_{k}) = \frac{f_{r}(F_{i}, C_{k})}{\max_{k=1,\dots,6} (f_{r}(F_{i}, C_{k}))}$$
(11)

In Equation (4),  $f_r(F_i,C_k)$  denotes the relative frequency of the classification  $C_k$  for the feature  $F_i$ . Since max( $f_r(F_i,C_k) \mid \forall k = 1, ..., 6) \leq 1$ ,  $DoB(F_i,C_k) \geq f_r(F_i,C_k)$  ( $\approx prob(F_i,C_k)$ ), *i.e.*, the

probability-possibility consistency principle holds if the Equation (4) is used. Other formulations of probability-possibility transformation are not considered in this study.

#### 3.3. Logical Transformation

Using  $DoB(F_i,C_k)$ , it is possible to find out the DoBs of the members of *State* (must be included, should be included, and unreliable). In doing so, it is important to understand the semantics of the classifications in Table 1 as follows:

As described above, if a feature is classified as One-dimensional (O) or Must-be (M) and it is not included in the product, then the customers are not satisfied. Therefore, that a feature "must be included" in the product means that it is "either O or M." This leads to the following formulation:

$$F_i \text{ is a must be feature} \to (F_i \text{ is } O) \lor (F_i \text{ is } M)$$

$$DoB(F_i, must be feature) = \max(DoB(F_i, O), DoB(F_i, M))$$
(12)

On the other hand, if a feature is classified as Attractive (A), it is an unexpected but customer-satisfaction-enriching feature. Thus, it "should be included" in the product to increase the level of customer satisfaction. This yields the following formulation:

$$F_i \text{ is a should be feature} \to (F_i \text{ is } A)$$

$$DoB(F_i, \text{ should be feature}) = DoB(F_i, A)$$
(13)

If a feature is classified as Indifferent (I), it is not helpful for increasing customer satisfaction. In addition, if the feature is Reverse (R), its inclusion in the product creates a great deal of dissatisfaction. This means that, if a feature is "not I or not R," it could be included in the product. This yields the following formulation:

$$F_{i} \text{ is a could be feature} \rightarrow (F_{i} \text{ is } \neg I) \lor (F_{i} \text{ is } \neg R)$$

$$DoB(F_{i}, \text{ could be feature}) = \max((1 - DoB(F_{i}, I)), (1 - DoB(F_{i}, R)))$$
(14)

Lastly, if a feature is classified as Questionable (Q), then the answer does not make sense, *i.e.*, the answer is unreliable. From this viewpoint, a feature is unreliable means that it is classified as Q. This yields the following formulation:

$$F_i \text{ is a unreliable feature} \to F_i \text{ is } Q$$

$$DoB(F_i, unreliable feature) = DoB(F_i, Q)$$
(15)

## 4. Results and Discussions

This section describes how the logical formulation described in the previous sections has been implemented to deal with the customer needs. For the implementation, a customer needs aggregation framework is considered, as illustrated in Figure 3.

As seen from Figure 3, seven steps underlie the aggregation process. The steps are described as follows.

- Step 1 Considering plausible product features (e.g., the features called Sedan, SUV, and Van for a product called car) and a customer needs model (e.g., the Kano model)
- Step 2 Developing a questionnaire
- Step 3 Sending the developed questionnaire to certain respondents
- Step 4 Collecting the respondents' opinions based on the developed questionnaire
- Step 5 Performing logical aggregation through the Degree of Belief (DoB) of all features in terms of must-be, should-be, and could-be features

- Step 6 Ranking the features based on the compliance analysis using the quantity called certainty and requirement compliances denoted as CC and RC, respectively
- Step 7 Making final decision on the features



Figure 3. Customer needs aggregation framework.

#### 4.1. Implementation

This subsection describes the results obtained by executing the aforementioned seven steps. The results obtained by executing Steps 1–5 are described first, which is followed by the descriptions of the results obtained by executing the Steps 6–7.

### 4.1.1. Execution of Steps 1–5

A total of 100 respondents were asked to answer a set of questions. The questions deal with different aspects of a small passenger vehicle. Certain questions were formatted using the present-not-present style of questioning as shown in Table 1.

The results related to three features, namely, Sedan, SUV, and Van, are reported in this article. Needless to say, the questions regarding these features were formulated using a present-not-present style of questioning, as shown in Table 1. The study was conducted in Bangladesh in the months of December 2011–March 2012. The answers of the 50 respondents selected at random out of 100 responded have been analyzed for this study. A plot in Figure 4 shows the relative frequencies of Sedan, SUV, and Van, *i.e.*, the product features considered.

Consider first the relative frequencies of Sedan shown in Figure 4. Most of the respondents consider Sedan to be an *indifferent* (I) feature. This conclusion does not make sense because a large number of customers in Bangladesh prefer to use sedans and are quite satisfied with sedan-type vehicles. Consider the relative frequencies of SUV, as shown in Figure 4. Similar to the previous case,

most of the respondents consider SUV to be an *indifferent* (I) feature. This conclusion also does not make any sense because numerous vehicle users prefer SUVs due to the suboptimal road conditions in Bangladesh. According to the relative frequencies shown in Figure 4, Van is a *reverse* feature, *i.e.*, most of the respondents hate this type of vehicle. This conclusion is somewhat unrealistic because certain users prefer vans because it helps them travel with a large family—a common scenario in Bangladesh. Therefore, it is not appropriate to make a decision based on the relative frequency, as mentioned above.



Figure 4. Relative frequencies of the members of Class.

The alternative is to use the logical process as described in the previous sections. To apply the logical process, first, the *DoBs* of Sedan, SUV, and Van were determined, as shown in Figure 5. To do this, the procedure defined in Equation (11) was used. Afterwards, the *DoBs* of the statuses (see *State* in Section 2) of the features Sedan, Van, and SUV were calculated, as shown in Figure 6, using the procedure defined in Equations (12)–(15). The *DoBs* shown in Figure 6 can be used to make a final decision by executing the steps 6–7, as described in the following subsection.



Figure 5. DoBs of the members of Class.



Figure 6. *DoBs* of the members of *State*.

#### 4.1.2. Execution of Steps 6–7

The final evaluation of the features called Sedan, SUV, and Van was done based on the concept of information content for the multi-valued logical situations (a situation similar to that of this study). The information content means here an ordered-pair (*CC*, *RC*), which has been found effective in quantifying the epistemic uncertainty in design [16,26–28]. The results are summarized in Table 2. The values of (*CC*, *RC*) listed in Table 2 underlie the following calculation process.

$\mathbf{P}_{\mathbf{a}}$ and $\mathbf{r}_{\mathbf{a}}$ and $(\mathbf{P}_{\mathbf{a}})$		X	
Kequirement (K <sub>E</sub> )	Sedan	SUV	Van
X must be included	(0.533, 0)	(0.383, 0)	(0.216, 0.88)
X should be included	(0.533, 0.772)	(0.383, 0.32)	(0.216, 0.88)
X could be included	(0.533, 0.5)	(0.383, 0.32)	(0.216, 0)
X somewhat should be included	(0.533, 0.435)	(0.383, 0.156)	(0.216, 0.602)
X must be or should be included	(0.533, 0.0)	(0.383, 0)	(0.216, 0.88)
-		(CC, RC)	

Table 2. Information content of the features.

In this study, *CC* is called the certainty compliance that measures the variability in the *DoBs* of the members of *State* for a given feature (Sedan, SUV, or Van) and *RC* is called the requirement compliance that quantifies the degree of fulfillment of a given requirement. In particular, one of the following propositions ( $R_E$ ) sets the requirement: *X* is a *must-be* included feature, *X* is a *should-be* included feature, *X* is a *could-be* included feature, *X* is a *somewhat should-be* included feature, and *X* is a *must-be* or *should-be* included feature. The user interface of a system, presented elsewhere [26,27] and shown in Figure 7, is used to calculate the information content in terms of (*CC*, *RC*). In this system, the information content in terms of (*CC*, *RC*) is defined as follows.



Figure 7. Determining information content of the states.

$$CC(F_i) = \frac{\sum_{j=1}^{4} I_c(DoB(F_i, S_j))}{4} \quad so that \quad I_c = \begin{cases} \frac{DoB - 0}{0.5 - 0} & DoB < 0.5\\ \frac{1 - DoB}{1 - 0.5} & otherwise \end{cases}$$
(16)  
$$RC(F_i) = \begin{cases} 0 & d > a\\ 1 & d < b\\ \frac{a - d}{a - b} & otherwise \end{cases}$$
(17)

so that

$$d = DoB(R_E) \quad a = \max_{j=1\dots4} (DoB(F_i, S_j)) \quad b = \min_{j=1\dots4} (DoB(F_i, S_j))$$

As defined in Equations (16) and (17), the values of  $DoB(F_i,S_j)$  and  $DoB(R_E)$  are needed for calculating the values of *CC* and *RC* for each feature  $F_j \in \{\text{Sedan}, \text{SUV}, \text{Van}\}$ . In doing so, the numerical degrees of beliefs shown in Figure 6 are first converted to their respective linguistic counterparts, as described in Section 2.2. The expected values of the respective linguistic truth-values based on the centriod method (*E*(.), see Section 2.2) are considered the degrees of belief of the respective features and used while executing Equations (16) and (17). Therefore, the *DoBs* corresponding to Equations (16) and (17) refer to the expected values of the linguistic counterparts of the *DoB* shown in Figure 6. For example, consider the feature called SUV. For SUV, the linguistic truth-value of *must-be included* is mostly true (*mt*) because its numerical truth-value is equal to 1 (Figure 6), which belongs to the linguistic truth-value called mostly true more than it belongs to other linguistic truth-values, as illustrated in Figure 1. Since the expected value of mostly true (*mt*) is E(mt) = 0.967 (based on the centriod method), this value is considered the degree  $DoB(F_i = \text{SUV}, S_j = \text{must-be included})$  of SUV when it is a must-be included feature.

Recall Table 2, which lists the information content of the three features for different requirements  $(R_E)$ . The results listed in Table 2 are also plotted in Figure 8. As seen from Figure 8, the variability in the information content of SUV is low compared to those of Sedan and Van. Van exhibits low information content when it is considered *could-be included* feature. When the requirement is set to *must-be included* 

*feature* or *should-be included* feature, Sedan's information content becomes low. The same nature is seen for the feature called SUV. As such, the customers in Bangladesh prefer SUV and Sedan more than they prefer Van. SUV and Sedan must be included in the passenger vehicle population. On the other hand, Van could be included in the passenger vehicle population but not as many as SUV and Sedan. This decision is schematically illustrated in Figure 9.



Figure 8. Variability in the information content.



Figure 9. Relative positions of features.

The above results imply that the presented logical aggregation process leads to a reliable conclusion and is thereby effective in making decisions in the early stages of the product development process.

## 5. Concluding Remarks

To deal with the intrinsic complexity of customer needs, the logical aggregation of customer opinions is a better choice compared to that of a relative frequency-based analysis. This faculty of thought is demonstrated to be true by logically aggregating the field data of customer needs collected from Bangladesh regarding small passenger vehicles. Here, the concept of possibility plays a vital role rather than the concept of probability. Thus, multi-valued logic or fuzzy logic plays an important role in the computation. For the sake of a clearer understanding, customer opinion data was obtained using a Kano-model-based questionnaire. One may reformulate the logical operations to define the categories (must-be, should-be, could-be, and unreliable) in accordance with the underlying customer

needs model. Further studies can be carried out to customize the methodology presented in this study for other customer needs models.

**Author Contributions:** Md. Mamunur Rashid and AMM Sharif Ullah formulated the Introduction section. AMM Sharif Ullah formulated the Preliminaries section. Md. Mamunur Rashid and AMM Sharif Ullah formulated the Logical Aggregation section. Md. Mamunur Rashid formulated the Results and Discussions section. AMM Sharif Ullah wrote the paper.

Conflicts of Interest: The authors declare no conflict of interest.

## References

- 1. Dieter, G.E.; Schmidt, L.C. Engineering Design, 4th ed.; McGraw-Hill: New York, NY, USA, 2009.
- 2. Kahn, K.B. The PDMA Handbook of New Product Development, 2nd ed.; Wiley: New York, NY, USA, 2004.
- 3. Ming, X.G.; Yan, J.Q.; Lu, W.F.; Ma, D.Z. Technology Solutions for Collaborative Product Lifecycle Management Status Review and Future Trend. *Concurr. Eng.* **2005**, *13*, 311–319. [CrossRef]
- 4. Jiao, J.; Zhang, L.; Pokharel, S. Process Platform Planning for Variety Coordination from Design to Production in Mass Customisation Manufacturing. *IEEE Trans. Eng. Manag.* **2007**, *54*, 112–129. [CrossRef]
- 5. Jiao, J.; Helander, M. Development of an Electronic Configure-to-Order Platform for Customised Product Development. *Comput. Ind.* 2006, *57*, 231–244. [CrossRef]
- 6. Jiao, J.; Zhang, Y. Product Portfolio Planning with Customer-Engineering Interaction. *IIE Trans.* 2005, *37*, 801–814. [CrossRef]
- Jin, J.; Ji, P.; Kwong, C.P. What makes consumers unsatisfied with your products. *J. Eng. Appl. Artif. Intell.* 2016, 47, 38–48. [CrossRef]
- 8. Kong, F.; Ming, X.G.; Wang, L.; Wang, P.; Zuo, H.; He, L. An integrated modularity approach for green product development. *Int. J. Environ. Technol. Manag.* **2011**, *14*, 397–416. [CrossRef]
- 9. Kano, N.; Seraku, N.; Takahashi, F.; Tsuji, S. Attractive quality and must-be quality. *Hinshitsu* **1984**, *14*, 39–48. (In Japanese)
- Meng, Q.L.; Jiang, X.; Bian, L.L. A Decision-Making Method for Improving Logistics Services Quality by Integrating Fuzzy Kano Model with Importance-Performance Analysis. *J. Serv. Sci. Manag.* 2015, *8*, 322–331. [CrossRef]
- 11. Meng, Q.L.; Jiang, X.; He, L.; Guo, X. Integrating Fuzzy Theory into Kano Model for Classification of Service Quality Elements: A Case Study of Machinery Industry in China. *J. Ind. Eng. Manag.* **2015**, *8*, 1661–1675.
- 12. Rashid, M.M.; Tamaki, J.; Ullah, A.M.M.S.; Kubo, A. A Numerical Kano Model for Compliance Customer Needs with Product Development. *Ind. Eng. Manag. Syst. Int. J.* **2011**, *10*, 140–153. [CrossRef]
- Rashid, M.M.; Tamaki, J.; Ullah, A.M.M.S.; Kubo, A. A Virtual Customer Needs System for Product Development. In Proceedings of the 2010 Annual Meeting of Japan Society for Precision Engineering, Sapporo, Japan, 4 September 2010; pp. 53–54.
- Rashid, M.M.; Ullah, A.M.M.S.; Sarker, M.A.R.; Tamaki, J.; Kubo, A. Logical Aggregation of Customer Needs Assessment. In Proceedings of the Fifth International Symposium on Computational Intelligence and Industrial Applications (ISCIIA2012), Sapporo, Japan, 20–26 August 2012.
- Rashid, M.M.; Ullah, A.M.M.S.; Tamaki, J.; Sarker, M.A.R. Epistemic Uncertainty Study of the Conceptual Phase of Product Development by Multi-Valued Logic and Information Content. In Proceedings of the International Conference on Mechanical, Industrial and Materials Engineering 2013 (ICMIME2013), RUET, Rajshahi, Bangladesh, 1–3 November 2013.
- 16. Ullah, A.M.M.S.; Tamaki, J. Analysis of Kano-Model-Based Customer Needs for Product Development. *Syst. Eng.* **2011**, *14*, 154–172. [CrossRef]
- 17. Wang, P.; Ming, X.G.; Li, D.; Wu, Z.; Xu, Z.; Song, W. Achieving sustainability through product-service life cycle management. *Int. J. Environ. Technol. Manag.* **2011**, *14*, 516–530. [CrossRef]
- 18. Xu, Q.; Jiao, R.J.; Yang, X.; Helander, M.; Khalid, H.M.; Opperud, A. An analytical Kano model for customer need analysis. *Des. Stud.* **2009**, *30*, 87–110. [CrossRef]
- 19. Dubois, D.; Prade, H. *Possibility Theory: An Approach to Computerized Processing of Uncertainty*; Plenum Press: New York, NY, USA, 1988.
- 20. Dubois, D.; Foulloy, L.; Mauris, G.; Prade, H. Probability-Possibility Transformations, Triangular Fuzzy Sets, and Probabilistic Inequalities. *Reliab. Comput.* **2004**, *10*, 273–294. [CrossRef]

- 21. Ullah, A.M.M.S.; Shamsuzzaman, M. Fuzzy Monte Carlo Simulation using Point-Cloud-Based Probability-Possibility Transformation. *Simulation* **2013**, *89*, 860–875. [CrossRef]
- 22. Zadeh, L.A. Fuzzy sets as a basis for a theory of possibility. Fuzzy Sets Syst. 1978, 1, 3–28. [CrossRef]
- 23. Klir, G.J. On fuzzy-set interpretation of possibility theory. Fuzzy Sets Syst. 1999, 108, 263–273. [CrossRef]
- 24. Mauris, G. Possibility distributions: A unified representation of usual direct-probability-based parameter estimation methods. *Int. J. Approx. Reason.* **2011**, *52*, 1232–1242. [CrossRef]
- 25. Yamada, K. A Study on Probability-Possibility Transformation Methods Based on Evidence Theory. J. Jpn. Soc. Fuzzy Theory Syst. 2001, 13, 302–312. (In Japanese)
- 26. Ullah, A.M.M.S.; Harib, K.H. An Intelligent Method for Selecting Optimal Materials and Its Application. *Adv. Eng. Inform.* **2008**, *22*, 473–483. [CrossRef]
- 27. Ullah, A.M.M.S.; Harib, K.H.; Al-Awar, A. *Minimizing Information Content of a Design using Compliance Analysis*; SAE Technical Paper 2007-01-1209; SAE International: Warrendale, PA, USA, 2007.
- 28. Ullah, A.M.M.S.; Rashid, M.M.; Tamaki, J. On Some Unique Features of C-K Theory of Design. *CIRP J. Manuf. Sci. Technol.* **2012**, *5*, 55–66. [CrossRef]



© 2016 by the authors; licensee MDPI, Basel, Switzerland. This article is an open access article distributed under the terms and conditions of the Creative Commons by Attribution (CC-BY) license (http://creativecommons.org/licenses/by/4.0/).